

Subject Index

A

Aluminum, 294
Arc deformation, 68
ASTM standards
 F 28, 88, 268

B

Boron, 199
 iron-boron, 47, 59, 80, 206,
 294
 iron-boron, and electron
 trapping, 68
 iron-boron, measurement
 method capability, 206
Bulk lifetime, 5, 80, 101

C

Carrier decay, excess minority,
 88, 101
Carrier injection levels, 206
Carrier lifetime, 47, 259, 268, 367
 characteristics, 268
 effective, 80, 156
 factors influencing, 206
 measurements, 47
 minority, 147, 199, 328, 347
 Czochralski silicon, 226,
 250
 Elymat technique, 101, 112
 temperature dependence, 68
 photoconductivity decay
 determination, 168
 silicon surface, 147
Chemical mechanical polishing,
 168
Chemical passivation, 268
Chemical purity, 283
Chromium, 206
 chromium-boron, 59, 206
Cobalt, 206
Copper, 18, 259, 294
Corona charge, 80

Crystals
 growth, 318
 multicrystals, 88

D

Damage, subsurface, 168
Decontamination monitoring,
 250
Defect introduction, rapid
 thermal processing, 250
Denuded zone, 305
Diffusion length, 305, 318, 367
 data, wafers exposed to
 cleans, 283
 effective carrier, 88
 minority carrier, 5, 30, 112,
 328
 sample preparation impact
 on, 185
 setup impact on, 185
 surface photovoltage, 125,
 199
 transition metals effect on, 18
Diffusion, metallic
 contamination, 219

E

Electron/hole lifetime, 68
Elymat technique, 30, 101, 112,
 226, 283, 305
Energy level, impurity, 5
Epitaxial, 47
 growth, 318
 layers, 268

F

Finite element method, 88
Frequency, high modulation,
 method, 147
Frequency resolved
 photoconductance, 68

G

Gate oxide integrity, 168
 Geometry effect, 88
 Gettering, 226, 250, 268, 318
 intrinsic, 168
 Gold, 206
 Grain boundary recombination,
 88

I

Impurity densities, 5
 Impurity identification, 59, 80
 Injection level, 125, 206, 259, 305
 analysis, 101
 control, 226
 influence of, 80
 iron-boron effects, comparison
 by, 59
 lifetime dependence on, 5
 Lorentzian amplitude
 dependence on, 68
 role of, 30
 search, 112
 Interface trap density, 47
 Iodine-ethanol chemical
 passivation technique, 268
 Iron, 18, 68, 168
 bulk concentration, 185
 chemical nature identification,
 101
 concentration measurement,
 125, 199, 259
 contamination, effect on
 lifetime, 294
 contamination, wafer handling,
 219
 energy level, 5
 gettering capability, 268
 high injection level region,
 259
 iron-boron, 47, 59, 80, 206,
 294
 iron-boron, and electron
 trapping, 68
 iron-boron, measurement
 method capability,
 206
 measurement comparison, 199
 segregation, 30

L

Lattice microdefects, 18
 Light illumination, 59

M

Metallic impurities, identifying,
 59
 Metal silicide precipitates, 101
 Metals (See also specific types)
 contamination, 156, 294
 contamination, correlation
 with particle
 contamination, 219
 contamination, intentional,
 185
 electrolytical metal tracer, 305
 impurities, effect on lifetime,
 294
 impurities, effects of, 347
 impurities, identifying, 59
 silicide precipitates, 101
 transition, 18, 59, 226, 318
 wafer handling
 contamination, 219
 Microdefects, 18, 125
 bulk, 305
 Microwave reflectance,
 photoconductivity decay
 by, 347
 Minority carrier decay, excess, 88
 Minority carrier diffusion length,
 5, 30, 305, 328
 degradation, 18
 imaging technique, 112
 surface photovoltage method,
 125
 Minority carrier lifetime, 147,
 199, 328, 347
 Czochralski silicon, 226, 250
 Elymat technique, 101, 112
 temperature dependence, 68
 Mirror polishing, 168
 Modulated photocurrent, 156
 Molybdenum, 47, 168

N

Nelder-Mead nonlinear fitting
 method, 250
 Nickel, 294

Nitrogen, 259
Non-contact measurement,
147
Nonlinear simplex fitting
procedure, 68

O

Optical excitation effect, 59
Oxygen concentrations, 199
Oxygen levels, 185
Oxygen precipitates, 30, 101,
226, 268, 318
characterization, 305

P

Particle contamination, 219
Passivation, 250, 259, 318
chemical, 268
surface, 80, 206, 367
Photoconductance decay, 185,
250
Photoconductance, frequency
resolved, 68
Photoconductive decay, 168, 206
ASTM F 28, 88, 268
comparison, surface
photovoltage
methods, 185, 199,
206
correlation with other
methods, 30, 259
geometry effects on, 88
laser microwave, 68, 250
microwave, 47, 59, 80, 226,
294
microwave reflectance, 347
sample inhomogeneity effects
on, 88
Photoconductivity amplitude
signal, 168
Photocurrent, modulated, 156
Photoluminescence technique,
laser excited, 268
Photovoltaics, 18
solar cell, wafers for, 367
Point defects, 226
Primary mode lifetime, 347

R

Resistivity
characteristics, 112
values, microwave reflectance
test, 347

S

SEMI, solar silicon
standardization, 367
Slip dislocations, 250
Solar silicon, 367
Spatial nonuniformities, 328
Spectroscopy, deep level transient,
199, 259, 294
Statistical process control, 156
Surface charge analyzer, 156
Surface contamination, 156
Surface electrical properties, 185
Surface inversion layers, 47
Surface passivation, 80, 206, 367
Surface photovoltage, 156
comparison, photoconductive
decay methods, 185,
199, 206
correlation with other
methods, 30, 259
diffusion length, 199
high modulation frequency,
147
metal contamination
characterization,
219, 294
method status, 125
theoretical basis, 185
Surface recombination, 5, 88
velocity, 5, 168, 185, 226,
328
chemical passivation
technique, 268
measurement issues, 156
metal silicide precipitate
relation, 101
reduction, 80
temperature dependence,
68

T

Thermal processing, 318
rapid, 250

392 RECOMBINATION LIFETIME MEASUREMENTS FOR SILICON

Thermal treatment, 283

Titanium, 59

Trapping centers, 68

U

Ultraviolet/millimeter wave
technique, 168

V

Velocity, surface recombination,
5, 168, 185, 226, 328

chemical passivation
technique, 268

measurement issues, 156

metal silicide precipitate

relation, 101

reduction, 80

temperature dependence, 68

W

Wet chemical process
cleaning, 283

X

X-ray fluorescence, total
reflection, 30

X-ray topography, 250