

Subject Index

A

- AATC (*see* American Association of Textile Chemists and Colorists)
- Acetone, permeation rate, 90
- Adsorption, 39
- Advanced gas-cooled nuclear reactor, working environment (*see also* Thermal protective clothing, dynamically insulated), 536
- Agricultural worker, 95
- Air blast applicators, use of protective clothing and equipment with, 104, 111
- Air permeability, 151
- Air thermometer, 379
- Alcohol, permeation in hairless mouse, 230
- Allergenic substances, 246
- Aluminized coats, 475, 482
- Aluminized fabrics, molten iron splash protection (*see also* Asbestos, aluminized), 401
- Aluminum
 - nonwoven, dynamic temperature measurements, 383
 - sticking on fabrics, 439
- Aluminum/wool, dynamic temperature measurements, 385
- American Association of Textile Chemists and Colorists (AATC) test methods
 - AATC Test Method 22-1980: 180
 - AATC Test Method 61-1980: 166, 180
 - AATC Test Method 79-1979: 140
 - AATC Test Method 124-1978: 158
- Ammonia cure process, 439
- Aniline, glove permeation testing, 75
- Anthropometric fit testing and evaluation, 556-568, 616-617
 - analysis and reporting, 566-567
 - anomalies, 561
 - battledress uniform for men and women, 591
 - bivariate frequency table, 559
 - data collection phase, 560-566
 - debriefing, 563, 566
 - hand size dimensions, 566
 - integration of assemblage, 562, 564
 - pretest preparation, 557-560
 - procurement tariff, 567
 - questionnaire, 560
- Anthropometric sizing system, 569-580, 616-617
 - battledress uniform for men and women, 581-592
 - 20-size system, 585-587
 - anthropometric design values for three sizes of shirt, 588-590
 - average ranges to be accommodated, 584-585
 - construction and grading of master patterns, 587-591
 - derivation of sizing systems, 582, 584-587
 - key sizing dimension, 582
 - shirt size categories and tariff, 588

- Anthropometric sizing system (*cont.*)
 battledress uniform for men and women (*cont.*)
 trouser size categories and tariff, 589
 bivariate frequency plot of stature and weight values, 575
 bivariate plot of height and width with three-size system, 577
 eight-size system for total body, categories and tariff, 579
 problems with scaling sizes, 570
 steps for developing, 573
 summary statistics for size X-large regular, 574, 576
 three-size anthropometric sizing system, 578
 three-size system based on size medium, 570-572
 Applicators, 95-96
 average exposure (*see also* California pesticide applicators' attitudes and practices), 97
 Aramid fabric, 331-332, 389, 470
 Asbestos
 abrasion testing, 454
 aluminized, 458-459
 heat transmission factors, 313
 molten iron splash protection, 401
 average calorimeter temperature rise in molten splash, 457
 fabric, properties, 450
 gloves, 399-400, 451-454
 history of use, 446
 molten iron splash evaluation, 459
 properties, 447-449
 substitutes (*see also* Fiberglass; Zetex), 446-460
 properties, 448
 raw materials, 447
 visual ratings of fabrics, 456
 ASTM Committee F-23 on Protective Clothing, history of, 1-2
 ASTM permeation cell, 22, 28-30
 ASTM standards
 B 117-73(1979): 154
 D 737-75(1980): 154
 D 1388-64: 397
 D 1682-64(1975): 139, 165
 D 1776-79: 140, 165, 189
 D 1777-64(1975): 154
 D 1910-64(1978): 154
 D 2863-77: 392
 D 3467-76: 40
 D 3512-82: 398, 402
 D 3775-84: 189
 D 3776-84: 189
 D 3787-80: 398
 D 3884-80: 454
 D 4108-82: 311, 316-321, 330, 334, 352, 360, 402, 407, 422-423, 465, 612
 E 84-84: 392
 E 96-80: 154
 E 622-83: 392
 F 739-81: 9, 22-23, 26, 32, 52-53, 57, 60, 69, 75, 77, 82-83, 99-100, 209, 215, 219, 247, 250-251, 257-258, 607-608
 F 903-84: 253-254, 263-264, 612

B
 Blackbody, emissivity, 378
 Blasocut Blaser, 61
 Body size variability, 556, 569
 Breakthrough time (*see also* Permeation testing), 7
 defined, 256
 liquid chemicals through clothing materials, 126
 Saranex laminated Tyvek, 278
 screens of materials, 122-123
 British standards
 BS 3791: 311-313, 316-317, 320, 326, 612
 BS 4724-1971: 123, 131
 BS 6357: 407, 413, 417

Burn injuries, 463
 Burn prevention, 475
 Burrell's solvent spectra approach, 35
 Burton's equation, 516, 529
n-Butanol, 214-215, 218
 Butyl rubber, 51
 Butyl rubber gloves, 75-76, 78-79, 219
 Butyl suits (*see also* Encapsulated chemical suits)
 hydrogen cyanide permeation, 53, 55
 problems with, 276-277
 suit weight and noise level, 281, 284

C

Caliban finish, 439-440, 614
 California pesticide applicators' attitudes and practices, 103-112
 applicators using air blast and other methods of pesticide application, 111
 commercial applicators' and growers' responses, 109
 frequency of safety equipment with reasons for low use, 107
 laundering of work clothes, 104, 111-112
 procedure for evaluation, 107
 responses to clothing-related questions, 107-108
 responses to cost and risk versus benefit questions, 108
 sources of information on pesticide application, 106
 storage and cleaning of clothing practices, 111-112
 study of objectives, 105
 users of Categories 1 and 2 pesticides and users of Category 3 pesticides, 110
 users of restricted versus nonrestricted pesticides, 109-110
 Calorimeters, 311
 disadvantages, 416-417
 Carbaryl, 95, 96
 Carbon tetrachloride, adsorbed mass calculation, (*see also* Fabrics, adsorptive, evaluating), 45-46
 Carcinogenic substances, 246
 Cellulose, solubility parameters, 199
 Chemical agent detection, 39
 Chemical exposure hazards, 207-212, 610-611
 decontamination and reuse, 211-212
 exposure assessment, 210-211
 protective clothing use, 209-210
 Chemical protective clothing (*see also* Seams and closures; specific types of clothing), 207
 decontamination (*see* Decontamination)
 defined, 250
 entrapment of substances, 212
 field evaluation, 250-260
 degradation testing, 251-253
 penetration testing, 253-255
 permeation testing (*see* Permeation testing)
 fit testing, 561-563
 gap in two-piece garment, 562-565
 heat exchange, 515-534
 cooling benefits from cover evaporation losses, 528-529
 effects of pumping coefficients and solar heat load, 532-533
 experimental and predicted results with wetted cover, 527
 heat exchange model predictions, 526-528
 mannikin runs, 524-525
 model predictions, 529-532
 net skin heat loss with wet cover, 531-532

Chemical protective clothing (*cont.*)

- heat exchange (*cont.*)
 - permeability index, 525, 528
 - procedure, 522-524
 - water requirements to maintain wet cover, 530
 - wetting with helmet, 533
 - model runs, 525-526
 - permeation resistance, 32-38, 607-609
 - criteria for selection of test chemicals, 37
 - proposed test battery, 35, 37
 - solubility parameter, 33-36
 - potential exposure of worker with, 221
 - reuse, 211-212
 - selection and use, 235-242
 - available levels of protection, 237-238, 240-241
 - consequences of direct skin contact, 237, 240
 - employee training for, 239, 242
 - likelihood of skin exposure, 236-237, 240
 - most appropriate selection, 238-239, 241-242
 - selection using permeation and toxicity data, 243-249
 - permeation class, 247-248
 - risk information (*see* Risk information)
 - use, 209-210
- Chemical resistance test methods, 250
- Chemical skin exposures, 208
- Chemicals, permeation through skin, 221-233
 - alcohol permeation in hairless mouse, 230
 - as function of tape stripping of skin, 224
 - comparison of mouse skin with human skin, 229

- enhancers, 231
 - human skin, 228
 - in vitro* permeation, 227, 231
 - in vivo* procedures, 227
 - moisture vapor transmission in skin, 225
 - non-electrolytes from aqueous solutions, 229
 - permeability coefficient, 228
 - risk, 222-223
 - routes, 225
 - stratum corneum, 225-226
 - test methods, 226-228
- Chemical toxicity, 243
- Chlorine, permeation testing, 52
- Clothing insulation (*see also* Thermal protective clothing), 515
- Coal tar, glove permeation breakthrough times, 18
- Contact thermometer, 379
- Convective heat, 327
 - flux, 421
 - protection against, 330-331
 - behavior of aramid fabric, 331-332
 - extreme specimen distortion, 331, 333
 - sensor response, 334-335
- Corona discharge, 593
- Corrosive substances, rating scale, 246
- Cotton, comfort ratings versus polybenzimidazole-blend fabrics, 396
- Cotton fire-retardant fabric, heat protection (*see also* U.S. Navy protective clothing program), 469-470
- Cotton flame-retardant fabrics, 422, 438-444
 - ammonia cure process, 439
 - bulk density retention, 366-367
 - diathermacy, 370-371
 - fabric evaluation, 441-444

mass retention, 364
 molten aluminum pour test, 442–443
 physical properties, 441, 444
 single and multiple layers, 421–437
 0.3 cal/cm²/s radiant heat only, 427–429
 1.0 cal/cm²/s convective/radiant exposure, 427, 430–431
 2.0 cal/cm²/s convective/radiant exposure, 427, 432–433
 comparison of contact versus spaced fabric/sensor configuration, 426
 effect of color on radiant heat protection, 435
 instrumental methods, 422–423, 426–427
 materials, 422, 424–425
 multiple-layer assembly diagram, 435
 protection times, 434, 436
 thickness retention, 365–366
 Critical body voltage, 593

D

Data base

protective clothing permeation testing, 88–89
 protective effects of glove materials, 67–73
 chemical resistance file, 69–70
 data base structure, 69
 data input, 68–71
 manufacturer file, 69
 medical report file, 70–71
 output data, 71–72
 product file, 68
 recommendations for improvement, 72–73
 reference file, 71

Decontamination, 207, 211–212, 612
 defined, 299
 encapsulated chemical suits, 288, 290
 fire fighter turnout gear (*see* Fire fighter turnout gear, polychlorinated biphenyl decontamination)
 Degradation, 250
 testing, 251–253
 Derksen curve, 466–467
 Dermal exposure, pesticides, 96–97
 Dermal pad dosimeters, 96
 Dermatitis, 214
 2,4-Dichlorophenoxyacetic acid, 95–96
 Dimethylformamide, glove permeation testing, 75
 Dimethyl sulfoxide, 231
 DIN (German standard) 23 320, Part 1: 321
 Dinoseb, 114
 Disposable garments, 151
 Dump valves, 286, 293
 Durable-press finish, 136, 162, 177, 180
 increased pesticide penetration, 182
 methyl parathion, distribution on fabrics (*see also* Malathion, distribution on fabrics), 200
 Durable-press resin finishes, 138

E

Electron emission, 593
 Electron microscopy, 187
 Electrostatic spark discharges, incendiary behavior, 593–603, 617
 critical body voltage
 hydrogen ignition, 601
 methane ignition, 599

- Electrostatic spark discharges (*cont.*)
 ignition apparatus, 595-597
 ignition tests, 597-598
 minimum ignition energy, 594-595, 598-599
 gas mixtures, 598-599
 methane, 601
 thermal effect on, 599-600
 quenching effect of electrodes, 594-595
- Encapsulated chemical suits, 286-296, 612
 maintenance of, 292-296
 drying, 292-293
 laundering, 292
 reassembly, 293
 soapy water inspection, 294-295
 storage, 295-296
 visual inspection, 293-294
 simulated work environment, 276-285
 protection factor and recovery time variability with air flow, 285
 suit weight and noise level comparison (*see also* Tyvek, Saranex laminated; Butyl suit), 284
 use procedures, 287-292
 air cutoff, 291
 buddy system, 287
 communications, 288-289
 decontamination, 288, 290
 doffing, 290
 in fire, 291-292
 loss of suit integrity, 290-291
 multiple-person donning, 287
 planning mission, 287-288
 ready personnel, 287
 self-extinguishing suits, 291-292
 training, 290-292
- Equilibrium sorption capacity, adsorptive fabrics, 45-46
- Esso Somentor 33, 61
 Evaporative heat loss, 515
- ## F
- FAA (*see* Federal Aviation Administration)
- Fabric functional finishes (*see also* specific finishes), 136-149, 162
 aerosol spray penetration, 151-160
 air permeability test results, 155, 157
 dry spray, 158, 160
 fabrics, 153, 155, 157
 physical data, 154-156
 water vapor permeability, 155, 158-159
 contamination of fabric, 139
 effect on pesticide residue remaining after laundering, 168-170
 extraction procedure, 141
 fabrics tested with, 138-139
 fluorocarbon finishes (*see* Fluorocarbon finishes)
 gas chromatographic analysis of, 141
 laundering of contaminated fabrics, 140, 147-149
 longevity of soil-repellent finishes, 172-173
 methyl parathion residues after laundering, 148
 moisture passing through textile layers, 137
 moisture-related fabric properties, 139-140
 pesticide penetration, 140, 143-147, 177-185
 analysis of, 181-182
 capillary forces, 137
 effects of laundering, 183-185

- exposure amount, 180-181
 - fabrics and finishes tested, 178-180
 - pesticide extracted from collector layer, 182-183
 - statistical analysis, 184-185
 - pesticide wetting and wicking, 140-142
 - resin finishes, 138
 - statistical analysis, 141
 - water-repellent, 164
- Fabrics, adsorptive, evaluating, 39-49
 - baseline mode, 43
 - breakthrough time, 46-47, 49
 - capacity, 49
 - challenge stream generator, 40-41
 - challenge stream mode, 43
 - degassing mode, 43
 - detection system, 41
 - equilibrium sorption capacity, 45-46
 - extrapolation of curve to saturation, 44-45
 - sample cell, 41-42
 - sorption kinetics, 46-48
 - test plumbing and instrumentation, 41-43
 - tests
 - mode, 43-44
 - reproducibility, 48-49
 - result curve, 44
 - total adsorption capacity, 48
- Federal Aviation Administration
 - standard FAA-RD-75-176: 311-312, 314, 612
- Federal Aviation Regulation (FAR) 25.853b: 406
- Federal test method standards (FTMS)
 - FTMS 191: 406, 465
 - FTMS 191A: 499
 - FTMS 191-5903: 392
 - FTMS 191-5905: 402
- Fiberglass
 - aluminized, molten iron splash evaluation, 459
 - properties, 449
 - texturized (*see* Zetex)
- Fire fighters, 463
 - temperature exposure, 464, 490
- Fire fighter's turnout gear, 615-616
 - burn injuries and specific body regions, 489
- functional integration, 487-495
 - methods, 490
- heat protection characteristics, 472
- history, 487-488
- polybenzimidazole-blend fabrics, 400, 402-403
- polychlorinated biphenyl decontamination, 298-307
 - analytical method, 300-301
 - decontamination results, 302-303
- fabric sampling protocol, 300
- Freon shower decontamination approach, 305-306
- Freon solvent system decontamination, 301-303
- process description, 303
- site contamination and decontamination, 301
- techniques and physical damage, 304-305
- thermal protective performance rating, 491-494
- Fire retardant materials, 497
- Fires, use of encapsulated chemical suits in, 291-292
- Fit testing (*see* Anthropometric fit testing and evaluation)
- Flame impingement, 340
- Flame ionization detector, 7, 41
- Flame resistance, 421
 - polybenzimidazole-blend fabrics, 392

Flame-retardant finishes, 359

Flames

heat transmitted through uniform fabric/underwear combinations, 471

protection against (*see also* specific fabrics), 317-325, 329

convective heat transfer, influence of specimen mounting, 324

curved calorimeter, 321-322

estimated burn time, 318-319, 323

estimated pain time, 318-319, 323

fuel gas and calorimeter influence, 319

heat sensors, 319-320

heat source, 317-319

mounting plate as physical restraint, 324-325

specimen mounting, 320-325

transmitted heat measurement, 330-334

U.S. Navy protective clothing program, 500-501, 505-507

Flammability, 465

Fluorocarbon finishes, 137-138, 151, 162, 164-165

longevity, 173-174

pesticide action on

penetration, 145

wicking, 142

residues on after laundering, 169

Formaldehyde, permeation testing, 52-53, 56

French Experimental Standard S74-107: 407, 413

Freon 113 decontamination process, 304

Freon shower decontamination approach, 305-306

Freon TF solvent, 298, 301-303

Functional finishes (*see* Fabric functional finishes)

G

Glove materials

data base on protective effects (*see* Data base, protective effects of glove materials)

influence of thickness on permeation resistance, 75-81

breakthrough time, 77, 80

procedure, 76-77

results, 77-79

permeation measurement, 7-20

breakthrough times, 16-17

comparison measurement methods, 11

experimental method, 8-10

glove thickness and density, 12-13, 17

glove types studied, 10

liquefied coal, 15-18

permeation rate, 16

stainless steel permeation cell, 9

toluene, 11-15

washing experiments, 18-19

permeation resistance, 241

pesticide permeation testing, 99

testing against metal cutting fluids, 59-66

candidate materials, 62-63

challenge chemicals, 61

permeation testing, 60-61, 63-64

tensile strength testing, 62, 65

vulcanizing agents, 66

Gloves (*see also* Organic solvents, bioassay for glove performance), 207

anthropometric comparison of fit test sample, 566

asbestos, 451-453

chlorine permeation testing, 53
 formaldehyde permeation testing, 53
 high-temperature use, 399-400
 procurement tariff, high-altitude gloves, 567
 testing, 451-453
 whole glove permeation testing, 256-257
 Zetex, 451-453
 Gore-Tex, 491
 Ground boom sprayer, 95
 Ground rig applicators, average exposure, 97
 Guinea pig model, 214
 skin absorption of chemicals, 218
 Guthion, 114

H

Heat conduction, 340
 Heat exchange
 balance equation, 549, 551-554
 chemical protective clothing (*see* Chemical protective clothing, heat exchange)
 convection coefficient, 524
 dry, and cooling efficiency, 516-518
 evaporative heat loss from wetted cover, 518-519
 from impermeable layer to clothing surface, 520-521
 from skin to impermeable layer, 520
 heat removal capability of air, 553
 linear dew point temperature, 521
 model predictions, 526-528
 saturated vapor pressure, 519-522
 sensible heat loss, 551
 sweating loss, 552
 wetted cover, 517
 Heat flux, 423

Heat sensor, 311
 Heat stress, 406, 515, 616
 Heat transfer, 358
 Hexane, glove permeation testing, 75
 Hydrogen, 593
 critical body voltage, 601
 Hydrogen cyanide, permeation testing, 52

I

Ignition
 hazard, 593
 resistance, 465
 time to, 340
 Impermeable garment, 515
 Infrared radiation theory, 377-379
 Infrared spectroscopy, permeation tests, 22-30
 ASTM cell pressure and detection of breakthrough time, 29
 breakthrough time versus static pressure, 30
 cell leakage, 29
 effects of varying pressure and flow rates, 28-30
 in-series or multiple tests, 26-27
 purge time, 25-26
 single-beam infrared instruments, 23
 static pressure in closed system, 28
 Teflon-lined gas cell, 25
 Infrared thermometer, 376, 379-380
 International Organization for Standardization (ISO) standards
 ISO 6530-1980: 123, 132, 134
 ISO 6942-1981: 311-314, 317, 321, 330-331, 612
 ISO/DIS 6529: 123, 132
 ISO/TC92/SC13/WG2: 406-407
 ISO/TC94/SC13/WG2N62: 318, 416
 ISO/TC94/SC9/WG1N38: 318

K

- Kelvar, 389
 bulk density retention, 366-367
 mass retention, 363
 thermal properties, 371-372
 thickness retention, 365-366
 Kirchhoff's law, 377

L

- Latex rubber, 51
 Laundering, 136
 contaminated clothes, 140, 152
 distribution of malathion and methyl parathion (*see* Malathion, distribution on fabrics; Methyl parathion, distribution on fabrics)
 effectiveness, 147-149
 effect on barrier properties, 183-185
 encapsulated chemical suits, 292
 procedure effects, 163-175
 effect of finishes, 165-166, 168-170
 effect of laundry treatment, 169, 171
 effect of pesticide class, 169, 171-172
 effect on laundering, 165-166
 extraction and analysis of pesticides, 166-167
 fabrics tested, 164-165
 hot water, 163
 insecticides, 165
 longevity of finishes, 172-173
 recommendations, 174-175
 residue remaining, 168-170
 specimen contamination, 165
 statistical analysis, 167
 Lightweight clothing materials, heat protection (*see also* Thermal protective clothing fabrics, test methods), 340-356

- effect of assembly thickness on temperature rise, 352, 354
 fabric descriptions, 351
 factors that control performance, 341
 heat transfer and estimates of burn injury, 351-356
 ignition times, 351
 modeling thermal environment of large fire, 342-345
 quartz-faced heater panels, 343
 specimen temperature as function of time, 348
 strength loss times, 350
 strength retention at equilibrium temperature, 348
 temperature in skin stimulant, 352-353
 temperature rise at depths in skin-stimulant device, 354-355
 thermal energy absorbed, 341
 transference of heat from outer to inner layers, 341
 Liquefied coal
 contaminants after wash experiments, gloves, 18
 glove permeation, 7-8, 15-18
 breakthrough times, 16-17
 chromatographs, 20
 glove thickness and density, 17
 permeation rate, 16

M

- Malathion
 chemical structure, 188
 distribution on fabrics, 187-203
 backscattered electron images, 193
 contamination procedures, 189-190
 determination of pesticide residue, 190
 distribution of pesticides on surface and within fibers, 198

- electron microscopy, 191
- fabrics tested, 188-189
- laundry procedure, 191
- residues remaining after laundering, 192, 199
- retention on durable-press after laundering, 201
- retention on surfaces of fibers, 196, 202-203
- solubility parameters, 199
- summary of analyses of variance, 197
- physiochemical parameters, 189
- Mancozeb, 95, 96
- Matrix release, 207, 211
- Metal cutting fluids, 59
- Methane, 593
 - critical body voltage for ignition, 594, 599
 - minimum ignition energy, 601
- Methyl isobutyl ketone, glove permeation testing, 75
- Methyl parathion
 - adsorption through outer garment fabric/undergarment fabric/skin, 146
 - chemical structure, 188
 - distribution on fabrics, 187-203
 - backscattered electron images, 194-195
 - contamination procedures, 189-190
 - determination of pesticide residue, 190
 - distribution on surface and within fibers, 198, 200
 - electron microscopy, 191
 - fabrics tested, 188-189
 - laundry procedure, 191
 - residues remaining after laundering, 192, 199
 - retention on surfaces of fibers, 196, 202-203
 - solubility parameters, 199
 - summary of analyses of variance, 197
 - outer garment fabric sorption, 143
 - penetration and functional finishes, 180-185
 - penetration through outer garment fabric/sentinel pad system, 144
 - physiochemical parameters, 189
 - residues after laundering, 136, 148
 - spun-bonded olefin/outer garment-fabric/sentinel pad sorption, 147
- Military standard MIL-C-43858: 41, 608
- Miran 1A, 23-24
- Miran 80, 23-24
- Mixer/loaders, 95-97
- Moisture vapor transmission rate, 225
- Molten metal, 475
 - cotton, flame retardant fabrics, 438
 - protection against (*see also* specific fabrics)
 - testing fabrics, 476-486
 - 1000-g molten metal splash tests, 482-483
 - 1500-g molten metal splash tests, 481-482
 - aluminized coats, 482
 - apparatus with small induction furnace, 477
 - application of results, 484-485
 - blister line, 480
 - complications, 476
 - different metals, 484
 - factors affecting splash test results, 478
 - measuring results, 477-480
 - method, 476
 - preliminary testing, 480
 - relating laboratory results to real world, 485-486

Molten metal (*cont.*)testing fabrics (*cont.*)time to burn and pain graph,
479**N**

National Fire Academy, hand signals, 288

National Fire Protection Association (NFPA) Standard 1971: 465

Natural latex gloves (*see also* Glove materials, testing against metal cutting fluids), 7, 10

chlorine permeation testing, 53–54

formaldehyde permeation, 53, 56

steady-state permeation rates, 13

Navy formula II, 511–512

Neoprene, 51

Neoprene gloves (*see also* Glove materials, testing against metal cutting fluids), 75–76, 79

Neoprene/natural rubber, permeation rate, 91

Neoprene suit materials, chlorine permeation testing, 53

NFPA (*see* National Fire Protection Association)

Nitrile-butadiene gloves, formaldehyde permeation, 53, 56

Nitrile-butadiene rubber, 51

Nitrile gloves (*see also* Glove materials, testing against metal cutting fluids)

variation in permeation resistance, 33

Nitrile rubber gloves, 7, 10, 75–76, 79

Nomex, 3, 389, 491, 495, 498

strength retention, 346–347, 349

Nomex/Kevlar, 340, 505, 507–509, 613

O

Olefin, spun-bonded, sorption, 146–147

Organic solvents, bioassay for glove performance, 214–219

exposure chamber, 216

materials and methods, 215–216

P

Paraquat, 114

Parathion, 114

Patch testing, protective effects of gloves, 70

Penetration, 126, 250, 263

defined, 178, 263–264

resistance (*see* Seams and closures, penetration resistance)

Penetration testing, 253–255

cell, 255

Percutaneous toxicity, 215

Permeability coefficient, 228

Permeation, 250

chemical protective clothing (*see* Chemical protective clothing, permeation resistance)

class, 243, 247–248

defined, 178

enhancers, 231

glove materials (*see* Glove materials, permeation measurement)infrared spectroscopy (*see* Infrared spectroscopy, permeation tests)

rate, 7, 51, 229

closed systems, 86–87

dynamic system, 85

scale, 248

versus time plot, 88, 90–91

resistance, 32

Permeation testing (*see also* Break-through time; Data base, pro-

- protective effects of glove materials; Glove materials; Work fabrics; specific types of clothing), 51-58, 82-92, 235, 254, 256-260
 - calculations, 84-85
 - chlorine permeation testing, 53
 - closed system calculations, 85-87
 - computer data base, 88-89
 - concentration of chemical in collection medium versus time, 87
 - data flow sequence, 89
 - formaldehyde, 53, 56
 - graphical presentation of data, 87-88
 - hydrogen cyanide testing, 53, 55
 - limitations, 257
 - metal cutting fluids, 60-61, 63-64
 - nomenclature, 83-84
 - probe tip of photoionization detector, 257
 - problems when using ASTM Method F 739-81, 82-83
 - procedure, 52, 83
 - rate versus time, 88
 - steady-state rate, 256, 258
 - summary of data, 57
 - test apparatus, 258-259
 - whole glove, 256-257
- Pesticides (*see also* California pesticide applicators' attitudes and practices)
 - class, effect of on residues remaining after laundering, 169, 171
 - dermal exposure, 104
 - penetration (*see also* Fabric functional finishes, pesticide penetration), 140, 143-147
 - garment fabric, 143
 - garment fabric with sentinel pad, 144-145
 - influence of capillary forces, 137
 - outer garment fabric/undergarment fabric/dermal pad, 145-146
 - spun-bonded olefin/outer garment fabric/sentinel pad, 146-147
 - protective clothing, 95-101
 - field monitoring, 96-97
 - heat stress factor, 98-99
 - information dissemination to users, 100
 - need for laboratory evaluations, 99
 - need for more field testing, 98-99
 - standardized and practical methods, 100
 - working group, 98
 - resistance to, 609-610
 - secondary exposure, 103-104, 111
 - wetting, 140-142
 - wicking, 140, 142
 - work fabrics as barriers, 114-120
- Pesticide spraying, protective clothing, 95-96, 121-134
 - analysis of samples, 124
 - breakthrough time measurement, 122-123
 - comfort of trial clothing, 133
 - contamination of spray operators, 124, 130
 - correlation between field and laboratory test results, 133-134
 - design of field studies, 127-130
 - laboratory evaluation of factors associated with protective efficiency, 131
 - observed contamination of operators' clothing, 128
 - penetration of spray liquids through made-up clothing, 124, 132
 - permeation materials, 131-132

Pesticide spraying (*cont.*)

- relative resistance of materials to penetration by liquid chemicals, 132

- relative spray penetration of test clothing, 130-131

- screening tests, 122-124

- selection of protective clothing materials for field studies, 124-127

- trial spray suits, 129

PFR rayon, 389

Phenol, contaminants after wash experiments, 19

Polybenzimidazole, 340, 349, 613-614

- bulk density retention, 366-367

- fabrics, thermal properties, 371-372

- mass retention, 363

- thickness retention, 365-366

Polybenzimidazole-blend fabrics, 389-403

- acid derivation reduction, 391

- chemical reaction, 390

- chemical resistance, 393-395

- comfort, 395-396

- engineering protective fabrics, 396-403

- burst strength, 398

- char length, 399

- contact heat testing time to ignition, 403

- firemen's protective apparel, 400, 402-403

- foundry and fire proximity, 400-401

- high-temperature gloves, 398-400

- limiting oxygen index, 397

- molten iron splash protection, 401

- molten metal test apparatus, 401

- random tumble pilling, 398

- stiffness, 397

- thermal protection performance, 402

- flame resistance, 392

- physical properties, 391

- programed temperature thermogravimetry, 393

- properties, 390

- strength at elevated temperature, 394

- tensile strength

- after immersion in inorganic acids, 394

- after immersion in inorganic bases, 394

- after immersion in organic chemicals, 395

- thermal stability, 392-393

Polychlorinated biphenyl, decontamination (*see* Fire fighter turnout gear, polychlorinated biphenyl decontamination)

Polyethylene-coated Tyvek, 51

- chlorine permeation testing, 53

- hydrogen cyanide permeation, 53, 55

Polyethylene terephthalate, solubility parameters, 199

Polymer glove materials, 59

Polymeric fabrics

- effect of source temperature on absorptance, 345

- heat flux absorbed, 344

Polyvinyl chloride, 51

- encapsulated suits, storage of, 296

- gloves, 7, 10, 219

- steady-state permeation rates, 13

- hydrogen cyanide permeation, 53, 55

Protection tests, 497

Protective clothing, 32, 103-112

- as a hazard, 100

- management programs, 236
- physical requirements of materials, 57
- Puncture testing, glove materials, 61-62

R

- Radiant heat, 311, 327, 340
 - dominant wavelength, 345
 - flux, 421
 - protection against, 312-317, 330-331
 - amount of absorbed heat, 315
 - bilateral radiation interchange, 344
 - color effect, 435
 - correction factor, 315-316
 - heat sensors, 324-316
 - heat source, 312-314, 342
 - heat transmission factors, 313, 315
 - quartz and gas-fired panels, 315
 - specimen mounting, 316
 - test methods, 312
 - quartz-faced heater panels, 315, 343
- Radiant heat protective clothing materials, 376-386
 - apparatus, 379-380
 - digital contact and air thermometer, 379
 - dynamic temperature measurements, 380-382
 - aluminum/wool, 385
 - nonwoven aluminum, 383
 - silicon/fiberglass, 384
 - emissivity, 378, 380, 382
- Infrared radiation theory, 377-379
- Infrared radiator, 379-380
- Infrared thermometer, 379-380
- radiated heat effect, 379
- test results, 382-386
- test rig, 380-381

- Ranque Hilsch cooling effect, 548-549
- Reflection index, 376
- Resin finishes, 138
- Risk assessment, 222, 235, 243
- Risk/benefit analysis, 235
- Risk information, 243-247

S

- Saturated vapor pressure
 - determination of, 519-521
 - final solution, 521-522
- Seams and closures, penetration resistance, 263-275, 611-612
 - experimental procedure, 264-269
 - cell sealant material, 267-268
 - sample garments, 267-269
 - seam constructions, 267-268
 - test apparatus, 265
 - test cell, 266
 - zipper construction, 268
 - penetration test results
 - butyl rubber, 272, 274
 - chlorinated polyethylene, 272, 274
 - copolymer of vinylidene chloride and vinyl chloride, 269-270
 - laminate of melted polypropylene, 271
 - microporous polytetrafluoroethylene laminated to a fabric, 272
 - plasticized polyvinyl chloride, 271-274
 - Viton elastomer, 272, 274
- physical properties of liquid challenge chemicals, 275
- Seepage, 294
- Shale oil, glove permeation breakthrough times, 18
- Silicon/fiberglass, dynamic temperature measurements, 384

Skin

- cross section, 223
 - direct contact consequences, 237
 - exposure, 207
 - simulant, 340, 352–353, 406
 - structure, 223–225
- Soil release finish, 177, 180, 182
- Soil-repellent finish, 136, 172–173
- Solubility parameter, 32
- and hydrogen bonding class, 35
 - correlation with permeation resistance, 36
 - expression, 34
- Sorption kinetics, adsorption fabrics, 46–48
- Splash test, 475
- Stoll curve, 475
- Strength retention and ignition during exposure, 346–351
- Styrene polymer production, chemicals found, 240

T

- Tensile strength testing, glove materials, 62
- Thermal injury, 358
- Thermal protective clothing (*see also* Cotton, flame resistant, single and multiple layers)
- dynamically insulated, 535–555
 - air distribution system in, 542–543
 - air flow and thermal conductance, 548
 - apparatus used for determining thermal conductances, 544
 - conductance of garment materials, 545
 - conductance of material assembly and predicted values, 545–546
 - defined, 537
 - duplex vortex tube, 550, 554

- dynamic insulation characteristics, 542–546
 - heat balance equation, 549, 551–554
 - hot environment protective suit, 537–542
 - inlet air pressure and temperature interval, 551
 - moisture uptake and sweat heat loss, 552
 - physical properties of materials used, 542
 - Ranque Hilsch cooling effect, 548–549
 - sensible heat loss, 551
 - thermal conductance, of complete assembly, 546–548
 - total heat removal capability of air, 553
 - total heat to be removed from body in hot environmental work suit, 553
- evaluating materials, 614–615
- fabric characteristics (*see also* Fire fighter's turnout gear), 463–473
- Derksen curve, 466–467
 - fabric specifications, 470
 - flammability, 465
 - heat protective properties, 465–466
 - ignition resistance, 465
 - moisture effects, 464
 - outerwear/underwear combinations, 469–471
 - single layers of fabrics, 467–468
 - thermal inertia, 464
 - thermal resistance, 464
 - time-heat relationship, 466
 - time to injury, 467, 469
 - total heat transmitted through uniform fabric/underwear combinations, 471
- laboratory measurement of performance, 612–614

- predicting performance, 358-374
 - air and fiber conduction, 373-374
 - air volume fractions of test fabrics, 362-363
 - apparent thermal conductivity, 368
 - average temperature, 370
 - bulk density retention, 366-368
 - flame-retardant cotton fabrics, 370-371
 - infrared transmission, 368
 - Kevlar fabrics, 371-372
 - mass retention, 363-364
 - materials, 359-360
 - method, 360-361
 - polybenzimidazole fabrics, 371-372
 - polymer-to-air ratio, 373
 - predicting thermal protective performance from initial properties, 372-373
 - specific heat capacities, 368
 - thermal properties, 368-370
 - thermal protective performance traces, 361-362
 - thickness retention, 364-366
 - tolerance times, 362
 - weight loss as function of exposure time, 361
- Thermal protective clothing fabrics,
 - test methods (*see also* Light-weight clothing materials, heat protection), 311-339
- burn time, 334-336
- convective heat, 331
- exposure of materials to intense heat, 328-329
- fabric integrity, 336-337
- factors that influence burn injury, 328
- flames (*see* Flames, protection against)
- function, 327
- hole formation, 329, 335
- nature of intense heat hazard, 329, 330
- pain time, 334-336
- radiant heat, 312-317
 - heat sensors, 314-316
 - heat source, 312-314
 - specimen mounting, 316
- relevance of test results, 337-338
- second-degree burn threshold assessment, 335-336
- sensor response, 334
- skin stimulant sensors, 336
- Thermal protective performance rating, 491-494
- test, 358, 360, 487, 613
- Thermistor, 95
- Toluene, 214-215
 - blood concentration with protective gloves, 217
 - glove permeation, 7, 9, 11-15, 75
 - glove thickness and density, 12-13
 - radiolabeled tracer study, 13
 - rate, 12
- Toxicity scale, 246
- 1,1,1-Trichloroethane, 214-215, 217
- Turnout coat (*see* Fire fighter's turnout gear)
- Two-chamber chemical permeation test cell, 61
- Tyvek, Saranex laminated, 277-278
 - encapsulating suit, 279-280
 - exhaust valves, 281, 284
 - face piece materials, 277
 - glove attachment, 281
 - knee reinforcement, 279-280, 282
 - limited-use garment, 285
 - protection factor, 282-284
 - recovery time, 283, 285
 - suit weight and noise level, 281, 284
 - ventilating vest, 280, 283
 - layered structure, 278
 - permeation data, 278

U

- U.S. Navy protective clothing program, 497-512
 - fire pit tests, 500, 502-504, 507-510
 - body burn percentage versus total heat, 508
 - burn incidence for body regions, 509
 - burn level and paper tape activation temperature, 504
 - facility, 500, 503
 - individual total heat, 507
 - number of garments tested, 504
 - test mannikins, 500, 503-504
 - thermal shrinkage, 510
 - uniform design effects, 509
 - fire resistance, 499-505
 - flame impingement, 500-502, 505-507
 - temperature rise in skin simulant, 506
 - materials, 499
 - Navy formula II, 511-512
 - paper tape-leather patch calibration procedure, 512
 - total heat protection, 510
 - vertical flammability performance, 505

V

Viton, 29

W

- Water repellent finish, 177, 179-180
 - effect on barrier properties of fabrics, 182-185
- Water vapor permeability, 151
- Wetted cover, 515
 - evaporative heat loss from, 518-519
 - heat balance, 517

Wheeler's equation, modified form, 47

- Wool, 405-419, 439
 - fabrics, 406
 - flame exposure, 408-413
 - air gap effect, 408-410
 - fabric construction and fiber type, 408, 411-412, 417-418
 - moisture effect, 412-413
 - repeatability and reproducibility, 408-409
 - heat protection, 468
 - melton, heat transmission factors, 313
 - molten metal splash, 413-416, 483
 - fabric construction and fabric type, 413, 415-416, 418
 - reproducibility, 413-414
 - physiological stress, 418-419
 - test methods, 407, 416-417
- Work fabrics, as pesticide barriers, 114-120
 - Duncan's multiple range for disintegrations per minute, 118-119
 - pesticides tested, 115-116
 - protocol, 116-117
 - split-plot ANOVA table, 117
 - test fabrics, 115
 - test procedures, 115-117
 - two-way interactions, 117-118

Z

- Zetex, 449, 614-615
 - abrasion testing, 454
 - development of safety clothing, 450-454
 - cut resistance, 451
 - glove design changes, 451
 - irritation problems, 450
 - glove testing, 451-454
 - molten metal testing, 454-459
 - aluminized, 458-459

- apparatus, 455
- average calorimeter temperature rise, 457
- grading system for damage, 456-457
- maximum rate of heat flow, 457
- splash evaluation, 459
- visual ratings, 456
- properties, 450
- Zipper
 - pressure sealing, 286
 - storage of, 295-296
 - testing seal, 294-295
- Zirpro flame-retardant treatments, 405, 417-418, 439