

Subject Index

A

- A-c potential drop technique, 1116-1117
- Activation energy, values, 248
- Advanced equipment, utilization, 21-23
- AF2-1DA, strainrange partitioning, total-strain version, 335-337
- Aging, 209, 798
 - crack growth, 215-216
 - cyclic hardening-softening effect, 802, 805
 - duplex stainless steel, 822
 - fatigue life effect, 802, 804
- AISI H13 hot-work tool steel, 576-587
 - chemical composition, 577
 - experimental procedure, 577
 - isothermal low cycle fatigue results, 579-581
 - lifetime results, 583, 585-587
 - non-isothermal thermo-mechanical fatigue results, 581, 583-584
 - theory, 577-579
- Alloy 1200
 - cyclic response, 99
 - fatigue performance, 104-105
- Alloy 6351
 - breaks in cyclic response, 99
 - cyclic hardening, 102, 104
 - cyclic response, 98
- Alloy 5083
 - cyclic hardening, 102, 104
 - cyclic response, 98
- Alloy 7005, fatigue performance, 104-105
- Alloy API, crack growth, 284
 - rate versus C^* , 285
- Alloys, design, 11-12
- Al-0.97Mg alloy, fatigue deformation coefficients, 855-856
- Al-Mg-Si alloys, 765-774
 - chemical composition, 766
 - fatigue-life relationship, 769
 - fatigue test data, 771
 - grain size, 766
 - grain structure, 767
 - heat treatment, 766
 - number of cycles to failure, 772-773
 - procedure, 765-769
 - specimen dimensions, 767
 - stress-plastic strain dependence, 771
 - stress-strain diagram, 769-771
 - stress-strain hysteresis diagram, 768
 - tensile test data, 771
- Al 2024-T3, 987
- Aluminide coating, 672
- Aluminum alloy, 94-105
 - age hardened, 765
 - cyclic and monotonic parameters, 103
 - cyclic hardening, 58, 95
 - cyclic hardening exponent, 104
 - cyclic stress-strain curve, 95, 97
 - description, 96
 - experimental procedures, 95
 - fatigue toughness, 103-104
 - fracture toughness, 103-104
 - hysteresis loop, 94
 - low cycle fatigue parameters, 102
 - Manson-Coffin curve, 94
 - microstructure, 102
 - notch tip strains, 1041-1042
 - stress amplitude, versus fatigue life, 101
 - total plastic energy, versus fatigue life, 101
 - see also* specific alloys
- 7475 Aluminum alloy, crack path, 13
- Al-4.5Zn-2.5Mg., stress-strain curve
 - over-aged, 64
 - peak-aged, 63, 74
 - under-aged, 62, 74
- Anisotropy, fatigue strength, 1181, 1195-1197
- Ashby maps, 437
- ASME N-47 method, life estimation, 1092-1093
- Aspect ratio, 8, 1206, 1210
- ASTM A 470, 973, 1238
- ASTM E 606, 79, 471, 765, 774, 1242
- Austenitic stainless steels, 414-438, 519
 - continuous fatigue specimens, 419-422
 - correlation between intergranular damage and stress relaxation, 428-429
 - crack propagation law, 420
 - creep-fatigue interaction, 543-556
 - creep fatigue specimens, 422-427
 - creep tests, 416

Austenitic stainless steels (cont.)

- experimental procedure, 415-416
 - fatigue failure, 717-720
 - fatigue resistance, 438
 - fractography, 416, 419-427
 - intergranular crack, 422, 424
 - intergranular damage, 422-423, 425
 - low-cycle fatigue tests, 416-419
 - Manson-Coffin plot, 547
 - metallography, 416, 419-427
 - parallel between creep-fatigue resistance and creep ductility, 428-431
 - round cavities, 422, 424
 - secondary crack density, 422
 - stress relaxation, as creep-fatigue life correlating parameter, 427-428
 - striation spacing measurements, 419-421
 - see also* Specific stainless steels
- Austenitic weld material, 209**
- Automotive design, cyclic deformation applications, 1231-1234**
- Axial fatigue, predicting bending fatigue from, 31-33**
- Axial strain, 1070 steel, 197, 202**

B**B-1900**

- bi-modal γ' distribution, 826, 830
- grain boundary, 829
- microstructure, after standard heat treatment, 826-827

see also Equiaxed cast superalloy

B-1900 + Hf, 638-655

- apparatus and test conditions, 640-641
- base material description, 640
- bithermal fatigue, 634-635
- chemical composition, 640
- coarsening, 647, 652-653
- cracking mode, 654
- cyclic hardening/softening, 642, 645, 650-654
- cyclic stress-strain response, 641-645, 654
- dislocation structure, 650-652
- flow stress, 653-654
- fractographic observations, 645-651
 - in-phase cycled specimen, 649
 - out-of-phase cycled specimen, 648
- heat treatment, 640
- hysteresis loop, 642, 644
- isothermal strainrange partitioning, 632-645
- partial dislocation, 653
- rafting, 647, 652-653
- strain as function of time, 641, 643
- TEM observations, 645-651
- tensile properties, 641
- thermal-mechanical testing, 641-642

Back stress, 487

- accuracy of measurements, 498-499
- prediction, 492-493
- time-dependent behavior, 491-492

Bauschinger effect, 978**Bauschinger energy parameter, 94****Bending fatigue, predicting from axial fatigue data, 31-33****Besseling's model, 700-701****Best fitting ellipse, 9****Biaxial fatigue, 861, 874****Biaxial strain controlled fatigue tests, Inconel 718, 867, 869****Biaxial stress**

- constant life lines, 862
 - gas turbine engine disk bore, 870
- Bilinear stress-strain curve, 1025, 1040**
- finite element calculations, 1039

Bithermal fatigue, 625-637

- B-1900 + Hf, 634-635
- case for bithermal cycling, 626-629
- dog-leg cycle, 630
- prior results, 629-631
- specimen geometry, 632
- thermomechanical loading effects, 628

Block loading, 184

- hysteresis loops from, 117

70-30 brass

- crack growth rate, 1063
- crack length, 1052
- crack propagation, 1053
- crack tip fracture strain, 1063
- tensile fracture ductility, 1063

Brittle zones, 746**Burgers vectors, 647, 651****C****Carbide**

- formation on grain boundaries and slip bands, 746-747
- oxidation, 670
- solubility limit, 579

Carbon steel, 1181

- chemical composition, 752, 1183
- crack growth rate, 1063
- crack length, 1052
- crack propagation, 1051-1052
- crack tip fracture strain, 1063
- mechanical properties, 752, 1183
- tensile fracture ductility, 1063

Cast steels, 1144

- characteristic and equivalent characteristic length, 1151-1152
- chemical composition, 1150
- cyclic and fatigue properties, 1151
- fatigue notch factors, 1152

- fully-reversed fatigue limits, 1151
- load-strain hysteresis, 1155
- load versus strain, 1156
- monotonic tensile properties, 1150
- properties, 1148-1151
- Cavitation
 - crack growth, 1254
 - HP-IP steam turbine rotor, 1250, 1252
- Cavity
 - growth, 316-317
 - nucleation, 316
 - rate equation, 316
 - spacing, 316
- Center notched specimen, 237-238
- Ceramics, 26
- Channeled one-dimensional flow model, 1209-1210
- Characteristic length, 1144, 1146-1147
 - cast steels, 1151-1152
 - load versus equivalent strain, 1156
 - notched strip specimens, 1152
- Charpy, impact properties, 1239
- Chip carrier array solder joints, 591, 594-595
- Cobalt-base superalloy, 1115
- Coefficient of correlation, nickel-based superalloys, 465
- Coefficient of thermal expansion, 9Cr-1Mo-V-Nb steel, 121
- Coffin-Manson relationship. *See* Manson-Coffin relationship
- Cold work
 - 20Cr-25Ni-Nb stainless steel, 719-720
 - fatigue life effect, 719-720
- Colonies, 839
- Combined cycle fatigue, 961
- Compact tension specimen, finite element net, 1007-1008
- Component size, 209
- Component stress history, 510, 512-515
- Composite materials, 12, 26
- Compressive limits, 1223
- Compressive overload
 - fatigue life effects, 179-182
 - see also* Fatigue, compression and compressive overload effects
- Compressive prestrain
 - schematic diagram, 165
 - see also* Very low cycle fatigue tensile or compressive prestrain
- Compressive stress, fatigue life, 177-178
- Computer simulation, 7-9, 1218
 - crack initiation and propagation, 1227, 1229
- Concentration factor, 1227
- Constant amplitude straining
 - 2.25 Cr-1Mo steel, 43-56
 - experimental procedure, 44-45
- Constant displacement amplitude cycling, 287
- Constant load amplitude cycling, 286
- Constant plastic strain amplitude tests, 439
- Constitutive behavior
 - emphasis, 28-30
 - Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 375-377
 - predicted versus observed, René 80, 703-706
- Constitutive equations, 123, 132, 1067-1068
 - FEM analysis, 1071, 1079
- Constitutive modeling, 329
- Constitutive theory
 - René 80, 700-701
 - three-dimensional version, 137
- Constrained diffusion cavity growth, 437
- Continuous cycling, Inconel 625, 471-473
- Continuous fatigue, crack density, 434
- Continuum mechanics
 - macroscopic, 989
 - model, 611
- Copper
 - cyclic data comparison, 75
 - cyclic stress-strain response, 151, 153
 - deformation history, 156
 - dislocation cell size and alternating plastic strain, 66, 72
 - dislocation structures, 65-66
 - fatigue hardening, 88
 - fatigue resistance, 151-152
 - incremental-step test, 70
 - monotonic stress-strain response, 151, 153
 - multiple-step test, 70
 - plastic-strain limit test, 69
 - silver penetration along tilt boundaries, 1211
 - stress-strain curve, 66
 - transient flow behavior, 151-152
- Copper alloys, cyclic hardening, 58
- Corrosion-fatigue, 812
- Crack, 1022
 - characteristics, 919
 - configurations, 1027
 - density, as function of plastic strain, 453
 - depth
 - R* ratio variation, 224
 - variation with stress, 219, 221
 - development, notched shaft, 885-888
 - equivalent strain energy density hypothesis, 1030-1034
 - extension curves, 1186-1187, 1193
 - formation, Waspaloy, 730-731, 735-736, 741-742, 744-745
 - front, 966
 - ground stages, 876
 - intercrystalline, 601-602, 609

Crack (cont.)

- leading, manganese-sulphide inclusion, 1196
- mode, B-1900 + Hf, 654
- monitoring, 209
- notation, 1024
- nucleation, 776
 - strain aging ferrous alloys, 786
 - stress concentration, 899
- path, 553, 965
- shape, 209, 212
- size, fatigue life, 882
- straight front, 228
- velocity, versus period of cycling, 9-10
- Widmannstätten microstructure, 847
- Crack closure, 209
 - crack growth effects, 220, 223-224
 - plastic strain, 220, 222
 - variation with depth, 223
- Cracked pearlite ratio, 757, 760-761
 - residual ductility, 763
- Crack growth, 257, 261-263, 313, 558, 874
 - accelerating and decelerating, 209
 - air and helium, 566
 - cavitation, 1254
 - coalescence, 1189
 - creep component, 308
 - environmental and creep effects, 307
 - equation, 1228
 - equivalent stress intensity range, 226
 - frequency dependence, 282
 - gray cast iron, 910-912
 - versus life plots, 886
 - load relaxation, 287
 - modelling, 210
 - propagation over final half of specimen, 218
 - real-time, 9-10
 - time dependence, 574
- Crack growth law, 317
 - empirical relations, 211-212
 - extension to deeper cracks, 218-219
 - separation of initiation and endurance cycles, 216-217
 - shape effects, 212
 - validity for large specimens, 219
- Crack growth rate, 268, 419, 434, 1050, 1125
 - air effect, 298, 300-301
 - analysis, 263-267
 - 70-30 brass, 1063
 - carbon steel, 1063
 - critical depth, 221
 - cyclic J -integral, 264, 267-268, 978-980, 1213
 - effective stress, 465
 - high temperature alloys, 227
 - Inconel 718, 958

- intergranular bulk damage, 423-424
- nickel-based superalloys, 460-461
- pipe and specimen testing, 11
- René 95, 298-299
 - predicted and observed, 301
- secondary crack density, 423
- striation spacing, 423
- Ti 6-4, 956
- underaged 7X75 alloys, 13
- variation with frequency, 215
- variation with total strainrange, 213
- Cracking behavior, 899-919
 - background, 899-902
 - direction, 913
 - experimental procedure, 902-903
 - gray cast iron, 910-912
 - Inconel 718, 905-908
 - life prediction, 916-919
 - multiaxial theories, 901
 - SAE 1045 steel, 907, 909-911
 - 304 stainless steel, 903-905
 - 316 stainless steel, 902-905
 - strain amplitude dependency, 914
 - tension states, 913
 - torsion, 903, 913, 916-917
 - fatigue, 901
 - transition from stage I to stage II, 900
- Crack initiation, 236-255, 261-263, 438, 611, 657, 711-712, 751-764, 812, 838, 874, 934, 938, 1115, 1218
 - acceleration by oxide failure, 197
 - center notched specimen, 237-238
 - computer simulation, 1227, 1229
 - continual observation, 1185
 - criterion, 421
 - cycle period and prior exposure role, 569, 572-573
 - definition, 560, 665, 876, 1117
 - double edge notched specimen, 237-238
 - duplex stainless steel, 817-818
 - elevated temperature, 968
 - endurance, 713
 - equiaxed cast superalloy, 836
 - experimental procedure, 752
 - formation of longitudinal shear crack, 886, 888
 - materials, experimental apparatus, and procedure, 237-239
 - microfracture processes, 755
 - microstructure, 900
 - multiaxial fatigue, 867
 - Neuber's rule, 1089
 - Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 381-382
 - notched specimen, 886, 890-891, 896, 949, 951-954
 - oxidation-assisted, 573

- from oxide pits, 568, 570-571
- period, as function of failure life, 421
- polycrystalline 316L stainless steel, 442-443, 446-448
- preferentially oxidized interdendritic areas, 668
- relative notch opening displacement, 236, 240
- shear planes, 900
- single-crystal 316L stainless steel, 448-449, 452-453
- site
 - duplex stainless steel, 814
 - equiaxed cast superalloy, 833-835
- strain amplitude versus number of cycles, 585
- TC6 titanium alloy, 843-844, 844-850
- versus total mechanical strain range, 669
- Waspaloy, 733, 736
- Crack initiation life, 238-240, 715, 1016, 1020, 1116
 - equation, 236
 - evaluation method, 244
 - versus hold time, 248-249
 - law, 240-242
 - versus parameter $T(\log t_p + C)$, 244, 246
 - prediction, 993
 - ratio, 239-240
 - scatter, 248, 250-254
 - temperature dependence, 242, 245
- Crack length, 1052
 - cycle ratio, 1193
 - densities, polycrystalline 316L stainless steel, 446-448
 - fatigue damage, 1193-1194
 - fatigue life, 1044
 - numbers of cycles, 1054
 - versus strain state, 894-895
 - switching of strain level, 1190
- Crack opening, 209
 - plastic strain, 220, 222
 - ratio, R variation, 225
 - variation with depth, 223
- Crack propagation, 558, 711-713, 938, 951, 955-958, 961, 972, 1048, 1164-1172, 1218
 - compressive overloads, 174
 - computer simulation, 1227, 1229
 - continual observation, 1185
 - cycle- and time-dependent, 1165-1167
 - cycle period role, 573-574
 - equiaxed cast superalloy, 836
 - failure phases, 713-716
 - law, austenitic stainless steels, 420
 - nickel-base superalloys. *See* Nickel-base superalloys
 - obstacles, 900
 - predicted and experimental, 1230-1231
 - simulation, 1225, 1227-1231
 - TC6 titanium alloy, 850-851
 - threshold, 573
 - values of m , 970
- Crack propagation life
 - equation, 236
 - versus hold time, 248-249
 - law, 242, 244-248
 - versus parameter $T(\log t_p + C)$, 244, 247
 - temperature dependence, 242, 245
- Crack propagation rate, 1163
 - creep fatigue, 435
 - versus creep J -integral range, 1171-1172
 - 1Cr-1Mo-0.25V steel, 1164, 1168
 - versus fatigue J -integral range, 1170
 - intergranular crack, 425, 427
 - 304 stainless steel, 1164, 1169
- Crack tip, 1049
 - condition, 724
 - division pattern, 1053, 1055
 - strain field, plastic deformation, 1053-1057
 - stress, redistribution and plastic zone correction, 1026
 - TC6 titanium alloy, 848-849
- Crack-tip opening displacement, 313, 315, 725-726
 - creep-fatigue, 317-319
 - fatigue, 317
 - total, 318-319
- Creep, 107, 329, 340, 414, 531, 711, 961, 1096, 1237
 - cavitation, endurance effect, 722-726
 - characteristics, 588, 598-599
 - combined with fatigue, 114-119
 - components, 596, 600-603
 - cracking, 588
 - 9Cr-1Mo-V-Nb steel, 111-112
 - definition, 589
 - deformation, 1199
 - fatigue behavior, 367
 - frequency effect, 597, 606
 - incremental intergranular damage law, 429
 - isochronous and relaxation, 115
 - Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 376
 - overstress dependence, 515-516
 - reversal stress influence, 114
 - temperature and period effect, 596-597, 604-605
 - total strain energy density, 1258
- Creep crack growth
 - characteristics, 589-590
 - rate, René 95, 298-300
- Creep damage, 313, 314, 1252
 - Franklin's cyclic creep damage equation, 1122-1123, 1125

- Creep damage (*cont.*)
 intergranular fracture due to, 322
 life prediction, 1121-1124
 Spera's accumulated creep damage method, 1121-1122, 1124
- Creep ductility, 544-545, 547
 creep-fatigue resistance, 428-431
 versus creep life, 430
- Creep-fatigue, 329, 342, 414, 588, 625
 crack density, 434-435
 crack propagation
 path, 422
 rate, 435
 crack-tip opening displacement due to, 317-319
 cycle, total-strain-range and life, 332
 environment study, nickel-base superalloys, 294-295, 297-303
 fatigue life, 418
 initiation period, 435
 intergranular damage, 431
 Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 371-383
- overstress concept application, 487-499
 back stress, prediction, 492-493
 damage parameter, 493-495
 damage rate equation, 497
 elastic core, 496-497
 experimental procedure, 488
 failure criterion, 495
 linear damage rule, 495-496
 strain waveforms, 489
 stress-strain response, 490-491
 test results, 488, 490
 unloading behavior, 491
- resistance, creep ductility, 428-431
 solder joint, fatigue, 589-590
- Creep-fatigue crack growth, 281-292
 application, 289-290
 constant displacement amplitude cycling, 287
 constant load amplitude cycling, 286
 cycle to time dependent cracking, 282-283
 data interpretation, 288-289
 experiments, 283-285
- Creep-fatigue degradation, 1096-1111
 analysis methods, 1099
 basic philosophy, 1097
 experimental work, 1102-1104
 finite element analysis, 1100-1102
 Neuber notch strain range analysis, 1099-1100
 uniaxial low cycle fatigue parameters, 1097-1099
- Creep-fatigue interaction, 313-326, 1066
 cavity, growth, 316-317
 creep ductility, 544-545, 547
 creep-fatigue testing, 544, 546-547
 creep rupture, 548
 creep testing, 544, 547-548
 damage accumulation, 545, 548
 experimental procedure, 319-320, 544
 life prediction, 319
 microstructure, 549-554
 model, 314-316
 intergranular damage, 435
 nitrogen effect, 543-556
 nucleation of cavities and cavity spacing, 316
 plastic strain range, 321
 relaxation during hold times, 545, 549
 round cavities, 315
 specimen geometry, 320
 stress-strain pattern, tensile hold period, 314
 test, 544, 546-547
 304 stainless steel, 237, 239
 unstable crack advance, 315
 wedge-crack formation, 552-553
 see also Viscoplasticity, based on overstress
- Creep-fatigue life, stress relaxation, 427-428
- Creep-fatigue life prediction, 399-412, 500-517
 analytical stress-strain behavior, 405-410
 component stress history, 510, 512-515
 creep-fatigue test data, 509
 cycles to failure, 401, 511
 cyclic creep test, 505-506
 cyclic relaxation test, 503-505
 cyclic stress-strain response, 402-405, 510-511
 damage parameter evaluation, 507-509
 hysteresis loop, 409
 incremental dwell, 503-505
 inelastic analysis, 407-408
 inside hysteresis test, 505-507
 minimum creep rate, 407

-variation, 514
 relaxation curve, 410
 strain-hold test, 403
 simulation, 508, 510
 strainrange partitioning, 402
 strength coefficient, 406-407
 stress-strain
 history at critical area, 513
 under operating conditions, 514-516
 testing procedure and conditions, 400, 502-504
 test machine control, 503
 test material and specimen, 400, 406-407, 502
 test system description, 503
- Creep *J*-integral range, 1163
 versus crack propagation rate, 1171-1172

- Creep law, 112
- Creep life
 - versus creep ductility, 430
 - versus intergranular creep damage, 430
- Creep properties, 399, 406
 - inelastic analysis, 408
- Creep rate
 - grain boundary, 591
 - HP-IP steam turbine rotor, 1239
 - minimum, master curve, 407
 - Monkman-Grant rule, 1123
- Creep rupture, 548
 - strength, master curve, 404
- Creep strain, versus time, 112, 120
- Creep test
 - austenitic stainless steels, 237, 239, 416
 - creep-fatigue interaction, 544, 547-548
- Critical plane concepts, multiaxial fatigue, 866-869
- Critical strain, 1063-1064
 - grain-boundary crack initiation, 616-617
- Critical stress drop, 49-50
- 1.25Cr-0.5Mo steel, 1097
 - Manson-Coffin relation, 1107
 - materials property, 1105
 - notch test, 1108
- 2.25Cr-1Mo steel, 412
 - compressive hold period effect, 715-716
 - crack growth, 286-287
 - displacement versus time, 286
 - rate versus C^* , 288
 - cyclic hardening/softening, 45, 47, 924-926
 - elastic core, 496-497
 - inelastic strain range versus number of cycles to failure, 1173-1174
 - low-cycle fatigue parameters, 46
 - monotonic mechanical properties, 46
 - strain energy parameters, 1173-1174
 - variable amplitude straining, 922-937
 - see also* Constant amplitude straining; Creep-fatigue life prediction
- 9Cr-1Mo-V-Nb pressure vessel steel, cyclic stress-strain time response, 107-122, 112-114
 - combined creep and fatigue, 114-119
 - creep, 111-112
 - hardening, modulus and coefficient of thermal expansion data, 121
 - hysteresis loops near half life, 117
 - material, 108
 - monotonic and cyclic hardening, 108-111
 - one-bar restrained thermal cycling test, 117-118
 - two-bar ratchetting test, 118-120
- 12Cr-Mo-V-Nb steel, 973
 - chemical composition, 973
 - defect size and fatigue life, 978, 980
 - variable strain range, 975-976, 979
- 1Cr-1Mo-0.25V steel
 - chemical composition, 973
 - crack propagation rate, 1164, 1168
 - strain energy parameters, 1177
 - variable strain range, 975, 978
- 1Cr-Mo-V steel, 972, 1259
 - chemical composition, 1238
 - fracture surface, 220
 - low cycle fatigue characterization, 1237
 - tensile properties, 1239
- 20Cr-25Ni-Nb stainless steel
 - cold work effect, 719-720
 - cycle shape effect on fatigue, 722-723
 - cyclic stress-strain response, 719
 - grain size effect on fatigue life, 718-719
 - intergranular creep cavitation, 724
 - Manson-Coffin plot, 713-715
- 1Cr-18Ni-9Ti
 - chemical composition and mechanical properties, 1134
 - observed versus predicted lives, 1141
 - strain energy partitioning life relationships, 1138
- Cu-2Al
 - dislocation structures, 65-66
 - stress-strain curve, 67
- Cu-4Al
 - dislocation structures, 67-68
 - stress-strain curve, 68
- Cu-8Al
 - dislocation structures, 67-68
 - incremental-step test, 72
 - multiple-step test, 71
 - plastic-strain limit test, 71
 - saturation stress, 74
 - slip band spacing and alternating plastic strain, 68, 73
 - stress-strain curve, 69
- Cumulative damage, 1144
 - Kettunen and Kocks relationship, 89
 - linear plot for life in time and in repeated cycles, 255
- Cumulative damage law, 236
 - application, 540-541
 - life in time and in repeated cycles, 248, 250-251
- Cumulative fatigue damage, 15
- Cumulative fatigue theory, 30-31
 - new damage equation, 34-35
- Cycle ratio, 757, 761
 - crack length, 1193
- Cyclic behavior, 107
- Cyclic constitutive behavior, 692
- Cyclic crack growth relation, 209

- Cyclic creep test, creep-fatigue life prediction, 505-506
- Cyclic deformation, 1218-1235
- applications in automotive design, 1231-1234
 - crack propagation simulation, 1225, 1227-1231
 - cycle stress-strain response, 1218
 - interactive load history, 1231-1233
 - modelling
 - material memory behavior, 1221-1223
 - using push-down list counting, 1223-1227, 1234
 - monotonic boundary points, 1223-1224
 - notch effects analysis, 1225, 1228
 - phenomena, 1220-1221
 - rheological spring-slider model, 1218-1219
 - stress, fatigue mechanism map, 524, 526-527
- Cyclic hardening, 519-520, 527, 638-639, 1099
- aging treatment effect, 802, 805
 - aluminum alloys, 95
 - B-1900 + Hf, 642, 645, 650-654
 - 2.25Cr-1Mo steel, 924-926
 - 9Cr-1Mo-V-Nb steel, 108-111, 121
 - dislocation structure, 74
 - duplex stainless steel, 814-815
 - face-centered-cubic alloys. *See* Face-centered-cubic alloys
 - kinematic, FEM analysis, 1072, 1074-1075, 1077
 - MARC-type combined, 1073, 1076
 - material properties, 1221
 - polycrystalline 316L stainless steel, 440-441, 443
 - simulation under strain control, 134
 - single-crystal 316L stainless steel, 443-445, 450
 - 304 stainless steel, 133
 - 316L stainless steel, 800
- Cyclic hardening exponent, 211, 229
- aluminum alloys, 104
 - singularity values, 1061
- Cyclic *J*-integral, 257, 264, 995
- crack growth rate, 978, 980
 - strain intensity factor range, 260-261
- Cyclic load, 1096
- Cyclic load-notch stress range, 1017-1019
- Cyclic plasticity, 399
- Cyclic plastic strain range, maximum, 1193
- Cyclic plastic stress-strain response, 2.25 Cr-1Mo steel, 55
- Cyclic 0.2% proof stress
- surface as function of temperature and strain rate, 523
 - temperature dependence, 520, 522
- Cyclic relaxation test, creep-fatigue life prediction, 503-505
- Cyclic saturation stress-strain curves, single-crystal 316L stainless steel, 445
- Cyclic softening, 519-520, 527, 577, 838, 978
- aging treatment effect, 802, 805
 - B-1900 + Hf, 642, 645, 650-654
 - 2.25Cr-1Mo steel, 924-926
 - duplex stainless steel, 814-816
 - material properties, 1221
 - TC6 titanium alloy, 843
- Cyclic strain amplitude, versus life curve, 86-87
- Cyclic stress range behavior, effect of tension hold times, 473, 476
- Cyclic stress-strain response, 43, 257, 267, 1007, 1015
- aluminum alloys, 95, 97
 - analytical expression for service set, 929
 - basic and service, 930-931
 - B-1900 + Hf, 654
 - cast steel, 1148
 - 2.25Cr-1Mo steel, 924, 927-928
 - 20Cr-25Ni-Nb stainless steel, 719
 - creep-fatigue life prediction, 510-511
 - 9Cr-1Mo-V-Nb steel, 116
 - cyclic deformation, 1218
 - different temperatures, 45, 47
 - duplex stainless steel, 816
 - hysteresis loops, 1252
 - magnesium-aluminum alloy, 721
 - nickel-based superalloys, 457-458
 - Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 375
 - OFE copper, 151, 153
 - parameters, 932
 - plastic-strain limit-test, 59
 - René 80, 463, 695
 - review of experimental data, 639-640
 - SAE 1038 steel, 79-80, 82-84
 - S10C steel, 274
 - S35C steel, 274
 - SNCM 439 alloy steel, 274
 - 316 stainless steel, 713, 715, 717
 - 316L stainless steel, 800, 803
 - thermomechanical fatigue, 638-655, 661-662
 - isothermal cycling, 646-647
 - variable amplitude straining, 929-932
 - weight of points, 935, 936
- Cyclic stress-strain test, 693
- Cyclic stress-strain-time response. *See* Constant amplitude straining
- Cyclic yield stress, temperature dependence, 45, 49

D

- Damage**, 487, 1237
 accumulation, 751
 creep-fatigue interaction, 545, 548
 per block/cycle, 1017
 definition, 144
 equation, new, cumulative fatigue analysis, 34-35
 function method. *See* Ostergren model
 measurements, 414
 mechanisms, 638, 745, 1253
 model, nonlinear. *See* Nonlinear history-dependent damage model
 monitoring system, 981
 postulate, 147, 149
 rate equation, 497
 rule, 979
- Damage analysis**, 143-144
 concepts and assumptions, 144-146
 procedure, 145
- Damage curve approach**, 15, 34, 156
- Damage development**, 874-897
 background, 876-877
 crack sizes and life, 882
 damage state as function of ratio of applied moments and life regime, 892-894
 intermediate to long life load cases, 885-888
 macroscopic growth behavior, 892-893
 material, 877
 notched shaft, 878, 885, 896-897
 short life load cases, 886, 890-892
 similitude assumptions, 875
 thin-wall tube, 877-885, 892, 894-895
- Damage parameter**, 993
 definition, 144
 evaluation, 507-509
 history-dependent, 156
 primary, 901
 semiempirical, 994
 time-dependent, 494-495
 time-independent, 493-494
- D-c potential drop method**, 1083
- Dead-load creep machine**, 285
- Decohesion zone**, 469
- Deep crack**, growth, 227-229
- Defects**, 972
 size
 and fatigue life, 980
 toleration, 233
- Deformation**
 1070 steel. *See* 1070 Steel, under thermal loading
 theory, 1049
 work density, 1213
- Diametral strain**, 259, 577
- controlled fatigue tests, 162
 maximum amplitude, 923-924
 versus fatigue life, 928, 933
 mean, 416
 relaxation rate, versus stress drip, 45, 49-50
 versus stress amplitude, 45, 48
- Diffusion-controlled cavity growth**, 437
- Directional coarsening**, 638, 647, 652-653
- Dislocation**
 behavior, 812
 cell after creep-fatigue, 549-550
 size and alternating plastic strain, 66, 72
 partial, 653
 spacing, 578
 tangling, 73, 549-550
- Dislocation structure**, 776
 B-1900 + Hf, 650-652
 change due to cyclic straining, 522, 525
 copper, 65-66
 copper alloys, 65-648
 cyclic hardening, 74
 fatigue mechanism map, 524, 526-527
 relaxation, 629
 unaged C-alloy, 789, 792-793
 unaged N-alloy, 779, 781
 Waspaloy, 730, 734, 736-737, 741, 744-745
- Dog-leg cycle**, 630
- Double-damage curve analysis**, 34
- Double edge notched specimen**, 237-238
- Double-linear damage rule**, 15, 34, 934, 937
- Ductility**, exhaustion of, 161
- Ductile refractory alloy**, comparison of bithermal and thermo-mechanical fatigue behavior, 631
- Ductile-type fracture**, 60Sn-40Pb solder, 349
- Ductility**, 1048, 1050
 loss
 fatigue life effects, 168-170
 superposed effects of microcracks, 170-171
 316L stainless steel, 806
 strain aging ferrous alloys, 779-780
- Duplex microstructure**, slip bands, 846
- Duplex stainless steel**, 812-822
 aging, 822
 behavior in 3.5% NaCl solution, 818, 820-821
 chemical compositions, 813
 crack initiation, 817-818
 sites, 814
 cyclic deformation, 815-817
 cyclic stress-strain response, 816
 experimental procedure, 813
 hardening/softening curves, 814-815
 Manson-Coffin relationship, 813-814

Duplex stainless steel (*cont.*)
 mechanical results, 813-814
 plastic strain amplitude effect on fatigue life, 822
 twinning, 815-817
 Dwell time, 414, 437

E

ECD
 chemical composition, 534
 experimentally determined parameters, 536-537
 Eigen strain
 grain boundary, 617
 inclusion D_0 , 614-616
 Elastic core, 496-497
 Elastic-plastic finite element analysis, notch specimen, 1007-1008
 Elastic-plastic strain-stress analysis, 1022
 FEMFAT, 1000-1003
 Elastic strain energy distribution
 ahead of penny shape crack, 1028
 ahead of through crack, 1029
 consequences of energy density equivalence
 near blunt notches, 1041, 1043-1045
 near crack tip, 1034-1036
 crack plane, 1025-1026
 elastic
 near blunt notches in plane stress, 1036-1037
 near cracks, 1025-1027
 elastic-plastic
 near blunt notches in plane stress, 1037-1038
 near cracks, 1027-1029
 equivalent strain energy density hypothesis, 1030-1034, 1038, 1040-1041
 grain boundary, 612-614
 near-tip local stresses, 1026
 number of cycles to failure, 528
 Elastic stress
 distribution
 ahead of edge notch, 1039
 notch, 1147-1150
 gradient, 1147
 Elastic stress concentration factor, 1078
 number of cycles to failure as function of, 1083, 1087
 Electrohydraulic closed-loop testing system, 44
 Elevated temperature, 123, 313, 519, 543, 611, 692, 728, 798, 961, 972, 1066, 1199
 constant amplitude straining, 43-56
 cyclic stress-strain-time response. *See* Constant amplitude straining
 fatigue-creep, 470

high frequency vibrations, 966, 968-969
see also High temperature fatigue
 Endurance, 726, 1096-1097
 creep cavitation effect, 722-726
 HP-IP steam turbine rotor, 1247-1248
 integrated, 209
 strain rate and hold time effects, 1248
 Environment, 456, 558, 728
 Equiaxed cast superalloy, 824-836
 crack initiation, 836
 site, 833-835
 crack propagation, 836
 experimental procedure, 825
 fractography, 831-834
 grain boundary, 828-829
 hot isostatic pressing, 834-836
 low-cycle fatigue, 826, 830-832
 metallography, 826-830
 monotonic data, 826, 830
 porosity, 834-835
 S/N curves, 830-832
see also B-1900
 Equiaxed microstructure, slip bands, 846
 Equilibrium stress, 125
 Equivalent harmonic cycle, 934

F

Face-centered-cubic alloys, testing method effects, 58-75
 experimental methods, 60-62
see also Multiple-step test; Plastic-strain limit test
 Failure behavior, 331
 Failure life, correlation between experimental and calculated, 166-167
 Failure mode
 Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 380, 382
 Waspaloy, 745
 Fatigue, 329, 399, 531, 611, 711, 765
 combined with creep, 114-119
 compression and compressive overload effects, 173-182
 materials, equipment and test techniques, 174-176
 smooth specimen design and dimensions, 175
 crack-tip opening displacement due to, 317 cycle
 plastic strain components, 590-591
 shape effect, 722-723
 fatigue aged C-alloy, 789-791
 high frequency vibrations, 963-965
 mechanisms, 812
 models, 456
 notch factor, 1146-1147

- keyhole specimen, 1152
- notched strip specimens, 1152
- propagation life, TC6 titanium alloy, 844
- properties, 776
 - fatigued and aged N-alloy, 784-787
 - unaged N-alloys, 778-784
- rate, 588
- softening, 43, 55
 - SAE 1038 steel, 83-84, 88
- stages, 988
- strength, anisotropy, 1181, 1195-1197
- striations, 946, 950, 954
 - Ti 6-4 alloy, 946
- temperatures above $0.5 T_m$, 528-529
- temperatures below $0.5 T_m$, 528
- test
 - notched strip specimen, 1149-1151
 - 304 stainless steel, 237, 239
- time-dependent, 15, 1133
- toughness, aluminum alloys, 103-104
- unaged C-alloy, 787-789
- Fatigue analysis
 - FEMFAT, 996-997, 999
 - notch analysis concepts, 990-995
- Fatigue-creep, 470
 - crack propagation characteristic, 540
 - interaction map, 531-532
 - tests, 1096
- Fatigue damage, 314, 1181
 - coefficients, AL-0.97Mg alloy, 855-856
 - crack length, 1193-1194
 - defined, 10
 - energy-based criterion, 1256-1258
 - 1070 steel. *See* 1070 Steel, under thermal loading
- Fatigue ductility coefficients, 102, 104
- Fatigue failure, 160
 - austenitic stainless steel, 717-720
 - cold work effect, 719-720
 - grain size effect, 718-719
 - test temperature effect, 716-717
 - magnesium alloy, 720-722
 - mechanism, 712-716
 - crack initiation, 712
 - crack propagation, 712-713
 - endurance of crack initiation and propagation phases of failure, 713-716
 - see also* Fatigue life
- Fatigue hardening-softening curves, 55, 77, 86, 88
 - 2.25 Cr-1MO steel, 45, 47
 - SAE 1038 steel, 83-84
- Fatigue J -integral range, 1163
 - versus crack propagation rate, 1170
- Fatigue life, 43, 77, 776, 1022-1045, 1144-1161, 1199
 - aging treatment effect, 802, 804
 - AIISI H13 hot-work tool steel, 583, 585-587
 - compressive stress, 177-178
 - constant lines, biaxial stress, 862
 - crack length, 1044
 - crack size, 882
 - creep fatigue, 418
 - 2.25 Cr-1MO steel, 55-56
 - curve derivation, 267-278
 - versus cycle frequency, 51-52, 346-347
 - in cycles, 137
 - cyclic strain amplitude, 86-87
 - definition, 664, 1117
 - ductility loss effects, 168-170
 - versus effective strain, 864
 - environmental degradation, 340
 - equation, 1163
 - experimental and predicted, 323-326, 1109-1110, 1156-1159
 - fraction, secondary crack density, 422
 - frequency and coating influence, 562
 - frequency dependence, 351
 - versus frequency/strain range, 597, 606
 - fully reversed cycles, 180-182
 - inverse relationship with matrix creep, 588
 - isothermal and thermo-mechanical fatigue, 670
 - linear damage rule, 1153-1154
 - load-strain model, 1154-1156, 1158-1159
 - load versus strain at equivalent characteristic length, 1157
 - matrix creep, 598, 600, 604, 608
 - maximum diametral strain amplitude, 928, 933
 - mean strain dependence, 752-753
 - microcrack propagation law, 1188-1189
 - modified Neuber's rule, 1153, 1158-1159
 - Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 377-379
 - normalized, versus normalized prestrain, 169, 171
 - notched components, 992-993
 - oxygen pressure effect, 567
 - p -change effect, 515
 - plastic strain amplitude effect, 822
 - polycrystalline 316L stainless steel, 441, 444-445
 - predicted, 276-278, 932
 - pre-oxidation effects, 1213-1215
 - SAE 1038 steel, 85
 - single-crystal 316L stainless steel, 445, 448, 451
 - 316L stainless steel, 801, 804
 - stress, 963-964
 - stress amplitude, aluminum alloys, 101
 - surface as function of temperature and strain rate, 524
 - TC6 titanium alloy, 851

Fatigue life (*cont.*)

- temperature and strain rate dependence, 522-524
- thermo-mechanical blocking loading, 191-192
- thermo-mechanical constant amplitude, 190
- total grain boundary creep, 598, 607
- total plastic energy, aluminum alloys, 101
- total plastic work per cycle, 1101
- total-strain-range, creep-fatigue cycle, 332
- variable amplitude load spectra, 1157
- variable amplitude straining, 929, 932-934
- see also* Creep-fatigue interaction; Fatigue failure

Fatigue life laws

- comparison of derived laws with existing laws, 1173
- cycle-dependent fatigue, 1164, 1169
- smooth specimen, 1164, 1169, 1172-1173
- time-dependent fatigue, 1169, 1173
- verification, 1173-1175

Fatigue loading, Inconel 625, 476-478

Fatigue mechanism map, 519-529

- change in dislocation substructure due to cyclic straining, 522, 525
- cyclic deformation stress and dislocation substructures, 524, 526-527
- experimental procedure, 520
- fatigue life, 527
- fracture modes, 524, 526-527
- temperature
 - above $0.5 T_m$, 528-529
 - below $0.5 T_m$, 528
- strain rate dependence of fatigue life, 522-524

Fatigue resistance

- austenitic stainless steels, 438
- bulk and surface control, 148
- deformation history dependence, 156
- OFE copper, 151-152
- predicted and observed, 155-156
- 316L stainless steel, 807-808
- transient flow behavior, OFE copper, 151-152

Feltner and Landgraf strain resistance prediction criterion, 85

FEM analysis, 672, 987, 1007, 1048, 1053, 1056, 1066, 1100-1102, 1144, 1146-1147

- constitutive relation, 1071
- constitutive equations, 1079
- cyclic, and strain measurement, 1067-1078
- elastic-plastic-creep, cyclic loading, 1067-1082
- equations, René 80, 701-702
- finite element mesh, 1070, 1079, 1101

kinematic hardening, 1072, 1074-1075, 1077

MARC, hysteresis loops, 1102

MARC-type combined hardening, 1073, 1076

monocrystalline superalloys, 681-682

notch strain

plane strain, 1011

plane stress, 1010

original and improved meshes, 1075-1078

predicted and experimental fatigue lives, 1089, 1092

programs for cyclic analysis, 1067-1068

specimen

dimension, 1053, 1055

plane strain, 1010

plane stress, 1009

stress/strain concentration factors, monotonic loading, 1079-1082

test specimen, 1069

FEMFAT, 987

application, 997-998

elastic-plastic multiaxial stress/strain behavior, 1000-1003

elements, 996

fatigue analysis, 996-997, 999

stress/strain analysis, 995-996

Ferritic Fe-26Cr-1Mo-5Ni alloy

cyclic deformation, 814-815

dislocation structures, 821

stress-strain response, 820

twinning, 815, 819

Ferritic-pearlitic steels. *See* SAE 1038 steelFerrous alloys. *See* Strain aging ferrous alloys

Fibrous precipitation, 549-551

Fixed plastic strain range, 588

Flow stress, 577

B-1900 + Hf, 653-654

Fractography, 961

austenitic stainless steels, 416, 419-427

equiaxed cast superalloy, 831-834

316L stainless steel, 805, 809

Fracture, 1237

factory roof, 901

macroscopically flat, 915-916

mechanics, 281, 282

SEM, 538-539

surface, 554

morphologies, high frequency vibrations, 966-967

316L stainless steel, 806-808

toughness, aluminum alloys, 103-104

Fracture life

versus parameter $T(\log t_p + C)$, 244, 247

temperature dependence, 242, 245

Fracture mode, 524, 526-527

René 95, 302

variation with mean strain, 760
 Waspaloy, 305
 Franklin's cyclic creep damage equation, 1122-1123, 1125
 Frequency-modified damage function, 393-395
 Frequency-modified low-cycle fatigue, 365-367
 Frequency separation, 1133
 life predictabilities, 1142
 life prediction equations, 1136, 1138
 model, 393-394
 Future directions, 7-12, 15-39, 1197
 constitutive behavior emphasis, 28-30
 cumulative fatigue theory, 30-31
 new damage equation, 34-35
 drive to organize meetings and symposia, 24-25
 emergence of China and other Asian technologies, 25-26
 emphasis on fundamentals, 27
 generalized Neuber equation for notch analysis, 32, 34
 improved formulation for treating mean stresses, 34, 36-37
 modified universal slopes equation, 31-32
 new materials, 26-27
 next twenty-five years, 16-17
 potential report proliferation, 17-20
 predicting bending fatigue from axial fatigue data, 31-33
 thermo-mechanical fatigue, 37-38
 time-effects on strainrange partitioning components, 38-39

G

GH36
 chemical composition and mechanical properties, 962, 1134
 observed versus predicted lives, 1141
 strain energy partitioning life relationships, 1139
 GH33A
 chemical composition and mechanical properties, 1134
 observed versus predicted lives, 1140-1141
 strain energy partitioning life relationships, 1139
 Gibbs-Thomson equation, 579
 Grain boundary, 838
 B-1900, 829
 carbide formation, 746
 cavitation, 554-555
 cavity nucleation and growth, 313
 chemistry, nickel-base superalloys, 295-297, 303-304

cohesive strength, 458-460
 creep, 595
 fatigue life, 598, 607
 cavities, 726
 rate, 591
 deformation, fatigue aged C-alloy, 791, 795
 diffusion, 615
 diffusion coefficient, 1210
 embrittled, 747
 equiaxed cast superalloy, 828-829
 oxidation, 1199-1216
 activation energy, 1211
 aspect ratio, 1206, 1210
 channeled one-dimensional flow model, 1209-1210
 cone-type oxide, 1206
 cross-sectional micrograph, 1201, 1203, 1205
 fatigue reversals as function of deformation work density, 1214-1215
 line profiles of Ni, Cr, and Al, 1201, 1204
 oxide depth, 1206, 1208
 oxygen concentration, 1209
 pancake-type oxide, 1207
 parabolic rate constant versus inverse absolute temperature, 1201-1202
 penetration, 1205-1213
 pre-oxidation effects on fatigue life, 1213-1215
 relationship between weight gain and oxidation exposure time, 1201
 specimen configurations, 1214
 spectrometric analysis, 1204
 surface oxidation, 1200-1205
 Weibull plot, 1208
 oxygen penetration along, 303
 power law expression, 590
 sliding, 555
 Waspaloy, 731
 Grain-boundary crack initiation, 611-621
 calculation of elastic strain energy and internal stress of grain boundary, 612-614
 critical shear strain, 617
 critical strain, 616-617
 diffusion flux, 615
 flux of atoms, 615
 high temperature fatigue, 617-619
 internal stress and eigen strain in inclusion D_0 , 614-616
 migration rate, 615
 number of cycles, 619-620
 shear strain change, 617-618
 stress field outside inclusion, 616
 Stroh's equation, 616
 wedge-type cracking, 616, 618
 Grain boundary creep, 588

Grain-boundary sliding, 29, 529, 611, 619
 blocking of, 614
 model, 617
 Grain size, 605
 Al-Mg-Si alloys, 766
 9Cr-1Mo-V-Nb steel, 109
 fatigue life effect, 718-719
 precipitates, 711
 Granulated-type fracture, 60Sn-40Pb solder,
 350
 Gray cast iron, 899
 cracking behavior, 910-912
 tension and torsion behavior, 913, 915
 Growth law, 125

H

Haig diagram, 942, 945, 947, 949
 Ti 6-4 alloy, 942, 945
 Hardening rule, 865
 High-cycle fatigue, 861, 961
 amplitude effect, 969-970
 High deformation fatigue, 77-92
 High frequency vibrations, 961-970
 effect of amplitude of high cycle fatigue
 stress, 969-970
 experimental procedure, 961-963
 fatigue behavior, 963-965
 fatigue crack paths, 965
 fracture surface morphologies, 966-967
 geometry of specimens, 962
 load spectra, 963
 High-strain fatigue crack propagation, 456
 High temperature alloys, 209
 crack growth rate, 227
 High temperature fatigue, 385, 456, 558, 657,
 1115, 1096, 1237
 grain-boundary crack initiation, 617-619
 nickel-base ODS alloy, 386-392
 316L stainless steel, 802-803, 805
see also Elevated temperature
 High-temperature low-cycle fatigue behavior
 life prediction, 1117-1120
 Historical perspective, 5-6
 Hold time, 43, 399, 415
 compression, 470, 473, 476
 cycles to failure, 436
 initiation stage, 423
 life prediction, 403-405, 410-411
 number of cycles to failure, 417
 relaxation during, 545, 549
 strain, 51-52
 stress, 53
 tensile, fatigue life effect, 722-723
 tension, 470, 472-473, 475-476
 Hollomon equation, 464

Hot isostatic pressing, 824-825
 equiaxed cast superalloy, 834-836
 microstructure, 826
 HP-45, 1097
 Manson-Coffin relation, 1106
 materials property, 1105
 notch test, 1108
 HP-IP steam turbine rotor, 1237-1259
 cavitation, 1250, 1252
 creep resistance curves, 1239
 damage mechanisms, 1253
 distribution of heavily segregated zones,
 1244
 endurance, 1247-1248
 energy-based criterion, 1256-1258
 experimental procedure, 1242, 1246
 hardness, 1249
 inclusions at rotor bore, 1243
 interaction between cavitation and crack
 growth, 1254
 linear damage summation rule, 1252-1253,
 1255-1256
 material, 1238-1242
 material effect, 1246-1249
 microstructure, 1238, 1240-1241
 parameters, 1245
 role, 1251-1252
 strainrange partitioning, 1252-1253, 1256-
 1257
 time effect, 1249-1250
 total strain energy density, 1258
 HRR singularity, 1049
 Hull-Rimmer model, 316-317
 Hypersurfaces, 1001-1002
 Hysteresis loop, 209
 Al-Mg-Si alloys, 768
 aluminum alloys, 94
 B-1900 + Hf, 642, 644
 creep-fatigue life prediction, 504
 distortion, 628
 hold position effect during tensile loading,
 138
 initial prestrain cycles, 176
 inside, 505-507
 isothermal fatigue, 591
 kinematic hardening, 1072, 1074-1075,
 1077
 load-displacement, 694
 load-strain, 1155
 MARC finite element program, 1102
 MARC-type combined hardening, 1073,
 1076
 with 10-min relaxation periods, 127, 129
 percent creep, 363
 produced by block loading, 117
 SAE 1038 steel, 80

shape, 94-95, 105, 1220
 crack growth, 220
 variation, 100
 slow/fast and fast/slow loadings, 128
 solder joints, 591
 square wave, 597, 601, 603
 steady-state, 128
 triangular wave, 597, 600, 602
 within hysteresis loops during strain-controlled loading, 130-132

I

Iida's formula, 166
 IN-739, 639
 IN100, 658
 crack depth variation with number of cycles, 664-665
 crack initiation, 668
 life versus total mechanical strain range, 669
 cyclic life, 468-469
 failure criterion, 462
 Hollomon equation, 464
 intergranular crack propagation path, 459
 Ludwik equation, 464
 main crack evolution, 662-663
 number of cycles, 666-667
 stabilized stress-mechanical strain loops, 662
 Inclusion, 972
 HP-IP steam turbine rotor, 1243
 Incoloy 800, 1097
 Manson-Coffin relation, 1106
 materials property, 1105
 notch test, 1108
 Incoloy 800H, 501, 1097
 Manson-Coffin relation, 1105
 materials property, 1105
 notch test, 1108
 Inconel, 899
 Inconel 625, 470-485
 chemical composition, 471
 comparison of predicted and observed life, 483
 continuous cycling, 471-473
 creep loading, 478-479
 experimental procedure, 471
 fatigue diagram, 472
 fatigue loading, 476-478
 high-temperature stability, 485
 hold time fatigue test, 474
 interspersed creep-fatigue tests, 472-477
 interspersed fatigue-creep, 479-482
 isothermal creep-rupture curve, 478-479
 life prediction, 476-482

strain parameters, 477
 stress range variation, 471, 473
 stress relaxation, 480-481
 rate, 472-473, 425
 Inconel 718, 939
 biaxial strain controlled fatigue tests, 867, 869
 correlation with shear strain parameter, 916-918
 cracking behavior, 905-908
 crack initiation, notched specimen, 951-953
 crack propagation, 955-958
 fatigue striations, 950, 954
 Haig diagram, 947, 949
 mechanical properties, 902
 number of cycles to failure, 947-950
 strainrange partitioning, total-strain version, 337-338
 Incremental damage accumulation law, viscoplasticity based on overstress, 135-136
 Incremental dwell test, creep-fatigue life prediction, 503-505
 Incremental-step test
 copper, 70
 Cu-8Al, 72
 cyclic hardening, 60-61
 SAE 1038 steel, 81-82
 saturation stress, 74
 Induction heating, 672-673, 690
 apparatus, 675
 Inelastic analysis, 399, 407-408
 constitutive equation, 405
 creep properties, 408
 plastic properties, 408
 Inelastic finite element analysis, 692
 Inelastic strain range, 492
 number of cycles to failure, 1117-1118, 1178
 number of cycles to initiation, 1118-1119
 viscoplasticity based on overstress, 124
 Inelastic volume fraction
 development of surface damage, 147
 similitude, 146-147
 Inside hysteresis test, creep-fatigue life prediction, 505-507
 Instron Corp., financial growth, 23
 Interaction damage rule, 53, 363, 1136
 Interactive load history, 1231-1233
 Inter-crystalline voids and cracks, 609
 Interdendritic damage fraction, as function of maximum stress, 536
 Interference plane, definition, 867
 Intergranular cavities, 556
 Intergranular crack, 185, 301, 414, 711
 austenitic stainless steels, 422, 424

Intergranular crack (*cont.*)

- path, 459
 - creep-fatigue interaction, 314
 - polycrystalline 316L stainless steel, 449
 - propagation rate, 425, 427
 - transition to transgranular, 454-455
- Intergranular creep, cavitation, 20Cr-25Ni-Nb stainless steel, 724
- Intergranular damage, 415, 422-423
 - creep-fatigue interaction model, 435
 - versus creep life, 430
 - evolution, 425
 - factor of crack propagation reduction, 424, 426-427
 - stress relaxation, 428-429
- Intergranular damage law, incremental, 429
- Intergranular decohesion, 469
- Intergranular fracture, 313, 519, 543
 - due to creep damage, 322
 - 316L stainless steel, 809
 - 60Sn-40Pb solder, 352-353
- Intergranular fractures, oxygen, 368
- Intergranular precipitation, 316L stainless steel, 809-810
- Intermetallic, 60Sn-40Pb solder, 351, 360-362
- Internal crack, 751
- Internal stress, 616
 - grain boundary, 612-614
 - inclusion D_o , 614-616
- Interspersed creep-fatigue tests, Inconel 625, 472-477
- Interspersed fatigue-creep
 - damage evaluation, 479-480
 - life calculation
 - compression hold times, 482
 - tension hold times, 481-482
 - loading pattern, 481
 - stress relaxation, 480-481
- Interstitial nitrogen, 316L stainless steel, 805-807
- Interstitial solutes, 776
- Isochronous stress, versus strain, 112-113
- Isothermal constant amplitude loading, stratified oxide layers, 193, 198
- Isothermal cycling, stress amplitude, 118
- Isothermal fatigue, 184, 1163
 - stresses, 191, 193-196
- Isothermal low-cycle fatigue, comparison with thermomechanical fatigue, 665-666, 668

J

- J -integral, 1163
- Journals, proliferation, 21

K

- Kettunen and Kocks relationship, 77, 88-89
 - engineering alloy values, 91
 - SAE 1038 steel, 89-90
 - versus saturation stress amplitude, 90
- Kinematic hardening, FEM analysis, 1072, 1074-1075, 1077
- Koe's equation, 1086
 - predicted and experimental fatigue, 1090-1091

L

- Landgraf's expression, 1154
- Large crack, through-thickness, 257
- Laser mirror assembly, 595
- LD-10 aluminum alloy, fatigue reversals as function of deformation work density, 1214-1215
- Lewis Research Center, 21-22
- Life fraction, time-independent, 494
- Life fraction rule, 399, 412
- Life prediction, 123, 257, 329, 371, 385, 487, 500, 531, 692, 861, 874, 899, 922, 938, 972, 987, 1007, 1016-1019, 1022, 1115-1131, 1144, 1237
 - cracking behavior, 916-919
 - crack initiation, 993
 - creep damage, 1121-1124
 - creep-fatigue interaction, 319
 - criterion, 947
 - equations, 1136-1138
 - experimental procedure, 1116-1117
 - experimental stress-strain behavior, 402
 - high-temperature low-cycle fatigue behavior, 1117-1120
 - hold-time effect, 403-405, 410-411
 - inelastic strain range, 1117-1119
 - Manson-Coffin laws, 124
 - methods, 708, 932
 - model, 457-464
 - physical basis, 457-458
 - notched specimen, 1082-1092
 - hold-time tests, 1089-1092
 - Koe's equation, 1086
 - Neuber's rule, 1083
 - no hold-time tests, 1082-1089
 - Stowell-Hardrath-Ohman's equation, 1086
 - ν - K , equation, 1083
 - oxidation-fatigue interaction crack growth model, 1124-1128
 - peak strain range, 1118-1119
 - quasi-fracture mechanics failure criterion, 458

René 80, 697-698
 rupture life, 541
 304 stainless steel, 496
 strainrange partitioning, 1120-1121
 strain-rate effect, 403-404, 410-411
 stress-hold and strain-hold data, 336, 338
 thermal fatigue, 1126-1129
 variable strain, 981-982
 viscoplasticity based on overstress application, 133-136
 Linear damage cumulation rule, 958-959, 1041
 derivation, 983
 Linear damage rule, 366, 495-496, 1120, 1136
 fatigue life estimations, 1153-1154
 Linear damage summation rule, 1257, 1237
 hold-time tests, 1255
 HP-IP steam turbine rotor, 1252-1253, 1255-1256
 Linear elastic fracture mechanics, 209, 225
 ratchetting, 232
 Load-controlled test, 209
 compared with strain-controlled data, 231
 increased displacement range, 231
 ratchetting, 230
 Load ratios, 939
 Load-strain hysteresis, cast steels, 1155
 Load-strain model, 1154-1156, 1159
 experimental and calculated crack initiation, 1158, 1160
 Local stress-strain analysis, notch specimen, 1014-1016
 Location parameter, 1207
 Low alloy steel, 399
 Lüders region, 88
 Ludwik equation, 464

M

MA 754 alloy. *See* Nickel-base ODS alloy
 Macrocrack, 886, 981
 Macroscopic growth behavior, 892-893
 Macroscopic low-cycle fatigue laws, 1181-1197
 material and test procedure, 1182-1183
 relation between cycle plastic strain range and number of strain cycles to failure, 1184
 specimen geometry, 1183
 waveforms for random loading, 1192
 Magnesium alloy, 711
 fatigue failure, 720-722
 Magnesium-aluminum alloy
 cyclic stress-strain response, 721
 temperature effect on fatigue life, 720-721
 Manson-Coffin curve, 44, 55

aluminum alloys, 94
 austenitic stainless steels, 547
 breaks, 95, 97, 99-100
 cycling with hold times, 52-53
 different temperatures, 45, 48
 20Cr-25Ni-Nb stainless steel, 713-715
 316 stainless steel, 713-714, 716-717
 Manson-Coffin endurance law, 419
 Manson-Coffin equation, 15, 30, 754, 1120, 1188
 Manson-Coffin fitting curves, 1246
 Manson-Coffin law, 16, 45, 55, 77, 344, 801, 836, 932, 1050
 frequency-modified, 342, 344
 life prediction, 124
 near crack tip in overall plastic deformation, 1053-1057
 validity, 257
 Manson-Coffin relationship, 5, 1181-1182
 1.25Cr-0.5Mo, 1107
 duplex stainless steel, 813-814
 furnace cooled and quenched C-alloy, 788-789
 HP-45, 1106
 IN100, 462, 464
 Incoloy 800, 1106
 Incoloy 800H, 1105
 nickel-based superalloys, 462-464
 René 80, 462-464
 solder joint, 589
 unaged N-alloys, 778-780
 Manson-Coffin strain-life relation, modified, 1041
 Manson's formula, 166
 MARC finite element computer program, 1100-1102
 MAR-MS09, 1115-1116
 Mar M247, 1178
 Masing's hypothesis, 1221
 Mathematical modeling, 123
 Matrix creep, 588-589
 fatigue life, 598, 600, 604, 608
 power law expression, 590
 Maximum stress criterion, 947
 Maximum stress life equation, 531-541
 cumulative damage rule application, 540-541
 experimentally determined parameters, 536-537
 fatigue-creep crack propagation, characteristic, 540
 fracture appearance, 538-539
 interdendritic damage fraction, as function of maximum stress, 536
 materials and procedures, 533
 maximum stress effect, 533, 535-540
 modified, 533, 536-537, 540

Maximum stress life equation (*cont.*)

- rupture life
 - versus predicted life, 541
 - dependence, 535
 - strain rate effect, 535
- Mechanical behavior of materials, milestones, 18
- Mechanical strain, 184
 - as function of time, 641, 643
- Memory events, 122-1223
 - compressive monotonic curve, 1222
 - effect on listing procedure, 1227
- Metallic materials, 257, 1218
 - polycrystalline, 611
- Metallurgy
 - austenitic stainless steels, 416, 419-427
 - TC6 titanium alloy, 839-840
- Microcrack, 164, 900, 1164
 - basket-weave microstructure, 846
 - fatigue life effects, 170-171
 - growth law, 1186
 - initiation, 1181
 - SAE 1045 steel, 907, 909
 - SNCM 439 alloy steel, 261
 - threshold stress for expansion, 459
 - Widmannstätten microstructure, 844-845
- Microcrack propagation, 657, 1181, 1187-1189
 - experimental and predicted lives, 1193-1195
 - single-crystal 316L stainless steel, 449, 453
- Microcrack propagation law
 - application, 1192-1197
 - Miner's rule, 1189-1191
- Microfracture, 753-756
 - mean strain effect, 756-763
 - mode map, 759
 - process, 751
 - surface crack, 755-756
 - types, 755
- Micromechanics model, 611
- Microstructure, 94, 711-726, 728, 838, 1237
 - aluminum alloys, 102
 - B-1900 after standard heat treatment, 826-827
 - creep cavitation effect on fatigue endurance, 722-726
 - creep-fatigue interaction, 549-554
 - evolution, 1249
 - hot isostatic pressing, 826
 - HP-IP steam turbine rotor, 1238, 1240-1241
 - mechanical properties, 824
 - parameters, HP-IP steam turbine rotor, 1245
 - role, HP-IP steam turbine rotor, 1251-1252

- 60Sn-40Pb solder, 351, 354-360
- TC6 titanium alloy, 839-840
- Widmannstätten, 839-840, 844-845
 - see also* Fatigue failure; Waspaloy
- Miner's rule, 180, 190, 1181-1182
 - derivation, 1189-1191
- Mismatch hoop strain, 1070 steel, 200, 202
- Mixed fatigue
 - definition, 942
 - Inconel 718, 957
 - prediction models, 958-959
 - Ti 6-4 alloy, 951, 955
- Modified universal slopes equation, 31-32
- Modulus, 9Cr-1Mo-V-Nb steel, 121
- Modulus of elasticity, 1037
- Modulus function, 125
- Mohr's circles of strain, 868
- Monitoring, 10-11
- Monkman-Grant rule, 1123
- Monocrystalline superalloys, 672-691
 - alloy composition, heat-treatment and coating, 673-674
 - chemical composition, 674
 - circumferential stress-strain history, 684-685
 - coating degradation, 686-690
 - finite-element model, 681-682
 - material properties, 681-683
 - stepped-disk specimen, 674
 - temperature history, 678-679
 - temperature history, 678-679, 682
 - test apparatus, 674-680
 - test specimens, 673-674
 - thermal fatigue tests, 680-681
 - thermoelastic finite-element analysis, 682-690
- Monotonic stress-strain response
 - aluminum alloys, 95, 97
 - OFE copper, 151, 153
 - SAE 1038 steel, 83-84
 - 316L stainless steel, 800, 803
- Mróz form circles, 1001
- Mróz model, 1000-1003
- Mróz segment, 999, 1001
 - damage, 1003-1005
 - elastic-plastic, 1003-1004
 - hysteresis loop, 1003-1004
- MTS Systems Corp., financial growth, 23
- Multiaxial fatigue, 861-871, 899
 - critical plane concepts, 866-869
 - damage development, 874-897
 - effective/equivalent concepts, 862-865
 - future directions, 869-871
 - material anisotropy, 873
 - model, 895
 - plastic work, energy concepts, 865-866

stress states, 987
theories, 916
 cracking behavior, 901
Tresca criterion, 863-864
von Mises criterion, 863-864

Multiaxiality, 30

Multiple-step test

copper, 70
Cu-8Al, 71
cyclic hardening, 60
prestrain, 73
SAE 1038 steel, 80

N

NaCl solution, duplex stainless steel, behavior, 818, 820-821

Neuber correction, 15

Neuber equation, generalized, notch analysis, 32, 34

Neuber hyperbola, 512-513

Neuber notch strain analysis, 1107, 1099-1100, 1109

Neuber relationship, 1227

Neuber's model, modified, 1158-1159

 crack initiation lives, 1159
 experimental and calculated crack initiation blocks, 1158

Neuber's rule, 1007-1020, 1083, 1099, 1144, 1153

 application, 1100
 crack initiation, 1089
 extension, analogous formulation, 1015
 FEM analysis, 1081-1082
 modified, 1153
 notch analysis, 1015-1016
 plane strain, regression, 1012
 plane stress, regression, 1011
 predicted and experimental fatigue lives, 1089
 proposed extension, 1009-1014

Nickel-base alloys, 555, 625, 938

Nickel-based superalloys, 27, 293-309, 329, 672, 692, 728, 1199-1200

 background, 457

 crack growth, 459

 rate, 460-461

 comparison of alloy behaviors, 307, 309-310

 creep-fatigue-environment study, 294-295, 297-303

 cyclic stress-strain response, 457-458

 grain boundary chemistry, 295-297, 303-304

 intergranular crack propagation path, 459

 life prediction model, 457-464

 modified compact tension specimen design, 295

 oxidation, 468

 quasifracture mechanics failure criterion, 458

 thermomechanical fatigue, 657-669

see also specific alloys

Nickel-base oxide dispersion strengthened alloy, 385-398

 experimental procedure, 386-387

 fatigue life, 397

 frequency-modified damage function, 393-395

 frequency-separation model, 393-394

 high-temperature low-cycle fatigue, 386-392

 inelastic strain range versus number of cycles to failure, 388

 lifetime prediction models, 392-396

 numbers of cycles to failure, 394-396

 specimen, 386

 strainrange partitioning, 395-396

 strain wave with compression hold time, 390

 sensitivity, 394

 with tensile hold time, 391-392

 triangular strain wave, 388-390

Ni-Co-Cr-Al-Y coated PWA 1480 superalloy, 371-383

 coefficients for models, 378

 constitutive behavior, 375-377

 cyclic life, 379, 381

 cyclic stress-strain behavior, 375

 failure mode, 380, 382

 life behavior, 377-379

 life model, 379-381

 low-cycle fatigue data, 374

 materials, 372-373

 stress-strain-time behavior, 376

 superalloy-coating interface, 384

 test procedures, 373

 values of constant ALPHA, 380

Nimonic 80, cavitation, 555

Nitrogen

 creep-fatigue interaction effect, 543-556

 interstitial, 316L stainless steel, 801, 805-807

Nitrogen steels, 798

Nonlinear history-dependent damage model based on bulk control, 147, 149-156

 damage postulate, 147, 149

 experimental aspects, 147, 149-151

 inelastic volume fraction and surface damage development, 147

 model framework, 151, 153-154

 similitude and inelastic volume fraction, 146-147

- Notch, 1007, 1022, 1144
 - elastic stress distribution, 1147-1150
 - sensitivities, 1151
- Notch analysis, 500, 513, 987
 - analytical expressions, 991
 - Creager and Paris stress field, 1031-1032
 - equivalent strain energy density hypothesis, 1038, 1040-1041
 - fatigue analysis on small and medium size computers, 990-995
 - generalized Neuber equation, 32
 - geometrical notches, 991-992
 - Neuber's rule, 1015-1016
 - parameters, 1018
 - welds, 992
- Notched shaft
 - AISI 4340 steel, 901
 - damage development, 878, 885, 896-897
 - stress gradients, 897
- Notched specimen, 1104
 - fatigue life, 992-993
 - geometries, 1103
 - keyhole, 1148, 1152
 - life prediction, 1082-1092
 - strip, 1148-1151
 - see also* Variable amplitude loading, notched components
- Notch effect, 209, 215, 874, 900, 1066-1094, 1225, 1228
- Notch equation, generalized, 513-514
- Notch specimen
 - distribution of relative damage, 1160
 - local stress-strain analysis, 1014-1016
- Notch strain analysis, 1144
- Notch stress, variation, 1014
- Notch tests, 1096
 - strain waveforms, 1098
- Notch tip, strain, 1041-1042
 - energy density, 1041, 1043
- Nucleation, 725
 - operational definition, 144
 - secondary crack rate, 433

O

- Ohji-Miller's hypothesis, 754-755
- Orowan looping, 749
- Ostergren model, 586-587, 696-697, 1133, 1136
- Overstress, 934
 - creep and relaxation dependence, 515-516
 - inelastic strain-rate dependence, 492
 - see also* Creep-fatigue, overstress concept application
- Oxidation, 185, 340, 438, 1115, 1199
 - carbide, 670
 - kinetics, 1199

- matrix, 1124-1128
- oxide depth, 1206, 1208
- rate, 574
- surface, 1200-1205
- weight gain during, 1200-1201
- see also* Grain boundary, oxidation
- Oxidation-fatigue interaction, 558-575
 - crack depth versus cycles, 563
 - crack growth model, life prediction, 1124-1128
 - helium environment, 567-568
 - mechanisms, 568-572
 - oxidation depths versus time, 572
 - oxygen-enriched environment, 560, 566-567
 - oxygen pressure role, 569
 - role of cycle period crack initiation, 569, 572-573
 - crack propagation, 573-574
 - strain-controlled test, 561
 - surface cracking progression, 564-565
- Oxide cracking, 184, 1199-1200
- Oxide structure
 - failure, crack initiation acceleration, 197
 - isothermal constant amplitude loading, 193, 198
 - morphology, 1199
 - 1070 steel, 193-194
 - temperature and strain history, 203
 - thermo-mechanical constant amplitude loading, 193-194, 199-200
 - zero applied load tests, 194, 201
- Oxygen
 - critical value, 1209
 - oxidation-fatigue interaction role, 569
 - penetration along grain boundaries, 303
- Oxygen-enriched environment, 560, 566-567

P

- Palmgren-Miner cumulative damage law. *See* Miner's rule
- Parameter C^* , 291-292, 1164
 - static load test, 288
- Paris expression, 299
- Paris law, 281
- Partitioned strain life relations, 508
- Pearlite
 - cracked ratio, 757, 760-761
 - cracking, 751
 - fracture under high deformation fatigue, 77-92
 - material and experimental procedures, 78-80
 - shear cracking, 758
 - strain-hardening, 78, 88
 - see also* SAE 1038 steel

Plastic compliance, 228
 Plastic deformation, 1096
 singularity variation, 1056-1057, 1059-1060
 strain field near crack tip, 1053-1057
 Plasticity, 329
 Plastic properties, 399, 408
 Plastic energy, total, versus fatigue life, 101
 Plastic strain
 amplitude variation with number of cycles, 778-779, 784, 788
 associated with opening/closing, 222
 components, fatigue cycle, 590-591
 crack density as function of, 453
 energy density, 1030, 1035
 equivalent, 1031, 1103
 increment, 701
 linear damage cumulative law, 983
 longitudinal amplitudes, 924
 maximum, 1109
 Plastic strain-life, polycrystalline 316L stainless steel, 441, 444
 Plastic-strain limit test
 copper, 69
 Cu-8Al, 71
 cyclic hardening, 59-60
 Plastic strain range, 209
 versus critical number of cycles, 321
 elastic strain range and number of cycles to failure, 528
 versus life data, 262-263
 Plastic work
 versus cycle number to crack initiation relationship, 1004
 multiaxial fatigue, 865-866
 total per cycle, 1101, 1110
 Plastic zone correction factor, 1026, 1037
 Plastic zone depth, 209
 Plastic strain rates, 1098
 Polycrystals, 438
 Porosity, 824
 Portevin-Le Chatelier effect, 809
 Power-hardening equation, 318
 Power law, 935
 equation, 318, 333
 flow data correlation, 334
 hardening material, 1029-1030
 hardening stress-strain curves, 1025
 Precipitation hardening, 61, 765
 Precrack
 size, 1215
 stage, load sequence effects, 989
 Pre-oxidation, fatigue life, 1213-1215
 Pressure vessel steels. *See* 9Cr-1Mo-V-Nb pressure vessel steel, cyclic stress-strain time response
 Prestrain, 160

Primary cracks, Waspaloy, 743
 Principal plane cracking, Waspaloy, 745-747
 Push-down list counting, 1223-1227, 1234
 PWA 1480. *See* Ni-Co-Cr-Al-Y coated PWA 1480 superalloy

Q

QT35, secondary crack, 901
 Quantitative metallography, 414

R

Radiant heating, 670-671
 Rain flow analysis, 923-924, 929, 1041, 1181, 1219
 interpretation, 1192-1195
 Ramberg-Osgood elastic-plastic solid, small crack, 1213
 Ramberg-Osgood law, 1027, 1040, 1049
 Random fatigue, 1192-1195
 Ratchetting, 209, 229-230
 linear elastic fracture mechanics, 232
 load control test, 230
 two-bar creep, 9Cr-1Mo-V-Nb steel, 118-120
 Ratio Q , 966-967, 969
 Relative Miner rule, 993
 Relative notch opening displacement, 236, 241
 definition, 240
 with respect to time, 243
 Relaxation, 107
 curve, 410
 during hold time, 545, 549
 isochronous curves, 113
 overstress dependence, 515-516
 rate, 437
 René 80
 Besseling's model, 700-701
 composition, 693
 constitutive theory, 700-701
 cycles to initiation, 699
 cyclic life, 468-469
 cyclic stress-strain response, 463, 695
 data analysis, 694
 failure criterion, 462
 finite element equations, 701-702
 Hollomon equation, 464
 isothermal cyclic stress-strain properties, 697-698
 load-displacement, hysteresis loops, 694
 Ludwik equation, 464
 Manson-Coffin plot, 695-696
 mechanical testing, 693-694

René 80 (*cont.*)

- modeling
 - procedure, 699-700
 - results, 702-706
- Ostergren approach, 696-697
- peak tensile and compressive stresses versus cycle number, 458
- predicted versus observed life, 697-698
- thermal mechanical cycles, 694

René 95

- composition, 294
- creep crack growth rate, 298-300
- environmental and creep effects on crack growth, 307
- fatigue crack growth rate, 298-299
- fracture modes, 302
- predicted and observed crack growth rates, 301
- tensile properties, 294
- see also* Nickel-base superalloys

René N4, 559, 672

- crack growth, 566
- crack initiation from oxide pits, 568, 570-571
- influence of frequency and coating on life, 562
- material properties, 681-683
- oxidation depths versus time, 572
- oxygen pressure effect on fatigue life, 567
- stiffness constants, 681, 693
- uncoated
 - crack depth versus cycles, 563
 - surface cracking progression, 564-565

Renucleation mechanism, 838

Residual ductility, 751-752

- change during fatigue, 753-756
 - with strain cycling, 754
- cracked pearlite ratio, 763
- mean strain effect, 756-763
- variation with strain cycling, 762

Residual static fracture ductility, 160

- versus prestrain, 164
- very low cycle fatigue tensile or compressive prestrain, 163-166

Reuchet-Rémy model, 468

Reversing d-c electrical potential method, 7

Rheological spring-slider model, cyclic deformation, 1218-1219

Room-temperature low cycle fatigue, 316L stainless steel, 800-802

Round cavities, 315

- austenitic stainless steels, 422, 424

RQC-100

- crack initiation life, 1020
- strain fatigue properties, 1019

R ratio, 209

- variation crack depth, 224

crack opening ratio, 225

Rupture life

- dependence on maximum stress, 535
- versus predicted life, 541

S

SAE 1038 steel

- chemical composition, 79
- cyclic stress-strain curve, 79-80, 82-84
- fatigue hardening/softening, 83-84, 88
- fatigue-life curve, 85
- ferritic pearlitic microstructure, 79
- heat treatment, 78
- hysteresis loop, 80
- incremental step test, 81-82
- Kettunen and Kocks relationship, 89-90
- mechanical properties, 82
- monotonic stress-strain curve, 83-84
- multiple step test, 80
- prediction of monotonic properties, 85
- tensile test, 82
- work-hardening, 88
- see also* Pearlite

SAE 1045 steel, 175, 899

- chemical composition, 174
- compressive overload effects, 180
- compressive stress effects, 178
- cracking behavior, 907, 909-911
- equivalent lives of fully reversed cycles, 182
- mechanical properties, 902
- region II behavior, 907-911
- static tensile properties, 877
- tension and torsion behavior, 913, 915
- type S crack system, 910
- see also* Fatigue, compression and compressive overload effects

Saturation

- definition, 642
- effect, 415
- plastic strain range, 89
- stress

Cu-8Al, 74

polycrystalline 316L stainless steel, 441-442

S10C steel

- cyclic stress-strain response, 274
- fatigue life, 276

S35C steel

- chemical composition, 258
- crack growth rate versus strain intensity factor range, 269
- cyclic stress-strain response, 274
- fatigue life, 277
- heat treatment, 258
- mechanical properties, 258
- plastic strain range, 262-263

- surface crack growth, 262
 - versus cyclic J -integral, 264
- Secondary crack
 - conservation equation, 433
 - density, 432-434
 - continuous fatigue, 434
 - creep-fatigue, 434-435
 - distributions, 425-426
 - nucleation rate, 433
 - QT35, 901
 - 304 stainless steel, 901
 - TC6 titanium alloy, 850
 - Waspaloy, 742
- Service failure, 160
- Service loadings, 972
- Sessler-Weiss's law, 755
- Shape function, 125
- Shear cracking, 913
- Shear modulus, 577
 - versus tensile plastic work, 586
- Shear planes, crack initiation, 900
- Shear strain, change in fatigue loading, 617-618
 - critical, 617
- Shear-type fracture, 60Sn-40Pb solder, 348
- Ship, service failure, 161
- Short-crack, 972
- Signum function, 135
- Similitude, 145
 - inelastic volume fraction, 146-147
- Sine's equivalent strain, 1154
- Single crystals, 371, 438
- Singularity
 - values and hardening exponent, 1061
 - variation with plastic deformation, 1056-1057, 1059-1060
- Slip band, 735-737, 741, 749, 838, 899-900
 - carbide formation, 746-747
 - duplex microstructure, 846
 - equiaxed microstructure, 846
 - persistent, 900
 - spacing
 - alternating plastic strain, 68, 73
 - incremental-step test, 74
 - multiple incremental test, 73
 - strain aging ferrous alloys, 784, 786-787
 - unaged N-alloy, 782
 - Widmannstätten microstructure, 844-845
- Slip lines
 - quantification, 853-858
 - curves of progressive change, 854
 - increase during fatigue tests, 855, 857
 - increase during tensile test, 856
 - method, 854
 - stereographic quantity, 854
 - quenched C-alloy, 789-790, 792-793
- Slip-plane sliding, 29
- Slope parameter, 1208
- Slow load cycling, 285
- Small crack, 1048
 - growth law, 1184
 - load sequence effects, 990
 - low oxygen environment specimen, 568
 - propagation process, 1050-1054
 - Ramberg-Osgood elastic-plastic solid, 1213
- Small crack growth, 257-279, 1182
 - cyclic J -integral, 260-261, 264
 - derivation of fatigue life curves, 267-278
 - initiation and growth behavior, 261-263
 - materials and experimental procedure, 258-260
 - plastic strain range versus life data, 262-263
 - rate versus strain intensity factor range, 265-266, 269-273
 - specimen schema, 259
 - strain intensity factor range, 260-261
 - surface crack growth curves, 262
- Small specimen crack growth data, 209-233
 - across whole section, 219-224
 - crack closure, 220, 223-224
 - hysteresis loop shape, 220
 - method, 219
 - stress-depth variation, 219
 - aging effect, 215-216
 - assessment procedure, 232
 - assessment route, 232-233
 - conversion to stress-intensity based relations, 224-229
 - crack growth law, 211-212
 - notch effect, 215
 - relation to load control tests, 229-231
 - remaining life path, 232
 - strain rate effect, 213-214
 - test choice, 231
 - tolerable defect path, 232-233
 - weld metal, 214-216
 - see also* Crack growth law
- SNCM 439 alloy steel
 - chemical composition, 258
 - crack growth rate versus strain intensity factor range, 270-271
 - cyclic stress-strain response, 274
 - fatigue life, 277-278
 - fatigue microcrack, 261
 - heat treatment, 258
 - mechanical properties, 258
 - plastic strain range, 262-263
 - surface crack growth, 262, 265-266
- 60Sn-40Pb solder, 342-368
 - ductile-type fracture, 349
 - environmental influences, 368
 - experimental procedure, 343-344
 - granulated-type fracture, 350

60Sn-40Pb solder (*cont.*)

- intergranular fracture, 352-353
- intermetallic, 351, 360-362
- low-cycle fatigue, 344-363
- microstructure, 351, 354-360
- oxygen effect, 368
- percent creep, 363-364
- shear-type fracture, 348
- strain life, 345
- strainrange partitioning, 363-364

Solder, 342

Solder joint

- fatigue, 588-609
 - chip carrier array, 591, 594-595
 - creep, 589-590, 598-599
 - holding torque, creep strain, versus time, 596
 - isothermal mechanical fatigue, torsional apparatus, 592-593
 - square wave, 597
 - strain life behavior, 597, 607
 - strainrange partitioning. *See* Strainrange partitioning
 - structural studies, 593-594
 - triangular wave, 597
- fatigue life
 - frequency/strain range, 597, 606
 - matrix creep, 598, 600, 604, 608
 - total grain boundary creep, 598, 607
- see also* 60Sn-40Pb solder

Solubility limit, 579-581

Solution hardening, 61

Specimen size, 209

Spectrum loading, 1144

Spera's accumulated creep damage method, 1121-1122, 1124

Stainless steel, 123, 236, 711, 899

- cyclic hardening, 58
- see also* Austenitic stainless steel; specific stainless steels

253MA stainless steel

- brittle fracture behavior, 551
- chemical composition, 544
- dislocation tangles, 549-550
- fracture surface, 554
- grain boundary cavitation, 555
- grain size and hardness, 545
- wedge-cracks, 552-553

304 stainless steel

- chemical composition, 237, 320, 520
- crack branching, 916
- cracking behavior, 903-905
- crack propagation rate, 1164, 1169
- creep-fatigue interaction test, 237, 239
- creep test, 237, 239
- cycles-to-failure versus time-to-failure, 136, 138

cyclic hardening, 133

fatigue test, 237, 239

identification of material functions, 126-127

life prediction, 496, 1082

maximum principal stress parameter correlation, 917, 919

mechanical properties, 237, 902

number of cycles to failure, 1083, 1086-1087

plate specimens, 1083-1084

region II behavior, 904-905

region III behavior, 904, 906

relative notch opening displacement, 241

round bar specimens, 1083, 1085

secondary crack, 901

shear strain parameter correlation, 917-918

stage I life as function of shear strain amplitude, 904, 907

stress ranges, 132

surface at failure, 904

tension and torsion behavior, 913-914

see also Creep-fatigue, overstress concept application

316 stainless steel, 543

comparison of bithermal and thermomechanical fatigue behavior, 629-630

cracking behavior, 902-905

chemical composition, 415, 544

cyclic stress-strain responses, 713, 715

dislocation cells, 549-550

fibrous precipitation, 549-551

grain size and hardness, 545

main crack path, 553

Manson-Coffin plot, 713-714, 716-717

stress-strain curve, 65

stringer, 905

tensile hold period effect on fatigue life, 722-723

tensile properties, 415

void formation, 552

see also Austenitic stainless steels

316L stainless steel, 438-453, 798-811

aging, 802, 804-805

chemical composition, 439, 799

crystal growth, 439

cyclic deformation, 817

cyclic hardening, 800

cyclic stress-strain response, 800, 803

effect of aging treatment on cyclic hardening-softening curves, 802, 805

experimental procedure, 439-440, 799-800

fatigue life, 801, 804

fatigue resistance, 807-808

fractographic analysis, 805, 809

fracture surfaces, 806-808

- high-temperature low cycle fatigue, 802-803, 805
- intergranular fracture, 809
- intergranular precipitation, 809-810
- interstitial nitrogen, 801, 805-807
- loss of ductility, 806
- mechanical behavior, 800-805
- mechanical properties, 439
- monotonic stress-strain response, 800, 803
- polycrystalline
 - crack initiation, 442-443, 446-448
 - cyclic stress-strain response, 440-441
 - fatigue lifetime, 441, 444-445
 - intergranular cracks, 449
- room-temperature low cycle fatigue, 800-802
- single-crystal
 - crack initiation, 448-449, 452-453
 - cyclic hardening, 443-445, 450
 - fatigue life, 445, 448, 451
 - microcrack propagation, 449, 453
 - specimen dimensions, 440
- specimen configuration, 799
- tensile properties, 800-802
- 316LN stainless steel
 - brittle fracture behavior, 551
 - chemical composition, 544
 - grain size and hardness, 545
- 321 stainless steel, strain energy parameters, 1176
- Standard deviation, definition, 392
- Standards, need for new, 19-20
- Static load test, 285
 - parameter C^* , 288
- Static tension tests, 162
- Statistical work-hardening theory, 86
- Steel
 - low alloy, 399
 - material properties, 1000
 - mechanical properties, 162
 - prestrain effects, 160
 - transmission loading history geometry, 1041, 1043
- 1070 steel
 - chemical composition, 186
 - microstructure, 187
 - under thermal loading, 184-205
 - axial strains, 197, 202
 - equipment, 186
 - fatigue test results and predictions, 188, 190-191
 - material, 185-187, 191-192
 - mismatch hoop strains, 200, 202
 - oxide structure, 193-194
 - test conditions, 186, 188-189
- Steel alloy, notch tip strains, 1041-1042
- Step function, 135
- Stepped-disk specimen, 672-674, 690
 - temperature history, 678-679
- Stowell-Hardrath-Ohman's equation, 1086
 - predicted and experimental fatigue, 1090-1091
- Strain, 1218
 - amplitude
 - correlation between experimental and calculated, 166, 168
 - versus number of cycles, 585
 - versus stress amplitude, 110-111
 - effective, versus life, 864
 - mean, 751
 - fatigue life dependence, 752-753
 - fracture mode variation, 760
 - residual ductility effect, 756-763
 - Mohr's circles, 868
 - plastic zone ahead of crack tip, 1035
- Strain aging ferrous alloys, 776-796
 - composition, 777
 - ductility, 779-780
 - experimental procedure, 777-778
 - fatigue aged C-alloy, 789-791
 - grain boundary deformation, 791, 795
 - precipitates formed, 791, 794
 - fatigued and aged N-alloy, 784-787
 - plastic strain amplitude variation with number of cycles, 784, 788
 - precipitates formed, 784-785
 - slip bands and crack nucleation sites, 784, 786-787
- S-N* curves, 787
 - unaged C-alloy, 787-789
 - slip lines, 788-789, 792-793
 - unaged N-alloy, 778-784
 - diffuse slip, 779, 781
 - Manson-Coffin relationship, 778-780
 - plastic strain amplitude variation with number of cycles, 778-779
 - precipitates formed during aging, 780, 783
 - slip bands, 782
 - S-N* curves, 778
- Strain concentration factors, inelastic stress, 1078
- Strain-controlled test, 209
 - compared with load control data, 231
 - fully reversed, 1242
 - oxidation-fatigue interactions, 561
- Strain cycling, 163, 165
 - change of residual ductility, 754
 - residual ductility variation, 762
- Strain distribution, 1154
 - near crack tip under plastic deformation, 1062
 - variation near crack tip, 1054, 1056, 1058-1059

- Strain energy density, 1022
 - concentration factor, 1044
 - distribution
 - ahead of crack tip, 1024-1036
 - near blunt notches in plane stress, 1036-1045
 - total, failure in pure creep, 1258
- Strain energy parameter, 1163
 - versus number of cycles to failure, 1173-1178
- Strain energy partitioning, 1133-1142
 - life predictabilities, 1142
 - life prediction equations, 1137
 - life relationships, 1138-1139
 - materials and experimental procedure, 1134-1135
 - observed versus predicted lives, 1140
 - waveforms of verification test, 1135
- Strain fatigue, 329, 1019
- Strain hold test, numerical simulation, 508, 510
- Strain hysteresis loops, versus stress, 110
- Strain intensity factor, 257
- Strain intensity factor range, 269-271, 279
 - cyclic J -integral range, 260-261
- Strain life, 154, 597, 607
 - equation constants, 190
 - fatigue law, 975, 979, 983
 - 60Sn-40Pb solder, 345
- Strain parameters, 477
- Strain range, 160, 1061
 - correlation between experimental and calculated, 167
- Strain range
 - criterion, 204
 - inelastic, versus number of cycles to failure, 388
 - modified for crack increment, 1230
- Strainrange partitioning, 15, 29, 53-56, 363, 395-396, 399, 412, 625, 1133
 - application, 1257
 - calculated and experimental life, 1121-1122
 - creep-fatigue life prediction, 402
 - equations, 395
 - HP-IP steam turbine rotor, 1252-1253, 1256-1257
 - isothermal, B-1900 + Hf, 632-635
 - life predictabilities, 1142
 - life prediction, 1120-1121
 - equations, 1136-1137
 - number of cycles to initiation, 1120-1121
 - observed versus predicted lives, 1141
 - solder fatigue, 589
 - experimental procedure, 591-593
 - plastic strain components, 590-591
 - structural studies, 593-594
 - total-strain version, 329-341
 - AF2-1DA, 335-337
 - analysis, 331-333
 - evaluation of method, 335-338
 - Inconel 718, 337-338
 - Walker constitutive model, 333-335
 - time-modified, 38-39, 342, 365-366, 365-367
 - viscoplasticity based on overstress, 134
- Strain rate, 209, 399, 519
 - crack growth effect, 213-214
 - life prediction, 403-404, 410-411
 - viscous, 437
- Strain ratio, 259
- Strain resistance prediction criterion, 85
- Strain singularity
 - Manson-Coffin law. *See* Manson-Coffin law, strain singularity
 - near crack tip, 1053, 1055
- Strain tensile, versus stress, 109
- Strain-time waveforms, 315
- Strength coefficient, 406-407
- Stress, 1218
 - concentrator, 215
 - effective range, 1013
 - equivalent
 - plastic zone ahead of rack tip, 1034
 - and stress intensity factor, 1031
 - as function of time, 641, 643
 - isothermal fatigue, 191, 193-196
 - mean, 15, 30, 185, 937, 1017
 - correction, 1154, 1229-1230
 - improved formulation, 34, 36-37
 - versus strain hysteresis loops, 110
 - versus strain tensile curves, 109
 - thermo-mechanical fatigue, 191, 193-196
 - total, versus number of cycles, 50-51
 - variation with crack depth, 219, 221
- Stress amplitude
 - versus cumulative diametral plastic strain, 48
 - versus fatigue life, 101
 - isothermal cycling, 118
 - versus strain amplitude, 110-111
 - versus temperature, 50
- Stress concentration, 611, 1007
- Stress concentration factor, 1009, 1043
 - equivalent, 1044
- Stress controlled tests, 1083
- Stress-dip procedure, 44
- Stress drop, 209
 - with crack penetration, 209
- Stress gradients, 874
- Stress-intensity, 224-229
 - deep cracks, 226-229
 - equivalent, 209
 - short cracks, 225-226
- Stress intensity factor, 951, 995, 1027-1028, 1145, 1227

equivalent stress, 1031
 Paris law, 281
 Stress intensity parameter, 466
 Stress range, 527
 peak, number of cycles to initiation, 1118-1119
 strain rate dependence, 520-522
 temperature dependence, 520-522
 Stress relaxation, 430, 576
 as creep-fatigue life correlating parameter, 427-428
 intergranular damage, 428-429
 rate, Inconel 625, 472-473, 425
 Stress-strain, 77
 copper, 66
 Cu-2Al, 67
 Cu-4Al, 68
 Cu-8Al, 69
 FEMFAT, 995-996
 hysteresis loop, 59
 notch principal, 1011, 1013
 over-aged Al-4.5Zn-2.5Mg, 64
 peak-aged Al-4.5Zn-2.5Mg, 63, 74
 response, 184
 316 stainless steel, 65
 under-aged Al-4.5Zn-2.5Mg, 62, 74
 Stress/strain concentration factors, nominal stress, 1080-1081
 Stress-time waveforms, 315
 Striations spacings measurements, 419-421
 Stringer, 316 stainless steel, 905
 Stroh's equation, 616
 Superalloy, 371, 531, 638, 961, 728
 chemical composition, 534
 mechanical properties, 824
 single-crystal. *See* Oxidation-fatigue interactions
 see also specific superalloys
 Superimposed stresses, 938-960
 crack initiation on notched specimens, 947, 951
 crack propagation, 951, 955-958
 material and specimens, 939
 maximum stress criterion, 947
 number of cycles to failure, smooth specimen, 942-947
 prediction models for mixed fatigue conditions, 958-959
 test analysis, 939, 942
 test program and notations, 939-941
 Surface
 crack, 751
 20Cr-25Ni-Nb stainless steel, 724
 microfracture, 755-756
 damage, development and inelastic volume fraction, 147
 at failure, 304 stainless steel, 904

Surface-mounted solder joint array, 588
 SUS304 steel, wedge-type crack, 618

T

T91
 creep, 111
 stress versus strain tensile curves, 109
 2024-T351 aluminum alloy
 chemical composition, 174
 compressive overload effects, 179
 compressive stress effects, 177
 equivalent lives of fully reversed cycles, 181
 mechanical properties, 175
 see also Fatigue, compression and compressive overload effects, 173-182
 TAZ-8A, 1199-1200
 chemical composition, 1200
 TC6 titanium alloy, 838-851
 basket-weave microstructure, 845-846
 chemical composition, 839
 crack initiation, 848-850
 crack propagation, 850-851
 cyclic softening, 843
 experimental methods, 838-839
 fatigue crack tip, 848-849
 fatigue life, 851
 fatigue propagation life, 844
 low cycle fatigue properties, 841-844
 metallography, 839-840
 microstructure, 840
 regimes of rolling and heat treatment, 839
 specimen geometry, 839
 tensile properties, 840-841
 total strain and fatigue life, 841-842
 voids, 849-850
 formation, 850
 Widmannstätten microstructure, 844-845
 Tensile cracking, 913
 Tensile limits, 1223
 Tensile plastic work, versus shear modulus, 586
 Tensile prestrain
 schematic diagram, 165
 see also Very low cycle fatigue tensile or compressive prestrain
 Tensile strength, pearlite, 78
 Tensile test, SAE 1038 steel, 82
 Tension/compression hold time, 470
 Tension dwell, 209
 Texture, 385
 Thermal cycling, 107, 209
 one-bar restrained, 117-118
 Thermal fatigue, 15, 576, 672, 1096, 1115, 1163

- life prediction, 1126-1129
- monocrystalline superalloys, 680-681
- variation of number of cycles to various crack depth, 1126-1127, 1129
- Thermal loading
 - railroad wheels, 185
 - see also* 1070 Steel, under thermal loading
- Thermally activated process, 236
- Thermal strain, as function of time, 641, 643
- Thermal stress, 29
- Thermoelastic finite-element analysis, monocrystalline superalloys, 682-690
- Thermo-mechanical block loading
 - experimental lives and isothermal predictions, 191-192
 - maximum stress, 197
 - predicted blocks-to-failure, 190
 - stress-mechanical-strain-behavior, 192, 197
 - temperature-time histories, 189
- Thermo-mechanical constant amplitude fatigue test results, 205
- life predictions, 190
- loading
 - maximum stress, 197
 - oxide layers, 193-194, 199-200
 - stress mechanical-strain behavior, 192, 197
 - temperature-time histories, 189
- Thermomechanical fatigue, 184, 577, 625, 638, 657-669, 692
 - comparison of isothermal low-cycle fatigue, 665-666, 668
 - crack development, 662-664
 - cyclic stress-strain response, 661-662
 - cycling, 627-629
 - disadvantages, 628
 - damage, 204
 - definition of life to crack initiation, 664-665
 - experimental procedure facilities, 660-661
 - material and specimens, 658
 - non-isothermal, 581, 583-584
 - Ostergren approach, 696-697
 - simplified formulation, 37
 - stresses, 191, 193-196
 - testing procedure, 661
 - test principle, 658-659
 - thermal mechanical strain cycle, 659-660
- Thermo-mechanical strain cycle, 659-660
- Thermo-mechanical testing, B-1900 + Hf, 641-642
- Thin-wall tube, damage development, 877-885, 892, 894-895
 - crack length versus strain state, 894-895
 - damage nucleus, 892
 - as function of strain state and amplitude, 879-881
- high-cycle fatigue, 879-881
- low cycle fatigue, 882, 884
- in torsion, 882, 883
- Through-thickness crack specimen, 259-260
- Ti 6-4 alloy, 939
 - crack initiation, notched specimen, 951-952
 - crack propagation, 951, 955-956
 - fatigue striations, 946
 - Haig diagram, 942, 945
 - number of cycles to failure, 942-947
- Titanium alloy, 838, 938
- Tomkin's model, 1125
- Tool steel, 576
- Torsion, 728, 899
 - shear, 588
- Torsional cracking, notched shaft, 886, 889
- Torsional fatigue
 - cracking behavior, 901
 - temperature effect on fatigue life, 747-749
 - Waspaloy, 736, 738-744
- Total life, versus hold time, 248, 250
- Transgranular crack, 711, 749
 - growth, 184
- Transgranular fracture, 519, 528
- Tresca criterion, 863-864
- Turbine components, stress-strain temperature cycle, 638-639
- Turbine rotor steels, 972-983
 - chemical composition and heat treatment of test materials, 973
 - experimental procedure, 973-974
 - life reduction under variable strains
 - defect-free material, 976, 978
 - material with defects, 978-980
 - multiple two-step strain, 973, 975
 - number of cycles to failure, 974, 977-979
 - total strains at start-up, 973
 - variable strain ranges
 - defect-free material, 974-975
 - materials with defects, 975-976
- Twinning, duplex stainless steel, 815, 819
- Two-bar creep ratchetting test, 9Cr-1Mo-V-Nb steel, 118-120
- Two-step loading, 1181, 1189-1190

Uniaxial low cycle fatigue parameters, 1097-1099

temperature effect on fatigue life, 747-749

Waspaloy, 729-736

V

- Variable amplitude, 1218
- Variable amplitude loading
 - notched components, 987-1005
 - precrack load sequence effect, 989
 - small crack load sequence effects, 990
- Variable amplitude straining, 922-937
 - cyclic stress-strain response, 929-932, 924, 927-928
 - dependence of number of peaks on maximum diametral strain amplitude, 924
 - experimental procedure, 923-924
 - fatigue life, 929, 932-934
 - hardening/softening curves, 924-926
 - rain flow analysis, 923-924
- Variable strain
 - life prediction, 981-982
 - loading, turbine rotor steels, 972-983
- Very low cycle fatigue tensile or compressive prestrain, 160-171
 - correlations between experimental results and estimated values, 166-169
 - experimental procedure, 162-163
 - loss of ductility effects, 168-170
 - reduction of fatigue life, 168-171
 - residual static fracture ductility, 163-166
 - superposed effects of ductility loss and microcracks, 170-171
- Viscoplasticity, 500
 - based on overstress, 123-138
 - application to life prediction, 133-136
 - formulation, 154-156
 - incremental damage accumulation law, 135-136
 - inelastic strain rate, 124
 - model outline, 124-126
 - numerical integration of system of differential equations, 127-133
 - predictions for strain-controlled loading, 132-133
 - signum function, 135
 - step function, 135
 - strainrange partitioning, 134
 - see also* Differential equations
- Viscosity function, 125
- Visible crack initiation life, 160
- ν - K , equation, 1083
 - predicted and experimental fatigue lives, 1089, 1094
- Void, 838, 1199
 - formation, 552, 758
 - intercrystalline, 601-602, 609
 - TC6 titanium alloy, 849-850
- von Mises criterion, 863-864
- von Mises equivalent stress, 1147

W

- Walker's functional theory, 331
- Waspaloy, 295, 728-749
 - composition, 296
 - crack formation, 730-731, 735-736, 741-742, 744-745
 - damage mechanisms, 745
 - dislocation structure, 730, 734, 736-737, 741, 744-745
 - effect of temperature on uniaxial and torsional fatigue lives, 747-479
 - environmental and creep effects on crack growth, 307
 - failure mode, 745
 - fatigue crack growth rate, 304, 306
 - fracture modes, 305
 - gage surfaces, 735, 739
 - γ morphology, 730
 - grain boundary, 731
 - heat treatments, 730
 - initial microstructures, 729-731
 - life comparisons, 736, 740-741
 - macrophotos, 740
 - materials, specimen fabrication, 729
 - metallurgical evaluation techniques, 729
 - normalized lives for each microstructure and stress state, 747-748
 - primary cracks, 743
 - principal plane cracking, 745-747
 - secondary crack, 742
 - tensile properties, 296
 - test matrix and procedures, 729
 - torsional low cycle fatigue tests, 736, 738-744
 - uniaxial low cycle fatigue test, 729-736
 - coarse-grain/small precipitate, 729-730
 - fine-grain/large-precipitate, 731, 733, 735-736
- Wedge-type crack, 611, 616, 618
- Wedge-type specimen, 1117
- Weibull distribution function, 1199, 1212
- Weibull modulus, 1208
- Weibull plot, 1208
- Weld metal
 - austenitic, 209
 - crack growth, 214-216
 - notch effect, 992
- Widmannstätten microstructure, 839-840
 - TC6 titanium alloy, 844-845

Y

- Yao-Munse's hypothesis, 754

Z

Zero applied load tests, non-stratified oxide
layers, 201

Zircaloy-4, stress-strain relation, 1032