Subject Index

New Zealand, 203

A

| - | performance-based, 203 |
|---|---|
| Acrylic polymer-based coating, 268 | Coefficient of Variance, 160 |
| | Communication, process of, 3 |
| Adhesion, 261 | Compressive stresses, 115 |
| Air Darrier, 101, 175 | Condensation, 101, 189 |
| Air Barrier Association of America, 175 | index, 160 |
| Air leakage, 101, 175 | Connectivity, 101 |
| Air permeance, 175 | Construction details, 84 |
| Air properties, 189 | Construction, laboratory mockups, 69 |
| American Architectural Manufacturers | |
| Association, 10 | Construction sequence, 101 |
| American Society of Civil Engineers | Control joint 214 |
| (ASCE), 10, 17, 42 | Control joint, 214 |
| Standard 7, 17, 42 | Cracking, 115, 214 |
| Anchored brick veneer walls, 115 | Curing, 214 |
| Architect, project role, 3 | Curtain wall, 17, 69, 231, 242 |
| Architectural glass, seismic design | |
| provisions, 242 | _ |
| Asphalt-saturated felt, 214 | D |
| ASTM Committee C16 on Thermal | |
| Insulation, 189 | Diamond mesh, 214 |
| ASTM Committee E06 on Performance of | Design |
| Buildings, 189 | architectural glass, 242 |
| ASTM MNL 18, 189 | building, 84 |
| ASTM MNL 40, 189 | codes, 10, 17 |
| ASTM standards (See also Standards), 175 | joint, 261 |
| E 283: 69 | panelized curtain wall system, 231 |
| E 330: 69 | panelized wall construction, 231 |
| E 331: 69 | pre-construction mockups, 69 |
| E 547: 69 | process for cladding materials, 17 |
| E 1233: 69 | sealant joint, 261 |
| E 2099: 69 | stucco, 214 |
| | tools, 189 |
| В | two-dimensional graphics, 84 |
| | Dew point temperature, 160 |
| Brick Industry Association, 10 | Dimension stone, 54 |
| Brick veneer, 115, 231 | Drainage plane, 268 |
| Brown coat, 214 | Drift, interstory, 242 |
| Building Envelope Research Laboratory, | |
| 242 | E |
| Building Industry Authority, New Zealand, | |
| 203 | Earthquake, 115, 242 |
| | Earthquake-Isolated Curtain Wall System |
| C | (EICWS), 242 |
| | Elastomeric sealants, 261 |
| Cladding, 17, 54, 203, 214, 261 | Elastomers, 132 |
| Cladding design, 42 | Emissions, 175 |
| Cladding Systems, 17 | Energy codes, 175 |
| Cladding wind load, | Evaluating a leak condition, 145 |
| determining, 42 | Expanded metal lath, 214 |
| Codes, building, 10, 214 | Expansion joint, 214 |
| | |

Exposure category, 42

International Building Code, 17

| Exterior insulation finish system (EIFS), | K |
|--|--|
| 231, 268 basic barrier, 268 | Vroft noner 214 |
| with drainage, 268 | Kraft paper, 214 |
| with trainage, 200 | L |
| F | Laboratory mockups, exterior wall systems. |
| Façade, 3, 54 | Lath, 214 |
| Failure envelope, 261 | Leakage, air, 101, 175 |
| Federal Emergency Management Agency | Leakage prevention, 84 |
| (FEMA) | Leakage, water, 10, 101, 145, 203, 214, |
| FEMA 302: 242 | 261 |
| FEMA 368: 242 | Legal proceedings, leak condition, 145 |
| Fenestration thermal performance rating (U- | Legal theories (of leakage), 145 |
| factor), 160 | Linear elasticity, 132 |
| Finish coat, 214 | Load, wind, 17 |
| Finite-element analysis, 132 | Longitudinal ultrasound velocities, 132 |
| Flashing, 84, 214 | |
| Flexible weather resistive barrier, 268 | M |
| Forensic evaluation, 145 | |
| Friction forces, 115 | Measurements |
| Fully engineered buildings, 17 | tensile, 132 |
| , | ultrasonic, 132 |
| G | Metal diverter, 214 |
| • | Metal edge fastening, 17 |
| Greenhouse gas, 175 | Mildew, 189 |
| Green strength, 268 | Missile impact, 17 |
| Green strength, 200 | Model building codes, 17 |
| н | Modeling, 189 |
| 11 | MOIST, 189 |
| Heat loss, 101 | Moisture |
| Tieat 1055, TOT | analysis, 189 |
| I | control, 189 |
| 1 | management, 101 |
| I | penetration, 10, 101, 203 |
| Impact resistance, 17 | Mold, 189, 214 |
| Infiltration resistance, 10 | Movement joints, 115 |
| Information exchange | |
| recommendations for, 69 | N |
| In-plane lateral load resistance, 115 | |
| Inspection, air barrier system, 175 | National Air Barrier Association, 175 |
| Insulation board, 268 | National Earthquake Hazards Reduction |
| Interface, 261 | Program (NEHRP), 242 |
| International Building Code, 17 Interstory displacement, 242 | National Fenestration Rating Council |
| | (NFRC) |
| Interstory drift, 242 | NFRC 100: 160 NFRC 500: 160 |
| J | National Roofing Contractors Association, |
| Joints | New Zealand Building Code, 203 |
| control, 214 | _ |
| design, 261 | 0 |
| failure, 261 | |
| movement, 115 | Owner, project role, 3 |

| P | Shelf angles, 115 Shielding, 42 |
|---|---|
| Panelized curtain wall system, 231 Paper-backed lath, 214 | Shutters, 17 Silicone sealant, 132 |
| Particulate fillers, 132 Partnership, owner, architect, and | Standards (See also ASTM Standards), 42, 214 |
| contractor, 3 Peel-and-stick membrane, 214 Plaster, 214 | standard practice for pre-construction mockups of exterior wall systems, 69 |
| Poisson's ratio, 132 | wall performance criteria, 10 |
| Portland cement, 214 | Steel studs, 231 |
| Precipitation control, 101 | Stone, façades, 54 |
| Pre-construction evaluation, 69 | Structural capacity, 17 |
| Prefabricated wall panels, 231 | Stucco, 214 |
| Premature building failure, 175 | |
| Pressure measurements, 42 Project | Т |
| definition, 3 | Thermal transmittance, 160 |
| scope, 3 | Topographic effects, 17 |
| specification and selection process, 3 Proving a leak condition, 145 | Two-dimensional (2-D) graphic representations of components, 84 |
| Q | U |
| | U-factor, 160 |
| Quality assurance, 101 air barrier system testing, 175 | Ultrasound velocity, 132 |
| R | V |
| Rain penetration, 101 | Veneer, 115, 214, 231 Vertical differential movement, 115 |
| Rake flashing, 214 | vertical differential movement, 113 |
| Relationship between owner, architect and contractor, 3 | W |
| Rigid board sheathing, 231 | Water infiltration resistance, 10 |
| RTV silicone sealants, 132 | Water management, 231 |
| Rubberized asphalt, 214 | Waterproofing membrane, 214 |
| \mathbf{S} | Weather barrier, 84, 268 |
| 3 | Weatherproofing, 84 |
| Scratch coat, 214 | Weather resistive coating, 268 |
| Sealant joint design, 261 | Weep screed, 214 |
| Sealant joint design, 201 Sealant joint failure, 261 | Wind-borne debris, 17 |
| Sealants, 261 | Wind climate, 42 |
| silicone, 132 | Wind load, 17, 42 |
| Secondary defense method, 203 | factors, 42 |
| Seismic | Window, 214 |
| decoupling, 242 | Windows and doors, 17 |
| design, 242 | Wind performance of exterior walls, 17 |
| life safety issues, 115, 242 | Wind tunnels, 42 |
| performance, 115 | WUFI ORNL/IBP, 189 |
| Self-furring lath, 214 | |
| Sequence (Step-by-step) views, 84 | Y |
| Shear cracking, 115 | - |
| Sheathing, 214, 231 | Young's modulus, 132 |
| | |