

Index

A

- AAR (alkali-aggregate reaction) (*see* Aggregates)
- Activation energy, 109
- Admixtures
- Mineral, 151
 - Set-retarding, 89-105
 - Water-reducing, 70, 75-85, 118-133
- Aggregates, 118-133
- Alkali-aggregate reaction, 135, 137, 146
 - Coarse, 5, 25
 - Dolostone, 38-67, 119
 - Fine, 5, 25
 - Flint, siliceous, 141
 - Granite, 94
 - Gravel, siliceous, 71
 - Hornblende, 119
 - Hydrothermal reactions of, 130
 - Limestone, 38-67, 94, 141
 - Quartzite, 41
 - Sand, manufactured, 94
 - Sand, natural, 14, 25, 38, 67, 71, 94
 - Shale, expanded, 21
 - Stone, crushed, 14, 16
- Air, ambient, 99
- Air content, 41, 120, 121
- Air drying, 26, 35, 42
- Air-entraining agent, vinsol resin, 119
- Aitcin, P.-C., 3-20
- Alite, 136, 137
- Alkali, 94
- Reaction with aggregate, 135, 137, 146
- Aluminates, 130
- Tricalcium, 70, 94
- Aluminum oxide, 98, 152
- American Concrete Institute (ACI)
- Committee 305, 69
 - Report 305-77, 104
 - Standard 318-77, 13
- American Petroleum Institute, 151
- Antifreeze bath, 121
- Arrhenius maturity function (*see* Maturity functions)
- Artic sea, 3-20
- ASTM specifications
- C 31-83: 99
 - C 150-83a: 94
 - C 192-81: 119
 - C 305-82: 155
 - C 494-82: Type A, 94
 - C 494-82: Type D, 94
 - C 494-82: Type F, 95, 118, 119
- ASTM tests
- C 39-83a: 5, 121
 - C 109-80: 71
 - C 293-79: 5
 - C 469-81: 5, 121
- Axial tension, 23
- B**
- Baffin Island, 13-19
- Basaltic rock, 161
- Bentonites, 161, 162
- Berner, D., 21-37

C

Caissons, 3-20
 Calcium hydroxide, 136-139, 163, 164
 Calcium oxide, 98, 151, 152
 Calcium silicate hydrates (*see* Silicates)
 Calorimeter, 152
 Capillaries (*see* Pore spaces)
 Carbonation, 56, 60, 135, 140
 Carette, G. G., 38-67
 Casualties, 168
 Chakraborty, M., 118-133
 Cheung, M. S., 3-20
 Clinker cooling, 136
 Cold storage, 4, 69
 Compaction, 121
 Compressive strength
 And bulk density, 162-163
 And calcium hydroxide, 137
 And cooling rate, 36
 And elasticity, 128, 129, 130
 And maturity, 111-113
 During average temperature curing, 121, 135
 During high-temperature curing, 25-30, 38, 45, 46, 63-67, 71-81, 88-106, 122-124, 130-131, 133, 150-161, 162-163
 During *in situ* temperature curing, 136, 141-144
 During low-temperature curing, 7-11, 18-19, 23, 25-30, 35, 107-117, 122
 During temperature cycles, 137-139
 Moist, 38-67
 Containers, offshore, 22, 36
 Cooling chamber, 24-25
 Cooling methods, 69, 106
 Cooling rate, 36, 136
 Cooling tower, 168-176
 Crane cathead, 170, 174

Crystalline structure, 103

Curing

Boxes, 99
 Cylinders, 120
 Fog, 26
 High temperature, 25-30, 38-67, 68-86, 88-106, 122-125, 130-131, 150-161, 162-163
 Low temperature, 3-20, 25-30, 35, 107-117, 122
 Molds, 42, 120
 Nonstandard, 99-100
 Standard, 17, 68-87

D**Decomposition**

Dolostone concrete, 63
 Limestone concrete, 63

Delivery time, effect on water requirements, 68-86, 103

Density, 163

Dolostone, 38-67

Drilling, for permeability test, 141

Ductility, 123

Durability, 135, 164, 166

Effect of freeze-thaw cycles, 22

E

Elastic strain, 22, 26, 30-33

Elasticity, 118-133

Electron microscope, 104-105, 159

Epoxy, 155

Exothermic reactions (*see also* Heat generation), 108, 135

Expressway, use of concrete in, 93, 97

F

Failure of concrete structure, 168-176

Farahmandnia, A., 168-176

Fatigue, cyclic, 21-37

Fatigue damage, 36

- Ferric oxide, 151
- Fiber formation, 103
- Fly ash, 25, 39, 71-86, 118-133, 134-149
- Fog (*see also* Curing), 4
- Freeze-thaw cycles, 22, 33-34, 36
- G**
- Gas
- Natural, 21
 - Petroleum, 21
- Gaynor, R. D., 68-87
- Gerwick, B. C., Jr., 21-37
- Glucose polymer, 95
- Granitic rocks, 161
- Gypseal, 151
- Gypsum, 70
- H**
- Halvorsen, G. T., 168-176
- Heat generation, 72, 108, 109, 135, 150-167
- Humidity, 24, 42, 72
- Hydration, 109, 134-149, 150-167
- And fly ash, 118
 - And slump loss, 82
 - Products of, 130
 - Secondary, 130
- Hydraulic reaction, 135
- I**
- Ice, 19, 30
- Elasticity of, 34
 - In cement pores, 22, 34-36
- Icebergs, 4
- Induction period, 17
- Intrusion pressure, 160-161
- Iron oxide, 98
- Iron sulfide, 38, 56
- K**
- Khan, T. S., 68-87
- Kilns, electric, 42
- L**
- Laminar flow, 155
- Lightweight concrete, 21-37
- Lignin retarder, 95
- Lignosulfonate, 71-86
- Lime, 130-131
- Limestone, 38-67
- Liquids, cryogenic, 36
- Loading, cyclic, 21-37
- M**
- Magnesium oxide, 98, 152
- Malhotra, V. M., 38-67
- Map-cracking, surface, 60
- Mass concrete, 118-133
- Maturity functions, 169
- Arrhenius, 107-117
 - Nurse-Saul, 107-117
- Maturity history, 171
- Meininger, R. G., 68-87
- Microcracks, 141
- Micrographs, electron microscope, 104-105, 159
- Microstructure, 159
- Migration of alkali-metal ions, 146
- Milling techniques, 136
- Mittelacher, M., 88-105
- Mixer, countercurrent, 41
- Moduli
- Elasticity, 5, 26, 30-33, 36, 121-123, 130, 163
 - Young's 5, 10-12, 19, 165
- Moisture (*see also* Water/cement ratio), 22, 26, 36, 43
- And pulse velocity, 66
 - Loss of, 72, 123

- Molds
 Cast iron, 120
 Steel, 42
- Mortars, 140, 150-167
- MTS testing machine, 23
- N**
- Naik, T. R., 107-117
 Nakagawa, Z., 150-167
 Naphthalene-formaldehyde super-plasticizer, 95, 119
 Nasser, K. W., 118-133
 Nitrogen, liquid, 24
 Nuclear waste storage, 155
 Nurse-Saul maturity function (*see*
 Maturity functions)
- O**
- Office building, use of concrete in, 95, 96, 97
 Oven drying, 26
 Owens, P. L., 134-149
 Oxidation, 56
- P**
- Pastes, 105, 141, 150-167
 Permeability (*see also* Tests), 22, 134-149, 155, 161-162, 166
 Petrographic investigations, 56
 Plastic
 Jackets, 121
 Plexiglas seals, 155
 Polyethylene bags, 72
 Saran wrap, 26
 Platens, loading, 25
 Poisson's ratio, 5, 26, 121
 Polivka, M., 21-37
 Pore space, 103, 147, 151, 154, 159-161, 165
 Pore-water pressure, 140
 Porosimeter, 154
- Portland cement, 39, 40, 71-72, 94, 119, 150-167
 High-heat, 134-149
- Power plant, 168-176
 Use of concrete in, 91, 92, 97
- Pozzolans, 119, 137-139, 147
- Pseudothixotropic flow, 159
- Pulse velocity, 39, 42, 52-53, 65, 67
- Pumpability, 166
- Pyrites, 56
- Q**
- Quartz, 151, 160
 Quartzite, 141
- R**
- Railroad, use of concrete in, 90, 94, 97
 Ready-mix concrete, 5
 Refrigeration (*see* Cold storage)
 Resonant frequency, 39, 54-55, 65, 67
 Reynolds number, 155
 Rodding, 120
 Roy, D. M., 150-167
- S**
- Salt, 4
 Chemical composition of, 6
 Sand, 160
 Manufactured, 94
 Natural, 14, 25, 38, 67, 71, 94
 Scaffold system, 172, 175
 Scatter diagrams, 91-96, 100
 Seal chambers, 155
 Sealed concrete, 118-133
 Seawater
 Artificial, 4-13
 Composition of, 14
 Set-retarder, 88-105
 Shah, V. K., 3-20

- Shear stress, 159
 Shock, thermal, 23
 Shrinkage, drying, 69, 72-73, 79, 83-84
 Silica fume, 151, 157, 166
 Silicates, 103-105, 130-131
 Alpha-dicalcium, 131
 Calcium, 138, 163
 Tricalcium, 136
 Silicon oxide, 98, 151
 Slag, 39
 Cements, 150-167
 Slump, 14, 25, 41, 69, 70-72, 82, 120, 121, 141, 144
 Slurries, 154, 158
 Sodium oxide, 98, 136
 Standard-weight concrete, 36
 Steam, 123
 Pressure of, 130
 Steel
 Cage, 16
 Cylinders, 121
 Molds, 42
 Storage
 Cold, 4, 69
 Room, 38-39
 Storm-wave action, 21-37
 Strain gages, 25, 26, 30-31
 Strip chart recorder, 154
 Sulfates, 118
 Sulfites, 98
 Summary, 177
 Superplasticizers, 95, 118-133, 152, 158-159
- Low, 3-20, 25-30, 107-115
 Room, 39, 43
 Temperature-strength correlation (*see* Compressive strength)
 Tests (*see also* ASTM Tests)
 Compression (*see also* Compressive strength), 4, 25, 43, 45, 46
 Cyclic loading, 26
 Drying shrinkage, 72-73
 Field, 13-20, 89-105
 Field cylinder, 173
 Figg permeability, 140, 145-146
 Fineness, Blaine, 98
 Gillmore set, 98
 Initial surface absorption (ISAT), 140, 145
 International Organization for Standardization (ISO), 147
 Soundness, 99
 Splitting tension, 25, 30
 Tensile strength, 26
 Thermal cracking, 144
 Thermal peaks, 157
 Thermal strain, 22-23
 Thermocouples, 7, 24, 25, 43
 Titanium dioxide, 152
 Tobermorite gel, 131, 132
 Transformers, linear variable differential (LVDTs), 25, 30-32
 Tricalcium aluminate (*see* Aluminates)
 Truck mixers, 70

V

- Vinsol resin, 119
 Viscometer, 155
 Viscosity, 154, 158-159

W

- Washburn equation, 154
 Water (*see also* Moisture; Steam)
 Adsorbed versus bulk, 34

T

- Temperature
 Average, 17, 68-87
 Cryogenic, 21-37
 Cycles, 134-149
 High, 38-67, 68-87, 88-106, 122-125, 150-167
 Limiting, 69

- Bath, 121
Measurement of permeability, 22, 134-149, 155, 161-162, 166
Mixing, 69, 73, 75-78, 82-86
Pore-water pressure, 140
Reducers, 70, 75-86, 118-133
Vapor, 56
- Water/cement ratio, 4, 7, 8, 14, 22, 39, 41, 44, 50-51, 56, 63, 65, 67, 69, 110, 118-119, 134, 135, 153
- Related to permeability, 147
Weight of concrete, 39, 43, 50-51, 60
White, E. L., 150-167
Willow Island cooling tower, 168-176

Y

Young's modulus (*see* Moduli)