Subject Index

A

Acoustic harmonics, 78
Acoustic radiation, 239
Ag-Au alloys, Zener relaxation, 394
Air, damping properties, 239
Alloys, high-damping, 162
Alumina, damping due to grain boundary sliding, 128
Amplitude-dependent damping, 78
  Cu-Al-Ni crystals, 94
  synthesizing model, 302
  under combined stresses, 349
  YBCO ceramics, 251
Anelasticity
  as function of temperature, 214
  high-temperature, 128
  resonant sphere technique, 267
Anelastic strain, 22
  Cu-Al-Ni crystals, 94
Anisotropy, 267
Antiferromagnetic domains, 365
Atomistic mechanism, 383
Attenuation, 267
Austenitic steels, complex alloyed, internal friction, 179

B

Binding energy, 383
Body-centered-cubic metals, 383

C

Carbides, in grain boundaries, 4
Carbon
  as foreign interstitial atoms, 189
  in solid solution, effect on damping, 365
Carbon Snoek relaxation, 189
Ceramics
  amplitude-dependent damping, 251
  damping due to grain boundary sliding, 128
  elastic and anelastic properties, 214
Cesium, Ni-Cr alloys, 4
CMSX-4, high-temperature damping, 143
Coatings, Fe-Cr-X, 115
Composites
  cylinders, in-air and underwater damping properties, 239
  damping, 62, 313
  damping capacity, 288
Computer simulation, 179, 394
Constrained layer damping, 62
Cottrell atmosphere, 189
Coupling model, 189
Crossover effect, 251
Crystals
  amplitude-dependent damping, 349
  dislocation amplitude-dependent damping, 22
Cu-Mn alloys, high damping, 365
Cu-Zn alloys, Zener relaxation, 394

D

Dampers, modeling, 331
Damping capacity, 115, 204
  zinc-aluminum alloy, 288
Debye-type relaxation peaks, superposition, 179
Diffusion mechanism, 143
Discontinuous precipitation, internal friction associated with, 46
Dislocation amplitude-dependent damping, 22
Dislocation damping, modeling, 78, 302
Dislocation-defect interaction, 189, 251
Dislocation structure, relaxation, 153
Domain wall pinning, 162

E

Elastic moduli, 143
Elastic properties, as function of temperature, 214
Electron microscopy
  Fe-Al alloys, 204
  Fe-Cr-based alloys, 162
Electrorheological fluid based dampers, modeling damping, 331

F

Fe-Al alloys, high damping state, 204
Fe-Cr alloys
  magnetomechanical damping, 162
  Snoek relaxation, 278

Fe-Cr-X coatings, magnetomechanical damping, 115
Fe-Ni-Mo alloys, 179
Fractals, 302

G

Grain boundary
  peak, 4
  sliding, damping due to, 128
Granato-Lücke theory, 349

H

Harmonic generation, modeling, 78
Helicopter rotor systems, viscoelastic damping layers, 62
High damping, Cu-Mn alloys, 365
High damping state, Fe-Al alloys, 204
Hilbert transform, 62
Hysteresis, 94, 115

I

Interaction energies, computer model, 394
Interatomic interaction energies, 278
Intergranular embrittlement, Ni-Cr alloys, 4
Intermetallic phase, CMSX-4, 143
Internal friction, 189
  associated with discontinuous precipitation, 46
  complex alloyed austenitic steels, 179
  computer model, 394
  dislocation breakaway damping, 78
  Fe-Al alloys, 204
  Fe-Cr alloys, 162, 278
  modeling, 302
  Ni-Cr alloys, 4
  single and polycrystalline materials, 267
  zinc-aluminum alloy, 288
  zirconia and alumina, 128
Internal stress, 22
Interstitial solutes, 383
α-iron, 189

K

Kerr effect, 115
Kink pair formation mechanism, 189

L

Lead-tin alloys, discontinuous precipitation, internal friction associated with, 46
Lead-zirconate-titanate, 227

M

Magnetic domains, 115
  Fe-Al alloys, 204
  Fe-Cr-based alloys, 162
Magnetic field, dislocation displacements, 153
Magnetoelastic damping, 365
Magnetomechanical damping
  Fe-Cr alloys, 162
  Fe-Cr-X coatings, 115
Magnetoplastic effect, 153
Magnetostriction studies, 204
Matrix relaxation, 46
Mechanical loss, 128
  PZT ceramics, 227
Mechanical spectroscopy, 189
Metallurgy, Cu-Mn alloys, 365
Metal matrix composite, damping, 313
Microcreep, 153
Microplasticity, thermally activated and athermal, 22
Modal analysis, 239
Modeling, 179, 394
  electrorheological fluid based dampers, 331
  Zener relaxation, 394
Modulus defect, 251
Monte Carlo method simulation, 278
$MoSi_2/Ti5Si_3$, elastic and anelastic properties, 214
Moties-pinners model, 302
Moving block analysis, 62

N

Neutron refraction
  Fe-Al alloys, 204
  Fe-Cr alloys, 162
Nickel-based superalloy, high-temperature damping, 143
Ni-Cr alloys, high-temperature internal friction and intergranular fracture, 4
Nonlinear dynamic model, 331
Nonmagnetic crystals, dislocation structure relaxation and microcreep, 153

O

Olivine, 267
Oxygen, in grain boundaries, 4

P

Paramagnetic impurities, 153
Parameter estimation, 331
Periclase, 267
Phase transitions, Young's modulus and mechanical loss associated with, 227
Piezoelectric ceramic, 227

Piezoelectric ultrasonic composite oscillator technique, 214, 251
Plasma sprayed coating, 115
Plasticity, thermally activated and athermal, 22
Polarization, 227
Polycrystalline metals, amplitude-dependent damping, 349

R

Resonance absorption by Fe-Cr-X coatings, 115
Resonant sphere technique, anelasticity, 267
Ruthenium, 267

S

Self noise, 239
SiC, elastic and anelastic properties, 214
Smart materials, 331
Snoek-Köster relaxation, 189
Snoek relaxation
  Fe-Cr alloys, 278
  ternary body-centered-cubic alloys, 383
Solute-solute interaction, 383
Spray deposition, 313
Square dependence, 179
Stability augmentation, 62
Strain aging, 365
Strain amplitude, SiC and $MoSi_2/Ti_5Si_3$, 214
Stress
  arbitrary states, 349
  combined, amplitude-dependent damping, 349
  effective, 22
Structure defects, 162
Substitutional interaction, 394
Substitutional solutes, 383, 394
Superconductors, amplitude-dependent damping, 251
System identification, 331

T

Ternary body-centered-cubic alloys, Snoek relaxation, 383
Thermoelastic martensitic transformation, Cu-Al-Ni crystals, 94
TiC particle reinforcement, 288
Torsion pendulum, low-frequency, 288

U

Underwater damping properties, 239

V

Vibrations, 251
  absorption by Fe-Cr-X coatings, 115
Viscoelastic damping, 62
Viscoelasticity, 331

W

Whole factor experiment, 179

X

X-ray scattering
  Fe-Al alloys, 204
  Fe-Cr alloys, 162

Y

YBCO ceramics, amplitude-dependent damping, 251
Young's modulus, 143, 214
  PZT ceramics, 227

Z

Zener peak, 4
Zener relaxation, computer model, 394
Zinc-aluminum alloy, damping capacity, 288
Zirconia, damping due to grain boundary sliding, 128