

Subject Index

A

Abrasion, 3
 Abrasion tests
 case history, 123–124, 123*f*
 plastics/elastomers, 53–55
 Abrasive wear, 1, 4–5, 5–6*f*
 testing, 33–44
 Acid number, 2
 Additive, 2
 Adhesive wear, 1, 5–6, 7*f*, 19
 testing, 45–50
 Amonton model, 18–19, 19*f*
 Asperity, 1
 ASTM D 2981, 66
 ASTM D 3028, 104, 105*f*
 ASTM D 3233, 109
 ASTM D 5183, 68
 ASTM B 611, 39–40, 88
 ASTM B 896, 74, 75*f*
 ASTM Committee D02, definition of grease, 63
 ASTM D 673, 86, 87*f*
 ASTM D 1478, 108
 ASTM D 1630, 56
 ASTM D 2047, 104
 ASTM D 2157, 104
 ASTM D 2228, 56
 ASTM D 2625, 109
 ASTM D 2670, 68, 68*f*
 ASTM D 2714, 66
 ASTM D 2981, 68
 ASTM D 3108, 104–105, 105*f*
 ASTM D 3389, 56
 ASTM D 3412, 104–105, 105*f*
 ASTM D 3704, 124
 ASTM D 4170, 68–69, 69*f*, 76
 ASTM D 4172, 67, 67*f*
 ASTM D 4175, 2–3
 ASTM D 4918, 108
 ASTM D 4998, 69, 69*f*
 ASTM D 5001, 67–68, 68*f*
 ASTM D 5183, 109
 ASTM D 5859, 104
 ASTM D 5963, 56
 ASTM D 6425, 109
 ASTM E 122, 30
 ASTM E 607, 104
 ASTM E 707, 104
 ASTM F 489, 104
 ASTM F 695, 104
 ASTM F 1875, 75–76, 75*f*
 ASTM Committee G02, 4

ASTM G 32, 59, 91, 92*f*
 ASTM G 40, 1–2, 91, 95, 101
 ASTM G 56, 41–42*f*
 ASTM G 65, 33–35, 53–54, 55*f*, 56
 ASTM G 73, 59, 91
 ASTM G 75, 59, 59*f*, 124–125, 125*f*
 ASTM G 76, 47, 59, 86–87, 127
 ASTM G 77, 47–48, 56–57, 57*f*, 66, 106, 106*f*, 128
 ASTM G 98, 45, 48
 ASTM G 99, 12, 45–46, 57, 67, 67*f*, 106, 106*f*
 ASTM G 105, 33, 34*f*, 88
 ASTM G 115, 100–102, 100–102*f*, 104, 104*t*
 ASTM G 118, 25, 103–104
 ASTM G 119, 89
 ASTM G 132, 36, 36*f*
 ASTM G 133, 12, 46–47, 49, 57, 66, 107, 107*f*, 110, 127–128
 ASTM G 134, 59, 92, 93*f*
 ASTM G 137, 47, 56, 106, 106*f*
 ASTM G 143, 104–105, 105*f*
 ASTM G 163, 102–103
 ASTM G 164, 108, 109
 ASTM G 171, 36–37, 37*f*, 55, 56*f*, 112, 117
 ASTM G 174, 35–36*f*, 54–55, 55*f*, 56, 123–124, 123*f*
 ASTM G 176, 106, 106*f*
 ASTM G 181, 49
 ASTM G 182, 108
 ASTM G 190, 30
 ASTM G 1242, 37, 37*f*
 ASTM G 4060 (Taber), 37–38, 38*f*
 ASTM STP 1159, 74
 ASTM tests for modes of wear and friction, 121*f*
 Atomic force microscopy (AFM), 114*t*
 Atomic/molecular erosion, 11
 Auger electron spectroscopy (AES), 114*t*

B

Ball bearings
 friction at low temperature, 108, 108*f*
 friction at room temperature, 108, 108*f*
 Ball catering test, 42–43, 42–43*f*, 89, 89*f*
 Ball on cylinder (BOCLE), 67–68, 68*f*
 Ball-on-plane, 73–74*f*
 Base oil, 2
 Bearing friction tester, 107–108, 108*f*
 Berkovitch tip, 115*f*
 Biotribology, 1, 118

tests, 118
 Block-on-ring test, 47–48, 48–49*f*, 56–57, 57*f*, 66, 106, 106*f*
 solid lubricants, 68
 Boundary lubrication, 3
 Break-in, 2, 58, 58*f*

C

Capstan friction, 104–105, 105*f*
 Carbide abrasion test, 88, 89*f*
 Cavitation, 91–93
 submerged water jet test, 92–93, 93*f*
 testing with an ultrasonic horn, 91–92, 92*f*
 Cavitation erosion, 1, 10, 10*f*, 21
 Chemical mechanical polishing (CMP), 3, 5
 Chemo-mechanical planarizing (CMP), 5
 Coatings and surface treatments, fatigue testing, 78–79, 80*f*
 Coefficient of friction, 1, 95, 101, 123
 Computer simulations, 17, 17*f*
 Contact geometry, 121*f*
 Crude oil, 2

D

Diamond-like carbon (DLC), 123
 DIN (Deutsches Institut für Normung), 3
 Droplet erosion, 3, 10, 11*f*
 Droplet/impingement erosion, 90–91, 91*f*
 Dropping point, 3
 Dry film, 13
 Dry-sand rubber wheel, 53–54, 55*f*
 Dry solid film lubricants, 3

E

Elastohydrodynamic lubrication, 3, 14
 Electrical contact tests, 74, 75*f*
 Erosion, 1–2, 9–11
 plastics, 59
 testing, 86–94
 types, 4*f*
 Erosion/corrosion test, 2, 90, 90*f*
 case history, 128, 128*f*
 Erosion models, 19–21
 Expert systems, 16–17

F

Fafnir test, 68–69, 69*f*
 Falex pin and vee block test, 109
 Falling sand, 53, 54*f*
 Falling sand test, 86, 87*f*
 Fatigue wear, 2
 Film/paper abrasivity tester, 42*f*

NOTE: Entries followed by *f* indicate figures; *t* indicates tables.

Finite element modeling (FEM), 17–18, 18*f*
 Flash point, 3
 Fluid friction, 12
 Fluid vs. solid friction, 96–98, 96*f*
 Footwear tests, 104
 Four-ball friction test, 68, 109
 Four-ball test, 67, 67*f*
 Fourier transform infrared spectroscopy (FTIR), 114*t*
 Fretting, 2, 7, 7*f*
 Fretting corrosion and wear, 2, 6
 case history, 125–126, 126*f*
 mechanism, 71–72, 72*f*
 Fretting fatigue, 74
 Fretting models, 21–22
 Fretting tests, 71–77
 types, 72–73*f*, 72–76
 Friction, 3
 databases, 98, 99*t*
 factors that effect, 98–99, 99–100*f*
 importance of, 96
 types, 5*f*, 12–13, 95–111, 96–98, 96*f*
 Friction data, reporting of, 103–104
 Friction force, 2
 Friction measurement, recording protocol, 102–103, 102*f*
 Frictionmeter, 104, 105*f*
 Friction models, 18–19, 19*f*
 Friction testing, 12–13, 95–111, 96*f*
 case history, 123, 123*f*
 FZG RIG, 69, 69*f*

G

Galling, 2, 6, 7*f*, 45, 46*f*
 Gas erosion, 10–11
 Gas jet erosion test, 86–87, 88*f*
 Gas lubrication, 14, 14*f*
 Gears
 fatigue tests, 84, 84*f*
 surface fatigue testing, 81–82, 82*f*
 testing with FZG rig, 69, 69*f*, 84, 84*f*
 Gouging, 3, 6*f*
 Gouging abrasion, 33, 34*f*
 Grease lubrication, 14, 76

H

Hertzian contact pressure, 2
 High-stress abrasion, 39–40, 39*f*
 Hip implant couples, 75–76, 75*f*
 Human joint deterioration, 8–9, 9*f*
 Hydrodynamic lubrication, 3

I

Impact wear, 2, 7–8, 8*f*, 78–85
 surface fatigue testing and, 82–83, 82–83*f*
 tests, 85, 85*f*
 Impingement, 2
 Impingement erosion, 10, 11*f*
 Indentation testing, 115, 115*f*
 Insolubles, 3

K

Kinematic viscosity, 3
 Kinetic coefficient of friction, 2

L

Laser ablation, 11
 Liquid erosion, 20
 Liquid lubricants, 13–14, 14*f*

Load-carrying capability tests, 68
 Load-wear index, 3
 Loop abrasion test, 54–55, 55*f*
 Low-stress abrasion, 33–39, 34*f*
 nonstandard tests, 38–39, 38*f*
 Lubricants, 3
 types, 5*f*, 13–14, 98*f*
 Lubricated fretting test, 68–69, 69*f*
 Lubricated wear testing, 62–70, 63*f*, 64*t*
 case history, 127–128, 127*f*
 Lubricating greases, 3, 63, 65*t*
 Lubricating oils, 3, 62–63
 Lubricity, 3

M

Magnetic tape abrasivity test, 42*f*
 Mass spectroscopy (MS), 114*t*
 Matching wear, 8, 9*f*
 Material documentation, for a valid wear test, 26
 Micro, nano, and biotribotests, 112–119
 Microtribology, 1
 Miller slurry test, 59, 59*f*
 Modeling and simulation, 16–23
 Mohs hardness, 117*t*

N

NACE liquid erosion test, 90*f*
 Nanotribology, 1
 Nonabrasive wear, 5–6
 case history, 124, 124*f*

O

Optical microscopy, 113, 114*t*
 Orifice enlargement, 90
 Oxidation, 3
 Oxidative wear, 3, 6–7*f*, 49–50, 49*f*

P

Pavement/tire tests, 104
 Petroleum, petroleum products, and lubricants, terminology, 2–3
 Pin and Vee block test, 68, 68*f*
 Pin-on-disk, 45–46, 46–47*f*, 57, 67, 67*f*, 106–107, 107*f*
 Plastic/elastomer wear, 51–61
 erosion, 59
 nonstandard tests, 60
 polymer wear and erosion, 52*f*
 specific wear rate, 58
 tribological idiosyncrasies of plastics, 52*t*
 wear mechanisms, 52*f*
 Plastic sliding, 18*f*
 Plastic-to-ceramic/cermet, 58
 Plastic-to-metal, 56–57, 57*f*
 Plastic-to-plastic, 57
 Polishing, 3, 5, 6*f*
 case history, 126–127*f*
 Polishing abrasion, 40–41, 40–41*f*
 Pour point, 3
 Procedure B reciprocating ball-on-plane and lube test, 110
 Product abrasivity, 41–42, 41*t*
 Profilometry, 113
 Propeller tests, 89, 89*f*
 PV limit, 58–59, 58–59*f*
 PV product, 2

R

Rails, tracks, and wheels, surface fatigue testing, 81, 81*f*
 Raman spectroscopy (Raman), 114*t*
 Reciprocating ball-on-plane, 46–47, 47*f*
 Reciprocating block-on-plane, 107, 107*f*
 Reciprocating lubricated friction and wear (SRV machine), 109, 110*f*
 Reciprocating test, 66
 Reporting wear losses, for a valid wear test, 29–30
 Role of time and distance, for a valid wear test, 28
 Rolling, 2
 Rolling element bearings, fatigue testing, 79–81, 80*f*
 Rolling element tests, 69–70, 69–70*f*, 83–84, 83–84*f*
 Rolling friction, 12, 96–98, 96*f*, 107–108, 107*f*
 Rolling surface fatigue tests, 84–85, 84–85*f*
 Rolling wear, 2, 7, 8*f*, 78–85, 86*f*
 Rubber abrasion, 55–56, 56*f*
 Run-in, 2

S

Scanning electron microscopy (SEM), 114*t*, 115–116, 115*f*
 Scanning probe microscopy (SPM), 114*t*, 116–117, 116–117*f*
 Scanning tunneling microscopy (STM), 114*t*
 Scoring, 2
 Scratches, 3
 Scratching abrasion, 4, 6*f*
 Scratch testing, 55–56*f*, 117–118, 118*f*
 Mohs hardness, 117*t*
 Scuff, scuffing, 3
 Scuffing/scoring, 48–49, 49*f*
 Secondary ion mass spectroscopy (SIMS), 114*t*
 Sliding friction, 12
 Sliding friction tests, 100–102, 100–102*f*
 Sliding wear, plastics/elastomers, 56–58
 Slip, 3
 Slurry abrasivity, case history, 124–125, 125*f*
 Slurry erosion, 3, 9, 9*f*, 20
 Slurry erosion tests, 87–90, 88*f*
 Slurry pot test, 89–90, 90*f*
 Soap, 3
 Solid film, 13, 13*f*
 Solid film lubricants, 63–66
 Solid-on-solid friction, 96–98, 96*f*, 104
 Solid-on-solid with fluid friction, 96–98, 96*f*, 109, 109*f*
 Solid-on-solid with third body friction, 96–98, 96*f*, 105–106, 105*f*
 Solid particle erosion, 3, 9–10, 10*f*, 19–20
 Solid particle erosion tests, 86–87, 87*f*
 case history, 126–127, 127*f*
 Solid particle impingement erosion, 2
 Spalling, 7, 8*f*
 Spark erosion, 11, 12*f*
 Spin-down friction testing, 108, 108*f*
 SRV, 3
 Static coefficient of friction, 2
 Static friction/blocking, 12–13

132 GUIDE TO FRICTION, WEAR, AND EROSION TESTING

Statistical significance, for a valid wear test, 26–27, 28*f*
 Stick-slip, 2, 101
 Stiction, 2, 101
 Surface analysis tools, 112–114, 113–114*f*, 113–114*t*
 Surface condition, for a valid wear test, 27–28
 Surface fatigue models, 22
 Surface fatigue testing, 78–85
 coatings and surface treatments, 78–79, 80*f*
 gears, 81–82, 82*f*
 impact wear and, 82–83, 82–83*f*
 rails, tracks, and wheels, 81, 81*f*
 rolling, 84–85, 84–85*f*
 rolling element bearings, 79–81, 80*f*
 Synthetic, 3

T

Taber abraser, 53, 54*t*, 55*f*
 Test confidence, 120
 Test data plotted with error bars, 122*f*
 Test environment, for a valid wear test, 28
 Testing, alternatives to, 16–23
 Test specimens, 122*t*
 Thickener, 3

Thin film, 13
 Three-body abrasive wear, 2
 Thrust washer test rig, 105*f*
 Topographic measures, 113*t*
 Traction, 2
 Traction coefficient, 2
 Transmission electron microscopy (TEM), 114*t*
 Tribology, 1, 2
 Tribometer, 1
 Tribosystem, 1
 Tribotesting, 1, 129*t*
 Two-body abrasive wear, 2

U

Ultra high molecular weight polyethylene (UHMWPE), 124

V

Viscosity, 3
 Viscosity index, 3

W

Wear
 categories of, 4, 4*f*
 different types, 1–15
 identification of mode, 3–4
 terminology, 1

Wear and friction measurements, for a valid wear test, 28–29, 29*f*
 Wear coefficient, 2
 Wear map, 2
 Wear models, 19
 Wear modes, 24*f*
 Wear rate, 2
 Wear test selection, 24–32, 121–123
 confidence and correlation with service, 120–129
 correlation case histories, 122–128
 define the system, 25–26
 elements of a valid test, 26–30
 features of some common tests, 32*t*
 objective, 24–25*f*
 reporting the data, 25–26, 26–27*f*
 wear/friction test checklist, 31*t*
 Wet sand/rubber wheel test, 88, 89*f*

X

X-ray diffraction (XRD), 114*t*
 X-ray photoelectron spectroscopy (XPS), 114*t*

Y

Yarn wear test, 42*f*