



An Environmental Product Declaration

In accordance with ISO 14025:2006 and ISO 21930:2017





ASTM International Certified Environmental Product Declaration

This document is a Type III environmental product declaration (EPD) covering five groups of steel doors as manufactured by AMBICO at their facility in Ottawa, Ontario.

This declaration has been prepared in accordance with ISO 14025 (1), ISO 21930 (2), ISO 14040/44 (3), (4), UL Environment's Product Category Rules for Commercial Steel Doors and Steel Door Frames (5), (6), and ASTM's General Program Instructions for Type III EPDs (7).

The intent of this document is to further the development of environmentally compatible and more sustainable construction methods by providing comprehensive environmental information related to the potential impacts of AMBICO's steel doors in accordance with international standards.

Environmenta	Product	Declaration	Summary
--------------	---------	-------------	---------

General Information	
Owner of the EPD	AMBICO Ltd. 1120 Cummings Avenue Ottawa, ON K1J 7R8 Link (URL) <u>https://www.ambico.com/</u> Established in 1955, AMBICO has become a leading supplier in the global market for precision doors, door frames, and windows for commercial and industrial facilities, including hospitals, military installations, prison facilities, hotels, museums, and art galleries.
	The owner of the declaration is liable for the underlying information and evidence.
Manufacturing Sites	Ottawa, ON 1120 Cummings Avenue K1J 7R8
Product Group	Steel Doors





Product Definition	Steel doors designed and manufactured for a wide array of uses, including acoustic, blast and pressure resistant, bullet resistant, flood resistant, and lead lined assemblies.
Product Category Rule (PCR)	UL Environment, Product Category Rule for Building-Related Products and Services.
	Part A: Life Cycle Assessment Calculation Rules and Report Requirements, Version 4.0. March 2022 (5).
	Part B: Commercial Steel Doors and Steel Frames EPD Requirements (6).
	ISO 21930:2017 serves as the core PCR (2).
Certification Period	April 11 th , 2025 – 5 year validity
Declared Unit	One commercial steel door, nominal dimensions of 3-feet by 7-feet considered in isolation (6).
ASTM Declaration Number	EPD 915
EPD Information	
Program Operator	ASTM International 100 Barr Harbor Drive, PO Box C700 West Conshohocken, PA 19428-2959, USA <u>https://www.astm.org/products-</u> <u>services/certification/environmental-product-</u> <u>declarations/epd-pcr.html</u>

Declaration Type

This production weighted average cradle-to-gate EPD applies to AMBICO's steel doors (all finishes and assembly types). The life cycle stages covered are the extraction and upstream production (A1), transportation to factory (A2), and manufacturing (A3). The declaration is intended for Business-to-Business (B-to-B) communication.

Applicable Countries

North America

Product Applicability

AMBICO's doors are designed and manufactured to meet a wide array of commercial applications, including but not limited to acoustic, blast & pressure resistant, bullet resistant, flood resistant, and lead lined assemblies. The steel door declared unit is presented as a mass-weighted average of steel doors designed and manufactured by AMBICO for use in all assembly types.





This EPD was independently verified	
by ASTM in accordance with ISO 14025:	daley & Bearle
Internal <u>External</u>	D
X	Tim Brooke 100 Barr Harbor Drive, PO Box C700 West Conshohocken, PA 19428-2959, USA <u>https://www.astm.org/</u>
EPD Project Report Information	
EPD Project Report	A Cradle-to-Gate Life Cycle Assessment of Steel Frames, Steel Doors, and Wood Doors Manufactured by AMBICO Ltd. (8).
Prepared by Athena Sustainable Materials Institute	Athena Sustainable Materials Institute 280 Albert Street, Suite 404 Ottawa, Ontario. K1P 5G8 <u>info@athenasmi.org</u>
The EPD project report was independently verified by and in accordance with ISO 14025 and the reference PCR:	Thomas P. Gloria, Ph.D. Industrial Ecology Consultants 35 Bracebridge Rd. Newton, MA 02459-1728
PCR Information	
Program Operator	UL Environment
Reference PCR	UL Environment, Product Category Rule for Building-Related Products and Services. Part B: Commercial Steel Doors and Steel Frames EPD Requirements (6).
Date of Issue	September 2020
PCR review was conducted by:	Lindita Bushi, Ph.D, LEED Green Associate. Athena Sustainable Materials Institute Tim Weller, AHC/CDC, FDAI. Allegion Dan Glover. ASSA ABLOY Door Group
EPD Explanatory material	Please contact the program operator for any explanatory material regarding this EPD. ASTM International Environmental Product Declarations
	100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, http://www.astm.org





1 PRODUCT IDENTIFICATION

1.1 PRODUCT DEFINITION

AMBICO's steel doors are designed to be installed in conjunction with steel door frames. The door assemblies manufactured by AMBICO are designed and manufactured to meet a wide array of uses, including but not limited to acoustic, blast and pressure resistant, bullet resistant, flood resistant, and lead lined assemblies.

This EPD presents the results for five groups of steel doors, with products grouped according to their mass. Table 1 below outlines the products included in each group.

Product Group	Included Products
Group 1	HM, RFXX, PRS1, PRS3, PRVS, and STC33 to STC38
Group 2	TORST, LL2B, and STC39 to STC51
Group 3	BR01 to BR03, PRS5, CLBR, LL4B, and LL6B
Group 4	STC52 & STC53, PRSC, BR04 & BR06, PLATE
Group 5	STC54 to STC59, BR05, BR07, and BR08

Table 1: Percent Production by Mass of Steel Doors by Product Type

1.2 PRODUCT STANDARDS

AMBICO's door assemblies are designed and manufactured to meet various performance standards depending on the end-use of the product, including but not limited to:

- NFPA 80-16: Standard for Fire Doors and Other Opening Protectives.
- UL 10C-16: Standard for Positive Pressure Fire Tests of Door Assemblies.
- ASTM E90-09(2016): Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements
- ASCE: Design of Blast Resistant Buildings in Petrochemical Facilities.
- UFC 3-340-02 Structures to Resist the Effects of Accidental Explosions.
- UFC 4-010-01 DoD Minimum Antiterrorism Standards for Buildings.





2 DECLARED UNIT

The declared unit is defined as one commercial steel door, nominal dimensions of 3-feet by 7-feet considered in isolation (6). The physical properties and characteristics of the declared unit are presented in Table 2 below.

Table 2: Phy	ysical Propert	ies of Declared	Unit – Steel Door

Material Property	Value per Declared Unit
Total Area (ft²)	21
Thickness (in)	1 ¾
Total Mass (lbs)	Group 1: 136.5
	Group 2: 180.8
	Group 3: 239.0
	Group 4: 315.0
	Group 5: 446.3
Mass per Unit Area (lbs/ft²)	Group 1: 6.50
	Group 2: 8.61
	Group 3: 11.38
	Group 4: 15.00
	Group 5: 21.25

Technical information such as thermal transmittance, air leakage, deflection, and sound transmittance information is not available for the average product covered in this EPD. Product specifications and drawings are available through AMBICO's website:

https://www.ambico.com/all-products/





3 MATERIAL CONTENT

The average material composition by input material (in %) for AMBICO's steel doors is provided in Table 3 below.

Material input	Material Content (in %)
Galvannealed steel	76%
Lead	9%
Steel tubes, angles, and channels	6%
Stainless steel	4%
Galvanized steel	1%
Fiberglass insulation	1%
Polystyrene insulation	1%
Primer	1%
Plastic laminate	1%
Ероху	<1%
Bronze	<1%
Total weight (Input)	100%

4 SYSTEM BOUNDARY

Figure 1 shows the life-cycle stages and information modules that are included within the cradle-to-gate LCA system boundary of this EPD. The boundary is "cradle-to-gate", which consists of Extraction and Upstream Production (A1), Transportation to Factory (A2), and Manufacturing (A3).

Figure 2 provides a visual representation of the cradle-to-gate system boundary as applied to AMBICO's manufacturing facility.





An Environmental Product Declaration In accordance with ISO 14025 and ISO 21930 AMBICO Steel Doors

PRODUCTION Stage	CONSTRUCTION Stage	USE Stage	END OF LIFE Stage	Optional supplementary
A1 Extraction and upstream production	A4 Transport to site	B1 Use	C1 De-construction Demolition	beyond the system boundary
A2 Transport to factory	A5 Installation	B2 Maintenance	C2 Transport	D Potential net benefits from
A3 Manufacturing		B3 Repair	C3 Waste Processing	reuse, recycling, and/or energy recovery beyond the system
 		B4 Replacement	C4 Disposal of waste	boundary
		B5 Refurbishment		I I Included
1 		B6 Operational Energy Use		Excluded
 Life Cycle Information wit	hin the System Boundary	B7 Operational Water Use		

Figure 1: Life Cycle Stages and Modules





An Environmental Product Declaration In accordance with ISO 14025 and ISO 21930 AMBICO Steel Doors



Figure 2: AMBICO Cradle-to-Gate System Boundary





5 LIFE CYCLE INVENTORY

5.1 DATA COLLECTION, SOURCES, AND CALCULATIONS

LCI data collection was based on a customized LCI survey. The LCI survey covered the primary data for AMBICO's manufacturing facility in Ottawa, ON for the 2023 reference year (12 consecutive months). Data calculation procedures follow ISO 14044 (4), and UL Environment's PCR for Commercial Steel Doors and Steel Frames (5), (6).

5.2 DATA QUALITY REQUIREMENTS AND ASSESSMENTS

The LCA project report provides a detailed description of the collected data and the data quality assessment regarding the UL Environment PCR requirements (5), (6) and ISO 14044 (5). Data quality is assessed based on its representativeness (technology coverage, geographic coverage, time coverage), completeness, consistency, reproducibility, transparency, and uncertainty (Table 4)

Data Quality Requirements	Description
Technology Coverage	Data represents the prevailing technology at AMBICO's facility in Ottawa, ON. Whenever available, North American typical or average industry LCI datasets were utilized for all upstream and core materials and processes.
	Technological representativeness is characterized as "high".
Geographic	The geographic region considered is the U.S. and Canada.
Coverage	Geographical representativeness is characterized as "high".
Time Coverage	Activity (primary) data are representative of the 2023 calendar year (12 months) and
	include the following:
	- Manufacturing material inputs for steel doors,
	-Inbound and outbound transportation data,
	-Production output and waste
	Temporal representativeness is characterized as "high".

Table 4: Data Quality Requirements and Assessment





Completeness	All relevant, specific processes were considered and modelled, including inputs (raw materials, energy, and ancillary materials) and outputs (emissions, waste, and production volume). The relevant background materials and processes were taken from the US LCI Database (adjusted for known data placeholders), ecoinvent v 3.9.1 LCI database for US, and third-party verified EPDs where applicable. The modelling has been completed in SimaPro v.9.5, 2024 (9). The completeness of the cradle-to-gate process chain in terms of process steps is rigorously assessed for steel doors and documented in the project report.
Consistency	The LCA team conducted mass balances at the facility and product level and selected process levels to maintain high consistency.
Reproducibility	Internal reproducibility is possible since the data and the models are stored and available in the <i>Athena AMBICO LCI database</i> developed in SimaPro v.9.5, 2024 (9). A high level of transparency is provided throughout the critically reviewed LCA project report as the LCI profile is presented for each declared product and major upstream inputs. The supporting LCA project report summarizes key primary (manufacturer-specific) and secondary (generic) LCI data sources.
Transparency	Activity and LCI datasets, including data sources, are transparently disclosed in the project report.
Uncertainty	A <i>sensitivity check</i> was conducted to assess the reliability of the EPD results and conclusions by determining how they are affected by uncertainties in the data or assumptions on the calculation of LCIA and energy indicator results. The LCA background report includes the results of a <i>sensitivity analysis</i> and <i>Monte Carlo uncertainty analysis</i> .

5.3 ALLOCATION RULES

This EPD follows the allocation guidelines of ISO 14044 (4) and the UL PCR (5), (6). AMBICO's manufacturing facility produces various co-products, such as steel frames, wood door leaves, astragals, side lites, and transoms. Production output and packaging data has been provided specific to steel doors, however allocation was required to calculate material inputs, waste, energy inputs, and ancillary materials. Mass was used as the physical parameter for allocating flows between the products of interest and other co-products to calculate the input material usage (galvannealed steel, stainless steel, etc.), energy flows (electricity, natural gas, propane, etc.), welding gasses, hydraulic fluid, greases, total water consumption, and waste flows. Allocation related to transport is based on the mass of transported inputs and outputs.





5.4 CUT OFF RULES

The cut-off criteria were followed as specified in the UL PCR Part A, Section 2.9 (5) and ISO 21930, 7.1.8 (2). All input/output data reported by AMBICO's manufacturing facility were included in the model. None of the reported flow data were excluded based on the cut-off criteria. No substances with hazardous and toxic properties that concern human health and/or the environment were identified in the framework of this EPD.

This EPD excludes the following processes and activities:

- Capital goods and infrastructure, and
- Personnel-related activity (travel, furniture, office operations and supplies).

6 LIFE CYCLE ASSESSMENT RESULTS

Table 5 through Table 9 present the "cradle-to-gate" LCA results for each grouping of steel doors as manufactured by AMBICO. As per the UL PCR, the US EPA Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts (TRACI), version 2.1, 2012 (10) impact categories are used as they provide a North American context for the mandatory category indicators to be included in this EPD. *These are relative expressions only and do not predict category impact endpoints, the exceeding of thresholds, safety margins or risks* [4], [5]. As per the PCR, it is also noted that the variation in life cycle impact category results within each product group is less than 10%.

Additional mandatory resource use, waste categories and output flows are also reported as specified in ISO 21930 (2). There are several emerging LCA impact categories and inventory metrics which are still under development and can have high levels of uncertainty that preclude international acceptance. These categories are noted with an asterisk (*) – use caution when interpreting data in these categories.





Table 5Production stage EPD Results (Total A1 to A3) – Steel Door Group 1HM, RFXX, PRS1, PRS3, PRVS, and STC33 to STC38

Impact category and inventory indicators	Unit	A1	A2	A3	A1-A3 Total
Global warming potential, GWP 100 ¹⁾	kg CO₂ eq	1.92E+02	2.05E+00	1.19E+02	3.13E+02
Acidification potential, AP ¹⁾	kg SO₂ eq	6.64E-01	2.42E-02	5.59E-01	1.25E+00
Eutrophication potential, EP ¹⁾	kg N eq	1.75E-01	1.45E-03	2.13E-01	3.89E-01
Smog formation potential, SFP ¹⁾	kg O₃ eq	7.71E+00	6.18E-01	5.51E+00	1.38E+01
Ozone depletion potential, ODP ¹⁾	kg CFC-11 eq	2.62E-06	8.48E-11	1.22E-06	3.84E-06
Abiotic depletion potential for non-fossil mineral resources ^{*2)}	Kg Sb eq	7.02E+01	0	9.83E-06	7.02E+01
Fossil fuel depletion, FFD ^{*1)}	MJ surplus, LHV	2.60E+01	4.26E+00	1.79E+02	2.09E+02
Abiotic depletion potential for fossil resources, ADPf ^{*3)}	MJ, LHV	2.16E+03	2.88E+01	1.49E+03	3.68E+03
Renewable primary resources used as an energy carrier (fuel), RPRe*4)	MJ, LHV	1.55E+02	0	3.20E+02	4.75E+02
Renewable primary resources with energy content used as material, RPRM*4)	MJ, LHV	0	0	4.04E+02	4.04E+02
Non-renewable primary resources used as an energy carrier (fuel), NRPRE ^{*4)}	MJ, LHV	2.33E+03	2.92E+01	2.41E+03	4.77E+03
Non-renewable primary resources with energy content used as material, NRPRM*4)	MJ, LHV	2.87E+01	0	9.69E+00	3.83E+01
Secondary materials, SM ^{*4)}	kg	2.88E+01	0	9.02E-03	2.88E+01
Renewable secondary fuels, RSF*4)	MJ, LHV	0	0	1.06E+01	1.06E+01
Non-renewable secondary fuels, NRSF*4)	MJ, LHV	4.75E-02	0	0	4.75E-02
Recovered energy, RE ^{*4)}	MJ, LHV	0	0	0	0
Consumption of freshwater, FW ^{*4)}	m³	6.10E-01	0	1.38E+00	1.99E+00
Hazardous waste disposed, HWD*4)	kg	3.61E-01	0	8.75E-04	3.62E-01
Non-hazardous waste disposed, NHWD*4)	kg	6.68E+00	0	3.34E+00	1.00E+01
High-level radioactive waste, conditioned, to final repository, HLRW ^{*4) 5)}	m³	5.67E-08	0	3.30E-06	3.36E-06
Intermediate- and low-level radioactive waste, conditioned, to final repository, ILLRW*4) 5)	m³	2.24E-05	0	7.68E-05	9.93E-05
Components for re-use, CRU ^{*4)}	kg	0	0	0	0
Materials for recycling, MR*4)	kg	1.44E+00	0	2.90E+01	3.04E+01
Materials for energy recovery, MER*4)	kg	0	0	0	0
Recovered energy exported from the product system, EE ^{*4)}	MJ, LHV	0	0	0	0
Removals and emissions associated with carbon content of bio-based packaging ⁴⁾	kg CO ₂	0	0	-3.30E+01	-3.30E+01





An Environmental Product Declaration In accordance with ISO 14025 and ISO 21930 AMBICO Steel Doors

Table 6 Production stage EPD Results (Total A1 to A3) – Steel Door Group 2TORST, LL2B, and STC39 to STC51

Impact category and inventory indicators	Unit	A1	A2	A3	A1-A3 Total
Global warming potential, GWP 100 ¹⁾	kg CO₂ eq	2.55E+02	2.71E+00	1.19E+02	3.76E+02
Acidification potential, AP ¹⁾	kg SO₂ eq	8.79E-01	3.20E-02	5.59E-01	1.47E+00
Eutrophication potential, EP ¹⁾	kg N eq	2.32E-01	1.92E-03	2.13E-01	4.46E-01
Smog formation potential, SFP ¹⁾	kg O₃ eq	1.02E+01	8.18E-01	5.51E+00	1.65E+01
Ozone depletion potential, ODP ¹⁾	kg CFC-11 eq	3.47E-06	1.12E-10	1.22E-06	4.69E-06
Abiotic depletion potential for non-fossil mineral resources ^{*2)}	Kg Sb eq	9.30E+01	0	9.83E-06	9.30E+01
Fossil fuel depletion, FFD ^{*1)}	MJ surplus, LHV	3.44E+01	5.65E+00	1.79E+02	2.19E+02
Abiotic depletion potential for fossil resources, ADPf* ³)	MJ, LHV	2.86E+03	3.82E+01	1.49E+03	4.39E+03
Renewable primary resources used as an energy carrier (fuel), RPRe* ⁴⁾	MJ, LHV	2.05E+02	0	3.20E+02	5.25E+02
Renewable primary resources with energy content used as material, RPRM*4)	MJ, LHV	0	0	4.04E+02	4.04E+02
Non-renewable primary resources used as an energy carrier (fuel), NRPRE ^{*4)}	MJ, LHV	3.09E+03	3.87E+01	2.41E+03	5.53E+03
Non-renewable primary resources with energy content used as material, NRPRM*4)	MJ, LHV	3.80E+01	0	9.69E+00	4.76E+01
Secondary materials, SM ^{*4)}	kg	3.82E+01	0	9.02E-03	3.82E+01
Renewable secondary fuels, RSF*4)	MJ, LHV	0	0	1.06E+01	1.06E+01
Non-renewable secondary fuels, NRSF*4)	MJ, LHV	6.29E-02	0	0	6.29E-02
Recovered energy, RE ^{*4)}	MJ, LHV	0	0	0	0
Consumption of freshwater, FW ^{*4)}	m³	8.08E-01	0	1.38E+00	2.18E+00
Hazardous waste disposed, HWD*4)	kg	4.78E-01	0	8.75E-04	4.79E-01
Non-hazardous waste disposed, NHWD*4)	kg	8.85E+00	0	3.34E+00	1.22E+01
High-level radioactive waste, conditioned, to final repository, HLRW ^{*4) 5)}	m³	7.51E-08	0	3.30E-06	3.38E-06
Intermediate- and low-level radioactive waste, conditioned, to final repository, ILLRW*4) 5)	m³	2.97E-05	0	7.68E-05	1.07E-04
Components for re-use, CRU ^{*4)}	kg	0	0	0	0
Materials for recycling, MR*4)	kg	1.91E+00	0	2.90E+01	3.09E+01
Materials for energy recovery, MER*4)	kg	0	0	0	0
Recovered energy exported from the product system, EE ^{*4)}	MJ, LHV	0	0	0	0
Removals and emissions associated with carbon content of bio-based packaging ⁴⁾	kg CO ₂	0.00E+00	0.00E+00	-3.30E+01	-3.30E+01





Table 7Production stage EPD Results (Total A1 to A3) – Steel Door Group 3BR01 to BR03, PRS5, CLBR, LL4B, and LL6B

Impact category and inventory indicators	Unit	A1	A2	Α3	A1-A3 Total
Global warming potential, GWP 100 ¹⁾	kg CO₂ eq	3.37E+02	3.58E+00	1.19E+02	4.59E+02
Acidification potential, AP ¹⁾	kg SO₂ eq	1.16E+00	4.23E-02	5.59E-01	1.76E+00
Eutrophication potential, EP ¹⁾	kg N eq	3.06E-01	2.53E-03	2.13E-01	5.21E-01
Smog formation potential, SFP ¹⁾	kg O₃ eq	1.35E+01	1.08E+00	5.51E+00	2.01E+01
Ozone depletion potential, ODP ¹⁾	kg CFC-11 eq	4.58E-06	1.49E-10	1.22E-06	5.81E-06
Abiotic depletion potential for non-fossil mineral resources ^{*2)}	Kg Sb eq	1.23E+02	0	9.83E-06	1.23E+02
Fossil fuel depletion, FFD ^{*1)}	MJ surplus, LHV	4.55E+01	7.46E+00	1.79E+02	2.32E+02
Abiotic depletion potential for fossil resources, ADPf* ³⁾	MJ, LHV	3.78E+03	5.05E+01	1.49E+03	5.32E+03
Renewable primary resources used as an energy carrier (fuel), RPRe*4)	MJ, LHV	2.72E+02	0	3.20E+02	5.92E+02
Renewable primary resources with energy content used as material, RPRM*4)	MJ, LHV	0	0	4.04E+02	4.04E+02
Non-renewable primary resources used as an energy carrier (fuel), NRPRE ^{*4)}	MJ, LHV	4.09E+03	5.11E+01	2.41E+03	6.54E+03
Non-renewable primary resources with energy content used as material, NRPRM*4)	MJ, LHV	5.02E+01	0	9.69E+00	5.99E+01
Secondary materials, SM ^{*4)}	kg	5.05E+01	0	9.02E-03	5.05E+01
Renewable secondary fuels, RSF*4)	MJ, LHV	0	0	1.06E+01	1.06E+01
Non-renewable secondary fuels, NRSF*4)	MJ, LHV	8.32E-02	0	0	8.32E-02
Recovered energy, RE*4)	MJ, LHV	0	0	0	0
Consumption of freshwater, FW ^{*4)}	m³	1.07E+00	0	1.38E+00	2.44E+00
Hazardous waste disposed, HWD*4)	kg	6.32E-01	0	8.75E-04	6.33E-01
Non-hazardous waste disposed, NHWD*4)	kg	1.17E+01	0	3.34E+00	1.50E+01
High-level radioactive waste, conditioned, to final repository, HLRW ^{*4) 5)}	m³	9.93E-08	0	3.30E-06	3.40E-06
Intermediate- and low-level radioactive waste, conditioned, to final repository, ILLRW*4) 5)	m³	3.92E-05	0	7.68E-05	1.16E-04
Components for re-use, CRU ^{*4)}	kg	0	0	0	0
Materials for recycling, MR*4)	kg	2.52E+00	0	2.90E+01	3.15E+01
Materials for energy recovery, MER*4)	kg	0	0	0	0
Recovered energy exported from the product system, EE ^{*4)}	MJ, LHV	0	0	0	0
Removals and emissions associated with carbon content of bio-based packaging ⁴⁾	kg CO ₂	0	0	-3.30E+01	-3.30E+01





Table 8 Production stage EPD Results (Total A1 to A3) – Steel Door Group 4STC52 & STC53, PRSC, BR04 & BR06, PLATE

Impact category and inventory indicators	Unit	A1	A2	Α3	A1-A3 Total
Global warming potential, GWP 100 ¹⁾	kg CO₂ eq	4.44E+02	4.72E+00	1.19E+02	5.67E+02
Acidification potential, AP ¹⁾	kg SO₂ eq	1.53E+00	5.58E-02	5.59E-01	2.15E+00
Eutrophication potential, EP ¹⁾	kg N eq	4.04E-01	3.34E-03	2.13E-01	6.19E-01
Smog formation potential, SFP ¹⁾	kg O₃ eq	1.78E+01	1.43E+00	5.51E+00	2.47E+01
Ozone depletion potential, ODP ¹⁾	kg CFC-11 eq	6.04E-06	1.96E-10	1.22E-06	7.26E-06
Abiotic depletion potential for non-fossil mineral resources ^{*2)}	Kg Sb eq	1.62E+02	0	9.83E-06	1.62E+02
Fossil fuel depletion, FFD ^{*1)}	MJ surplus, LHV	6.00E+01	9.84E+00	1.79E+02	2.49E+02
Abiotic depletion potential for fossil resources, ADPf ^{*3)}	MJ, LHV	4.98E+03	6.66E+01	1.49E+03	6.54E+03
Renewable primary resources used as an energy carrier (fuel), RPRe* ⁴⁾	MJ, LHV	3.58E+02	0	3.20E+02	6.78E+02
Renewable primary resources with energy content used as material, RPRM*4)	MJ, LHV	0	0	4.04E+02	4.04E+02
Non-renewable primary resources used as an energy carrier (fuel), NRPRE*4)	MJ, LHV	5.38E+03	6.73E+01	2.41E+03	7.86E+03
Non-renewable primary resources with energy content used as material, NRPRM*4)	MJ, LHV	6.61E+01	0	9.69E+00	7.58E+01
Secondary materials, SM ^{*4)}	kg	6.65E+01	0	9.02E-03	6.65E+01
Renewable secondary fuels, RSF*4)	MJ, LHV	0	0	1.06E+01	1.06E+01
Non-renewable secondary fuels, NRSF*4)	MJ, LHV	1.10E-01	0	0	1.10E-01
Recovered energy, RE ^{*4)}	MJ, LHV	0	0	0	0
Consumption of freshwater, FW ^{*4)}	m³	1.41E+00	0	1.38E+00	2.78E+00
Hazardous waste disposed, HWD*4)	kg	8.32E-01	0	8.75E-04	8.33E-01
Non-hazardous waste disposed, NHWD*4)	kg	1.54E+01	0	3.34E+00	1.88E+01
High-level radioactive waste, conditioned, to final repository, HLRW ^{*4) 5)}	m³	1.31E-07	0	3.30E-06	3.43E-06
Intermediate- and low-level radioactive waste, conditioned, to final repository, ILLRW*4) 5)	m³	5.17E-05	0	7.68E-05	1.29E-04
Components for re-use, CRU*4)	kg	0	0	0	0
Materials for recycling, MR*4)	kg	3.32E+00	0	2.90E+01	3.23E+01
Materials for energy recovery, MER*4)	kg	0	0	0	0
Recovered energy exported from the product system, EE ^{*4)}	MJ, LHV	0	0	0	0
Removals and emissions associated with carbon content of bio-based packaging ⁴⁾	kg CO ₂	0	0	-3.30E+01	-3.30E+01





Table 9 Production stage EPD Results (Total A1 to A3) – Steel Door Group 5STC54 to STC59, BR05, BR07, and BR08

Impact category and inventory indicators	Unit	A1	A2	Α3	A1-A3 Total
Global warming potential, GWP 100 ¹⁾	kg CO₂ eq	6.29E+02	6.69E+00	1.19E+02	7.54E+02
Acidification potential, AP ¹⁾	kg SO₂ eq	2.17E+00	7.90E-02	5.59E-01	2.81E+00
Eutrophication potential, EP ¹⁾	kg N eq	5.72E-01	4.73E-03	2.13E-01	7.89E-01
Smog formation potential, SFP ¹⁾	kg O₃ eq	2.52E+01	2.02E+00	5.51E+00	3.27E+01
Ozone depletion potential, ODP ¹⁾	kg CFC-11 eq	8.56E-06	2.77E-10	1.22E-06	9.78E-06
Abiotic depletion potential for non-fossil mineral resources ^{*2)}	Kg Sb eq	2.30E+02	0	9.83E-06	2.30E+02
Fossil fuel depletion, FFD ^{*1)}	MJ surplus, LHV	8.50E+01	1.39E+01	1.79E+02	2.78E+02
Abiotic depletion potential for fossil resources, ADPf* ³⁾	MJ, LHV	7.06E+03	9.43E+01	1.49E+03	8.64E+03
Renewable primary resources used as an energy carrier (fuel), RPRe* ⁴⁾	MJ, LHV	5.07E+02	0	3.20E+02	8.27E+02
Renewable primary resources with energy content used as material, RPRM*4)	MJ, LHV	0	0	4.04E+02	4.04E+02
Non-renewable primary resources used as an energy carrier (fuel), NRPRE ^{*4)}	MJ, LHV	7.63E+03	9.54E+01	2.41E+03	1.01E+04
Non-renewable primary resources with energy content used as material, NRPRM*4)	MJ, LHV	9.37E+01	0	9.69E+00	1.03E+02
Secondary materials, SM ^{*4)}	kg	9.42E+01	0	9.02E-03	9.42E+01
Renewable secondary fuels, RSF*4)	MJ, LHV	0	0	1.06E+01	1.06E+01
Non-renewable secondary fuels, NRSF*4)	MJ, LHV	1.55E-01	0	0	1.55E-01
Recovered energy, RE ^{*4)}	MJ, LHV	0	0	0	0
Consumption of freshwater, FW ^{*4)}	m³	1.99E+00	0	1.38E+00	3.37E+00
Hazardous waste disposed, HWD*4)	kg	1.18E+00	0	8.75E-04	1.18E+00
Non-hazardous waste disposed, NHWD*4)	kg	2.19E+01	0	3.34E+00	2.52E+01
High-level radioactive waste, conditioned, to final repository, HLRW ^{*4) 5)}	m³	1.85E-07	0	3.30E-06	3.49E-06
Intermediate- and low-level radioactive waste, conditioned, to final repository, ILLRW*4) 5)	m³	7.32E-05	0	7.68E-05	1.50E-04
Components for re-use, CRU ^{*4)}	kg	0	0	0	0
Materials for recycling, MR*4)	kg	4.70E+00	0	2.90E+01	3.37E+01
Materials for energy recovery, MER*4)	kg	0	0	0	0
Recovered energy exported from the product system, EE ^{*4)}	MJ, LHV	0	0	0	0
Removals and emissions associated with carbon content of bio-based packaging ⁴⁾	kg CO ₂	0	0	-3.30E+01	-3.30E+01





Notes:

¹⁾ Calculated as per U.S EPA TRACI 2.1, v1.05, SimaPro v.9.5.0.2 GWP-100 (9), excludes biogenic CO_2 removals and emissions associated with biobased products, including bio-based packaging. Biogenic carbon content of packaging materials is reported separately. CO_2 emissions from calcination and carbonation do not apply to the declared products; 100-year time horizon GWP factors are provided by the IPCC 2013 Fifth Assessment Report (AR5), TRACI 2.1, v1.05 (10). FFD is required in LEED V4.1 MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations (11).

²⁾ Calculated as per CML-IA Baseline v3.05, SimaPro v.9.5.0.2 (9).

³⁾ Calculated as per CML-IA baseline, V4.7, SimaPro v.9.5.0.2. ADP_f is also required in LEED v4.0/v4.1 MR2 Credit: Building Product Disclosure and Optimization – Environmental Product Declarations (12), (11).

⁴⁾ Calculated as per ACLCA ISO 21930 Guidance (13).

⁵⁾ It should be noted that the foreground system (A3 manufacturing process) does not generate any high-level radioactive waste or low/intermediate level radioactive waste. Radioactive waste is primarily generated from electricity production. High level radioactive waste consists mainly of spent fuel from reactors. Low/intermediate level radioactive waste is primarily generated from routine facility maintenance and operation (2).

7 INTERPRETATION

AMBICO's EPD results for steel doors represent a "cradle-to-gate" environmental profile for one commercial steel door with nominal dimensions of 3-feet by 7-feet. As outlined in the UL PCR, a scaling factor of 0.0476 can be used to translate results per declared unit to square foot (6).

A1 – Material Extraction and Upstream Production is the primary contributor to the environmental impact of AMBICO's steel doors, contributing 25% to 66% of the overall potential environmental impact, depending on the impact category. The A1 impacts are primarily dominated by the galvannealed steel material input.

A3 – Manufacturing also contributes significantly to the potential environmental impact, accounting for 40% to 75% of the overall environmental impact, depending on the impact category. The A3 impacts are primarily dominated by natural gas used for heating the manufacturing facility and the use of welding gasses during manufacturing.

A2 – Transportation typically does not significantly contribute to the potential environmental impact of AMBICO's steel doors.

8 DECLARATION TYPE

This cradle-to-gate EPD applies to steel doors manufactured at AMBICO's facility in Ottawa, Ontario. Production activities covered include the *Extraction and Upstream Production (A1), Transport to Factory (A2),* and *Manufacturing (A3)* modules. This declaration is intended for Business-to-Business (B-to-B) communications.

This EPD covering AMBICO's steel doors falls under the description:

- An average product EPD, from a single manufacturing facility.





9 EPD COMPARABILITY LIMITATION STATEMENT

As specified in the UL PCR Part A (5), the following points apply to the comparability of Environmental Declarations:

- Environmental declarations from different programs may not be comparable.
- Comparison of the environmental performance of construction works and construction products using EPD information shall be based on the product's use and impacts at the construction works level. In General, EPDs may not be used for comparability purposes when not considered in a construction works context. Given this PCR ensures products meet the same functional requirements, comparability is permissible provided the information given for such comparison is transparent and the limitations of comparability explained (5).
- When comparing EPDs created using this PCR, variations and deviations are possible. Example of potential variations include different LCA software and background LCI datasets which may lead to different results for upstream or downstream of the life cycle stages declared (5).





10 REFERENCES

1. ISO 14025: 2006 Environmental labeling and declarations - Type III environmental declarations - Principles and procedures.

2. ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products and services.

3. ISO 14040/Amd1:2020 Environmental Management – Life Cycle Assessment – Principles and Framework, International Organization for Standardization.

4. ISO 14044/Amd1:2017/Amd2:2020 Environmental Management – Life Cycle Assessment – Requirements and guidelines, International Organization for Standardization.

5. UL Environment. Product Category Rules for Building-Related Products and Services. Part A: Life Cycle Assessment Calculation Rules and Report Requirements. Version 4.0. March 2022.

6. UL Environment. Product Category Rules (PCR) for Building-Related Products and Services. Part B: Commercial Steel Doors and Steel Frames EPD Requirements. Version 2.0. September 2020.

7. ASTM Program Operator for Product Category Rules (PCRs) and Environmental Product Declarations (EPDs), General Program Instructions, April 2020.

8. Athena Sustainable Materials Institute, A Cradle-to-Gate Life Cycle Assessment of Steel Frames, Steel Doors, and Wood Doors Manufactured by Ambico Ltd., November 2024.

9. PRé 2021.SimaPro LCA Software v 9.5, 2024, https://simapro.com/.

10. Bare, J., TRACI 2.0: The Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts 2.0. Clean Technologies and Environmental Policy 2011, 13, (5), *https://link.springer.com/article/10.1007/s10098-010-0338-9#page-1*.

11. LEED v4.1, MRc2: Building product disclosure and optimization, Environmental Product Declarations,. https://leeduser.buildinggreen.com/credit/NC-v4.1/MRc2#tab-credit-language.

12. LEED v4, MRc2: Building product disclosure and optimization, Environmental Product Declarations, *https://leeduser.buildinggreen.com/credit/NC-v4/MRc2#tab-credit-language*.

13. ACLCA 2019, Guidance to Calculating Non-LCIA Inventory Metrics in Accordance with ISO 21930:2017. The American Centre for Life Cycle Assessment. May, 2019.

