



Environmental Product Declaration



WEATHERBOND
ROOFING SYSTEMS

Single-Ply Simplified

Polyiso Roof Insulation Boards

GENERAL INFORMATION

EPD Program Operator	ASTM International 100 Barr Harbor Drive, PO Box C700 West Conshohocken, PA 19428-2959, USA www.astm.org
Reference PCRs	Product Category Rules for Building-Related Products and Services Part A: Life Cycle Assessment Calculation Rules and Report Requirements (UL 10010, Version 3.2), and Product Category Rule (PCR) Guidance for Building-Related Products and Services Part B: Building Thermal Insulation EPD Requirements (UL10010-1, Version 2.0), and ISO 21930: 2017
Declaration Holder	Weatherbond Roofing Systems P.O Box 251 Plainfield, PA 17081 USA https://www.weatherbondroofing.com/ For more information, please contact: Insulation Product Manager Carlisle Construction Materials 1-800-453-2554
LCA & Declaration Preparer	Shelly Severinghaus, LCACP Long Trail Sustainability 830 Taft Road Huntington, Vermont, 05462, USA www.ltsexperts.com
Declaration Number	EPD 272
Product	Polyisocyanurate Roof Insulation Boards
Intended Applications and Use	Commercial, light commercial, residential and industrial roof construction
Markets of Applicability	United States and Canada
Product RSL Description	40 years
Declared Product & Function Unit	1 m ² of installed insulation material with a thickness that gives an average thermal resistance $R_{SI} = 1 \text{ m}^2 \cdot \text{K/W}$ (5.678 ft ² ·°F·h/Btu) and with a building service life of 75 years (packaging included)
PCR Review was Conducted by:	- Part A - UL Technical Advisory Panel - Part B - Thomas Gloria, PhD (chair)
Date of Issue	November 12, 2021

Polyiso Roof Insulation Boards

Period of Validity	5 years from date of issue
EPD Type	Manufacturer-specific average
EPD Scope	Cradle-to-grave
Range of Dataset Variability	Manufacturer-specific average
Year(s) of Reported Manufacturer Primary Data	2017
LCA Completion	Life Cycle Assessment of Rigid Polyisocyanurate Foam Board Insulation, July 2021
LCA Software & Version Number	SimaPro (Version 9.0.0.35)
LCI Databases & Version Number	ecoinvent v3.5, Cut-off at Classification (ecoinvent centre, 2018), US LCI (NREL, 2015) and DATASmart v2018.1 (Long Trail Sustainability, 2018)
LCIA Methodology & Version Number	TRACI 2.1 version 1.05
This EPD was independently verified by ASTM in accordance with ISO 14025: 2006 and ISO 21930:2017: Internal x ☒ External	Terrie Boguski, P.E. – Harmony Environmental  tboguski@harmonyenviro.com
This life cycle assessment was conducted in accordance with ISO 14044: 2006, reference PCR, and ISO 21930: 2017	Shelly Severinghaus, LCACP – Long Trail Sustainability  shelly@ltsexperts.com
This life cycle assessment was independently verified in accordance with ISO 14044: 2006 and the reference PCR by:	Terrie Boguski, P.E. – Harmony Environmental  tboguski@harmonyenviro.com
Limitations: Environmental declarations from different programs (ISO 14025) based upon different PCRs may not be comparable. Comparison of the environmental performance of Building Envelope Thermal Insulation using EPD information shall be based on the product's use and impacts at the building level, and therefore EPDs may not be used for comparability purposes when not considering the building energy use phase as instructed under this PCR. Full conformance with the PCR for Building Envelope Thermal Insulation allows EPD comparability only when all stages of a life cycle have been considered, when they comply with all referenced standards, use the same sub-category PCR, and use equivalent scenarios with respect to construction works. However, variations and deviations are possible. When comparing EPDs created using this PCR, variations and deviations are possible. Examples of variations include different LCA software and background LCI datasets that may lead to different results for upstream or downstream segments of the life cycle stages declared.	

Polyiso Roof Insulation Boards

EPD SUMMARY

This declaration is a manufacturer-specific average, Type III Environmental Product Declaration (EPD) by Weatherbond Roofing Systems conducted in accordance with ISO 14025. Weatherbond has polyiso facilities in Montgomery, New York, Smithfield, Pennsylvania, Franklin Park, Illinois, Lake City, Florida, Terrell, Texas, Tooele, Utah, and Puyallup, Washington. Each facility's annual electricity use, natural gas use, water use and wastewater, product packaging, and solid waste data were divided by its annual production in board-feet (BF). Facility details such as location (to specify grid mix) and facility emissions handling were also included in the calculation. Finally, a production-weighted average across all manufacturing facilities was created to represent the manufacturing of polyiso roof insulation boards.

This document is based on the Life Cycle Assessment (LCA) study developed for Weatherbond by Long Trail Sustainability in accordance with industry accepted standards: Product Category Rules for Building-Related Products and Services Part A: Life Cycle Assessment Calculation Rules and Report Requirements (UL 10010, Version 3.2), and Product Category Rule (PCR) Guidance for Building-Related Products and Services Part B: Building Thermal Insulation EPD Requirements (UL10010-1, Version 2.0), ISO 14040, ISO 14044 and ISO 21930. This EPD provides users with information on environmental impacts of polyiso roof insulation boards during their life cycle.

LIFE CYCLE ASSESSMENT SCOPE AND BOUNDARIES

System Boundary: Cradle-to-Grave.

This declaration is a cradle-to-grave and the following life cycle stages are included as part of the system boundary: production, construction, use, and end-of-life. Each life cycle stage includes the following modules:

Production Stage

- **Supply of raw materials (A1):** Extraction, upstream processing and production of raw materials and energy associated with the production of polyiso roof insulation boards.
- **Transport of raw materials (A2):** Transport of materials (all chemical and material inputs including packaging) to polyiso roof insulation boards manufacturing facilities.
- **Manufacturing of products (A3):** Production of polyiso roof insulation boards (including associated emissions from production facilities).

Construction Stage

- **Transport from gate to site (A4):** Transport of polyiso roof insulation boards in bundles from the manufacturing facilities to product distributor sites or directly to project job sites.
- **Assembly/Install (A5):** Installation of polyiso roof insulation boards including: unloading from the truck by all terrain forklift to a staging area on a job site prior to moving bundles onto rooftop using crane, removal of all protective packaging, placement and attachment of individual roof insulation boards by a roofing crew, and removal and transport of installation waste scrap to a local landfill for disposal.

Polyiso Roof Insulation Boards

Use Stage

- **Use (B1):** Upon installation the product remains in place in the roof assembly and provides resistance to transfer of energy in and out of the building. There is no activity associated during the use of polyiso roof insulation boards.
- **Maintenance (B2):** Polyiso roof insulation boards are installed permanently within a weather protected exterior building envelope and therefore no maintenance is required to retain the functional performance of the product.
- **Repair (B3):** When the weather protection components of the building envelope are designed and installed properly and adequately maintained, it is reasonable to expect that the polyiso roof insulation boards will not incur damage affecting its performance. Therefore, repair activity is not required.
- **Replacement (B4):** The building service life as defined in the PCR is 75 years, and as rationalized in the reference service life one replacement is required.
- **Refurbishment (B5):** Polyiso roof insulation boards require no refurbishment activity.
- **Operational Energy Use of Building Integrated System During Product Use (B6) and Operational Water Use of Building Integrated System During Product Use (B7):** Polyiso roof insulation boards are not integrated technical systems and have no declared activity in either of the modules.

End-of-Life Stage

- **Deconstruction (C1):** At the end-of-life, the polyiso roof insulation boards are removed from the roof deck. Although, the polyiso roof insulation boards may be recovered from the roof system and reused, this activity is not considered in this study.
- **Transport (C2):** Transport of polyiso roof insulation boards to a landfill.
- **Waste Processing (C3):** Polyiso roof insulation boards do not require waste processing.
- **Disposal (C4):** Disposal of polyiso roof insulation boards in a landfill.

Geographic Coverage: Polyiso roof insulation boards manufactured in the United States.

Allocation Method: Mass allocation method was used to allocate input/output for sub-processes involving co-products. No allocation was necessary in the manufacturing of facers and polyiso foam that comprise roof insulation board products because there are no co-products for these materials. The allocations are already applied to the secondary data (i.e.,ecoinvent data) included in this study (ecoinvent center, 2019).

Polyiso Roof Insulation Boards

PRODUCT DESCRIPTION

Polyisocyanurate (Polyiso) is a cellular closed-cell rigid foam plastic insulation. Polyiso roof insulation boards consist of a foam core sandwiched between two facers (top and bottom). The foam core is comprised of a thermoset polymer that hardens by curing from a viscous liquid prepolymer. The rigid foam is produced through the reaction of methylene diphenylene diisocyanate (MDI) with polyester polyol. Other additives such as catalyst, surfactant, flame retardant, and blowing agent (pentane or pentane blends) are part of the formulation. Pentane is a hydrocarbon with negligible ozone depletion potential (ODP) (U.S. EPA, 2018) and low global warming potential (GWP) (U.S. EPA, 2020). For nearly 20 years, the polyiso industry has only utilized pentane or pentane blends in product formulations. Upon mixing of the components, the viscous pre-polymer is laid between the facers, and a chemical reaction cross-links polymer chains creating a rigid and durable cellular structure. For roofing applications, the most common facer is a glass fiber reinforced cellulosic facer (GRF) produced predominantly from recycled post-consumer and/or post-industrial fibers. Polyiso roof insulation is also manufactured with polymer-bonded coated glass facer (CGF), consisting of a glass fiber mat coated with polymers. Both facer types play a critical role in accommodating a continuous manufacturing process.

Features and Benefits

The versatile, durable and sustainable polyiso roof insulation boards offer the following benefits:

- *High thermal resistance*
- *Continuous thermal insulation*
- *Condensation control*
- *Direct-to-steel deck application without thermal barrier*
- *Improved water management (tapered products)*
- *Compatibility with roof system adhesives*
- *Resistance to construction traffic*
- *Lightweight and easy to install*

Polyiso Roof Insulation Boards



Figure 1: Polyiso Roof Insulation Board with GRF Facer.



Figure 2: Polyiso Roof Insulation Board with CGF Facer.

Polyiso Roof Insulation Boards

APPLICATION

Polyiso roof insulation boards may be used in residential, light commercial, commercial, and industrial roof construction projects on new buildings and on existing buildings during reroofing. Polyiso is the most widely used type of insulation in above-deck commercial roof applications in the United States and Canada. In commercial roof systems, one or more layers of polyiso are installed (with board joints staggered) direct-to-deck (i.e., steel, concrete, or wood) and below the membrane to provide continuous insulation. On low-slope roof applications, Polyiso can be installed as a flat stock or as tapered product to provide improved slope and more effectively manage drainage of rainwater. Polyiso may be attached to the roof deck using mechanical fasteners or adhesives to achieve the desired system performance. Polyiso is a versatile insulation, and it is compatible with all low-slope roof covering types including: single-ply membranes systems (i.e., TPO, PVC and EPDM), modified bitumen system, built-up roofing, standing-seam metal roofing and metal panels. The roof systems may be mechanically attached through the Polyiso insulation, adhered to the Polyiso facer or held in place with ballast. A typical roof system with a metal deck is illustrated below. Many factors and design consideration impact the selection of a roof system, and additional components such as air barrier, vapor retarder, thermal barrier and cover board may be required in specific applications. Polyiso insulation may be installed in direct-to-deck applications without a thermal or ignition barrier. On steep-slope roof applications, Polyiso can be used as a part of vented nail base system below asphalt, composite and metal shingles and metal panels.



Figure 3: Typical Roof Assembly with Polyiso Roof Insulation Boards Installed Direct-to-Steel Deck.

TECHNICAL REQUIREMENTS

Polyiso roof insulation boards are manufactured to meet the requirements of industry consensus product specifications and standards in the United States and Canada. Compliance with model building codes does not always ensure compliance with state or local building codes, which may be amended versions of these model codes. Always check with local building code officials to confirm compliance. Typical physical properties for Polyiso roof insulation boards are listed in Table 1.

- ❑ ASTM C1289 – Standard Specification for Faced Rigid Cellular Polyisocyanurate Thermal Insulation.
- ❑ CAN/ULC-S704.1 – Standard for Thermal Insulation, Polyurethane and Polyisocyanurate, Boards, Faced.
- ❑ CSI and CSA MasterFormat® Reference: 072200 Roof and Deck Insulation.

Polyiso Roof Insulation Boards

Table 1: Typical Physical Properties of Polyiso Roof Insulation Boards and Corresponding Requirements Listed in ASTM C1289 and CAN/ULC-S704.1 Standards.

PHYSICAL PROPERTY	STANDARD DESIGNATION	ASTM C1289 (TYPE II, CLASS 1 & 2)	CAN/ULC S704.1 (TYPE 4, 5 & 6)
Thermal Resistance (R-value or long-term thermal resistance), °F·ft ² ·h/Btu (K·m ² /W), min	→	Class 1 Class 2 For 1.0-inch (25.4 mm): 5.6 (0.97) 5.3 (0.93) For 1.5-inch (25.4 mm): 8.4 (1.48) 8.0 (1.41) For 2.0-inch (25.4 mm): 11.2(1.97) 10.6(1.87) measured per ASTM C518 at 75°F (24°C) after 180 conditioning period	10.22 (1.80) for 1.97-inch (50-mm) thick board measured per CAN/ULC-S770 long-term thermal resistance
Compressive Strength, psi (kPa), min	ASTM D1621	16 (110)	16 (110)
Flexural Strength, psi (kPa), min	ASTM C203	40 (275)	24.7 (170)
Tensile Strength, psf (kPa), min	→	500 (24) measured per ASTM C209	500 (24) measured per ASTM D1623
Dimensional Stability, % Linear Change, Thickness, Max	ASTM D2126	-40°F (-40°C) / ambient RH: 4.0 158°F (70°C) / 97% RH: 4.0 200°F (93°C) / ambient RH: 4.0	Not Applicable
Dimensional Stability, % Linear Change, Length and Width, max	ASTM D2126	-40°F (-40°C) / ambient RH: 2.0 158°F (70°C) / 97% RH: 2.0 200°F (93°C) / ambient RH: 2.0	-20°F (-29°C) / ambient RH: 2.0 158°F (70°C) / 97% RH: 2.0 176°F (80°C) / ambient RH: 2.0
Water Absorption, % by Volume, max	→	1.0 measured per ASTM C1763 – Procedure B	3.5 measured per ASTM D2842 – Procedure B
Water Vapor Permeance, perm (ng/Pa·s·m ²)	ASTM E96/E96M Desiccant Method	Class 1: ≤1.5 (≤85.8) Class 2: ≤4.0 (≤228.8)	Class 1: ≤0.26 (≤15) Class 2: ≥0.26, ≤1.05 (≥15, ≤60) Class 3: > 1.05 (>60)

Thermal Performance: The recognized consensus approach for determining the thermal resistance of permeably-faced closed-cell foam insulation with captive blowing agents such as polyiso relies on the concept of Long-Term Thermal Resistance (LTTR) as described in CAN/ULC-S770 “Standard Test Method for Determination of Long-Term Thermal Resistance of Closed-Cell Thermal Insulating Foams” and ASTM C1303/C1303M “Standard Test Method for Predicting Long-Term Thermal Resistance of Closed-Cell Foam Insulation.” LTTR provides a laboratory method of accelerating the aging of closed-cell thermal insulation products with captive blowing agents to estimate the long-term aged thermal resistance. This approach is based on a scientific theory of aging plastic foams with captive blowing agents developed in the 1990s and a robust evaluation of the methodology spearheaded by Oak Ridge National Laboratory (Stovall T., et. al., 2012). The polyiso industry has adopted the LTTR methodology for quantifying thermal resistance of permeably-faced polyiso roof insulation boards. Additional information regarding LTTR methodology is available on the PIMA website (www.polyiso.org).

Polyiso Roof Insulation Boards

PROPERTIES OF DECLARED PRODUCT AS DELIVERED

The manufactured and cured Polyiso roof insulation boards are typically shipped and delivered to jobsites stacked in bundles protected by a plastic wrap, plastic bag or both. The boards are typically 1.2 m by 2.4 m (4 feet by 8 feet) in size and stacked one on top of another to form a bundle. The number of Polyiso boards in a bundle will vary depending on product thickness. Typically, the bundles are 1.2 m (48-inches) in height. For example, twice the number of 2.54 cm (1.0-inch-thick) boards can be stacked to make up the same height bundle compared to 5.08 cm (2.0-inch-thick) insulation boards. Typically, 48 boards at 2.54 cm (1.0-inch-thick), 24 boards at 5.08 cm (2.0-inch-thick) or 16 boards at 7.62 cm (3.0-inch-thick) comprise a bundle of Polyiso roof insulation.

MATERIAL COMPOSITION

Polyiso roof insulation boards are comprised of a foam core and two facers on the top and bottom surfaces. The foam core consists of the average weighted formulation by mass listed in Table 2. More than half of the foam formulation consists of MDI which reacts with polyester polyol containing other chemicals including blowing agent, flame retardant, surfactant, catalyst and water. The chemical reaction forms a rigid cellular foam structure following a curing process. The two most common types of facers in Polyiso roof insulation and used in this study are; (1) glass fiber reinforced cellulosic facer (GRF) and (2) coated polymer-bonded glass fiber (CGF). The GRF is comprised of a cellulosic fiber felt containing glass fiber for added strength. The CGF facer is composed of a glass fiber mat bonded with organic polymer binder and coated with polymer coatings.

Table 2: Weighted Average Foam Formulation for Polyiso Roof Insulation Boards.

COMPONENT	FORMULATION RANGE (% by Mass)
MDI	55.8% - 56.8%
Polyester Polyol	30.3% - 31.6%
Blowing Agent (Pentane)	7.2%
Flame Retardant (TCPP)	3.1% - 3.2%
Surfactant	0.5%
Catalyst	1.7% - 2.0%
Water	0.0% - 0.1%

Note: Percentages may not total 100 due to rounding.

Polyiso Roof Insulation Boards

MANUFACTURING

This module includes manufacturing of polyiso roof insulation boards, packaging, manufacturing waste, and associated releases to the air, soil, ground, and surface water. The raw materials transported to the polyiso manufacturing plant consist of chemical liquids stored in onsite tanks or totes. The chemicals for the “A” side (MDI), the “B” side (polyester polyol plus catalyst, surfactant, and flame retardant) and the blowing agent (pentane) are pumped from storage into process tanks. The “B” side and blowing agent are then pumped to a mixer and then to a mix head where they are combined with the “A” side and injected between the top and bottom facers on the pour table. The mixed chemicals react rapidly to form a closed-cell foam board with a foam core sandwiched between the top and bottom facers. The rigid foam board moves through a heated laminator, which controls thickness and aids in cell formation, curing, and facer adhesion. The board exits the laminator and is fed through saws that trim the board to the desired width and then through a cross-cut saw that cuts the board to the desired lengths. The finished rigid boards are then stacked, packaged with plastic wrap, labeled, and moved via fork lift to a warehouse area for storage and eventual loading onto trucks for shipment. The manufacturing process for polyiso roof insulation boards at a typical manufacturing plant is illustrated in Figure 2. Bundles of polyiso roof insulation boards are wrapped and/or bagged in plastic prior to shipment from the manufacturing facility. Packaging used to wrap/shroud bundles is made from extruded low-density polyethylene (LDPE) film. Data was collected directly from each facility participating in this study on the wrap factor basis (pound of wrap per board foot). (*Note: Board foot is a unit of measure for the volume of material in the United States and Canada. It is the volume of: 1-foot (30.48 cm) length, 1-foot (30.48 cm) width and 1.0-inch (2.54 cm) thickness.*)




Figure 4: Process Flow Diagram for Polyiso Roof Insulation Boards.

(Note: Weatherbond has four out of seven of its polyiso manufacturing facilities operating with thermal oxidizers for emissions control of pentane.)

Polyiso Roof Insulation Boards

TRANSPORTATION

The polyiso roof insulation boards are transported in wrapped bundles from the manufacturing facilities to product distributor sites or directly to project job sites by a diesel-powered truck with a flatbed trailer. The average transport distance from production facility is 687 km (427 miles). Additional transportation details are reported in Table 3.

PRODUCT INSTALLATION

Upon delivery to the jobsite, the bundles of polyiso roof insulation boards are unloaded from the truck to the rooftop using a crane or all terrain forklift, all packaging is removed, assumed to be landfilled, and the individual boards are placed on the roof deck by a roofing crew. The boards are secured to the insulation or roof deck prior to the installation of the roofing membrane. The waste scrap from installation is collected and transported to a local landfill for disposal. Disposal of installation waste scrap to a local landfill was modeled as 1% of the board foot. Additional installation details are reported in Table 4.

USE & REFERENCE SERVICE LIFE

The use phase follows the installation of polyiso roof insulation boards. In a roofing system, the insulation is located on top of a roof deck and below the roof membrane. The roof membrane when installed properly and adequately maintained, protects the insulation from the environmental elements, and weather during its use. Therefore, it is expected that Polyiso will not sustain damage that affects its performance and function and does not require maintenance. As defined in the governing PCR, the Building Estimated Service Life (ESL) is 75 years. The necessary steps for providing weather protection are specified by manufacturer installation instructions and are mandated by model building codes. The roof membrane's useful life span is influenced by many variables including roof system design, quality of the installation, type and durability of the membrane, roof system component configuration and maintenance as well as weather conditions and events. Assuming that variables are sufficiently addressed through the membrane and the roof system design and installation, the insulation will serve its functional purpose for the 75-year life span of the building. However, the real-world reroofing scenarios, building owner tendencies, and the expected service life of roof membranes all indicate that reroofing activity will take place during the 75-year building ESL.

Reroofing activity may initially occur at 15-30 years after the installation of the original system and be driven by recurring roof leaks that cannot be remedied by patch repairs of the membrane. When reroofing is required, options are available to address the need for a new roof membrane without the need to replace the insulation. The model building codes, describe a "Roof Recover" as an acceptable reroofing practice, which occurs when a new roof covering is installed on top of the existing roof system without disturbing or removing the existing roof covering or the insulation below. Roof Recover, as defined by industry practices involves visual examination and appropriate testing to ensure that all roof components, including insulation, have not sustained damage or deterioration. This approach allows the insulation to be reused instead of being disposed of into a landfill. The "Roof Recover" approach is a common practice in the roofing industry, it is permitted by model building codes, and allows the service life of a roof system to be extended (without the need to replace the insulation). Although, Roof Recover approach is a common practice, it is often not captured in reroofing studies available in the public domain, which typically contemplate full roof replacement. Pertinent to this declaration, Weatherbond recognizes a 20-year life span for the original installation of the membrane followed by a "Roof Recover", which extends the life of the original roof system to 40 years. This practice establishes a 40-year RSL for Polyiso roof insulation boards. The model building codes allow a roof to be recovered only once. Where two roof membranes are installed on an existing roof, a reroofing process referred to as a "Roof Replacement" is required. This process involves the removal of all roof components

Polyiso Roof Insulation Boards

down to the roof deck. Depending on the condition of the insulation or cover board, these materials can be reused on site, resold on secondary markets or landfilled. Typically, roof demolition is preferred to alleviate the labor required to separate materials for reuse. Therefore, this study conservatively assumes all insulation is disposed in the landfill during Roof Replacement. Therefore, the Polyiso roof insulation boards cradle-to-grave assessments incorporate all life cycle stage environmental impacts connected with the original building construction with a “Roof Recover” operation at 20-years as well as the building’s “Roof Replacement” operation at 40-years. This translates to 1.9 replacement cycles during the 75-year building ESL (75-year ESL/40-year RSL = 1.9 replacement cycle).

END OF LIFE

At the end of building service life and during roof replacement, the polyiso roof insulation boards are disposed in a landfill. At the time of building deconstruction, polyiso roof insulation boards are removed manually or by cranes and transported 32 km (20 miles) to landfill sites by truck for disposal (Pavlovich, 2011). A United States specific dataset for landfilling plastic waste was used in this analysis.

CUT-OFF RULES

The cut-off criteria used for material and energy flows in this study ensures that all relevant environmental impacts are represented. In accordance with ISO 21930 Section 7.1.8 – “Criteria for the inclusion and exclusion of inputs and outputs,” the cut-off rules applied in this study are described by the following [paraphrased]:

- All inputs and outputs to a (unit) process [are] included in the calculation...for which data is available.
- Data gaps [are] filled by worst-case estimates with proxy data [as is the case for catalysts]. [The] assumptions for such choices [are] documented.
- [All known material and energy flows are reported; no known flows are deliberately excluded.]
- Particular care [is] taken to include material and energy flows [known to contribute emissions into air, water or soil related to the environmental indicators of this standard]. [Conservative assumptions in combination with plausibility considerations and expert judgement can be used to demonstrate compliance with these criteria].

A 1% mass cut-off of the mass composition of the weighted average products were used to calculate renewable and non-renewable primary resources with energy content used as material inventory metrics. No known flows are deliberately excluded from this EPD.

DATA SOURCES

This study uses a combination of primary and secondary data. The primary data was collected from manufacturers and specific facilities for production of polyester polyol, GRF and CGF facers, and polyiso roof insulation boards. In instances when the primary data is not available, ecoinvent v3.5, Cut-off at Classification (ecoinvent centre, 2018), US LCI (NREL, 2015) and DATASMART v2018.1 (Long Trail Sustainability, 2018), which contain detailed peer reviewed LCI data were used.

Polyiso Roof Insulation Boards

DATA QUALITY

The quality of the data is representative of the processes modeled as the primary data comes from day-to-day production of polyiso roof insulation boards. Additional information regarding time, geographic and technology coverage is provided below:

TIME COVERAGE: Primary data for production of polyester polyol, facers, and Polyiso roof insulation boards (including energy, water and raw material inputs, transportation distances and modes for raw materials, direct emissions, wastewater and manufacturing scrap), was collected in 2018 for the reference year 2017.

GEOGRAPHIC COVERAGE: The geographic coverage of this study includes manufacturing, distribution and installation in the United States and Canada.

TECHNOLOGY COVERAGE: The process technology modeled is based on Polyiso manufacturers, polyester polyol manufacturers, and facer manufacturers representing production in United States and Canada. Primary data was collected for production of polyester polyols, GRF and CGF facers, and manufacturing of Polyiso roof insulation boards (including energy, water and raw material inputs, transportation distances and modes for raw materials, direct emissions, wastewater and manufacturing waste).

PERIOD UNDER REVIEW

The primary data collected and used in this study represents the manufacture of polyester polyols, GRF and CGF facers, and polyiso roof insulation boards during the 2017 calendar year.

ESTIMATES AND ASSUMPTIONS

The material and energy inputs for production of polyiso roof insulation boards were modeled with data collected from the Weatherbond's seven manufacturing facilities in the United States. MDI was used to model catalyst impacts and is a worst-case estimate. The amount of MDI used to approximate each catalyst is doubled; 1 kg of catalyst is modeled with 2 kg of MDI as a proxy. The disposal of installation waste scrap sent to the landfill was assumed to be 1% of board foot. The impacts associated with installing and removing boards on building roofs were estimated using data collected from a previous LCA project, as the installation methods have not changed (Pavlovich, et. al., 2011), and are described in greater detail in the LCA report. At the end of service life, the transport distance to the landfill for disposed roof insulation boards is estimated at 32 km (20 miles).

Polyiso Roof Insulation Boards

LCA SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

The following technical information was considered in the life cycle assessment.

Table 3: Transport to building site details (A4).

Name	Value	Unit
Fuel Type	Diesel	
Vehicle Type	Unspecified freight lorry	
Transport distance*	687	km
Weight of products transported	Dependent on product	
Volume of products transported	Dependent on product	
*Data on average transportation distance to building site was collected from each polyiso manufacturing facility.		
NOTE: Liters of fuel, capacity utilization, gross density of products transported and capacity utilization volume factor determined by the ecoinvent transportation process used: <i>Transport, freight, lorry, unspecified market for transport, freight, lorry, unspecified Cut,off.</i>		

Table 4: Installation into the Building (A5).

Name	Value	Unit
Diesel for construction equipment	2.36E-04	Gallons diesel/ft ²
VOC content	N/A	µg/m ³
Product loss per functional unit	1	%
Output materials resulting from on-site waste processing, generated by packaging waste (assumed landfilled)	0.00351	kg
Product: Glass Fiber Reinforced Cellulosic Facer (GRF) Polyiso Roof Insulation		
Waste materials at the construction site before waste processing, generated by product installation (assumed landfilled)	0.00733	kg
Product: Coated Glass Facer (CGF) Polyiso Roof Insulation		
Waste materials at the construction site before waste processing, generated by product installation (assumed landfilled)	0.00815	kg
Note	The data for VOC content is not available and it is designated with a symbol N/A.	

Polyiso Roof Insulation Boards

Table 5: Reference Service Life.

Name	Value	Unit
RSL	40	years
Declared product properties (at the gate) and finishes, etc.	1	m ²
	1	R _{SI}

Table 6: Replacement (B4).

Name	Value	Unit
Replacement Cycle	1	Number/RSL
Replacement Cycle	1.9	Number/ESL

Table 7: Disposal/End of life (C1-C4).

Name	Value	Unit
Landfill	100	%

LCA RESULTS

Functional Unit: The functional unit for building envelope thermal insulation as defined by the PCR (Part B, Section 3.1) is: 1 m² of installed insulation with a thickness providing a thermal resistance of 1 m²·K/W and with a building service life of 75 years (packaging included). In the United States, thermal resistance (R_{IP}) is commonly reported in imperial system unit of measure (ft²·°F·h/Btu) with 1 m²·K/W equivalent to 5.678 ft²·°F·h/Btu. The data for a 0.066 m (2.6-inch) thick, GRF faced and CGF faced roof insulation boards, 2.6 m²·K/W (15 ft²·°F·h/Btu) R-value is normalized to a thermal resistance of 1 m²·K/W (5.678 ft²·°F·h/Btu).. Table 8 provides the characteristics of the functional unit.

Polyiso Roof Insulation Boards

Table 8: Functional Unit Properties.

Name	Value	Unit
Functional Unit	1 m ² (10.76 ft ²) of installed insulation with a thickness providing a thermal resistance of 1 m ² ·K/W (5.678 ft ² ·°F·h/Btu)	
Product: Glass Fiber Reinforced Cellulosic Facer (GRF) Polyiso Roof Insulation		
Mass	0.733 (1.62)	kg (lb)
Thickness to achieve functional unit	0.025 (0.984)	m (in)
Product: Coated Glass Facer (CGF) Polyiso Roof Insulation		
Mass	0.815 (1.80)	kg (lb)
Thickness to achieve functional unit	0.025 (0.984)	m (in)

This declaration is cradle-to-grave and all information modules are declared. As discussed in the Life Cycle Assessment Scope and Boundaries Section, Modules B1, B2, B3, B5, B6, B7, C1 and C3 do not contribute to impacts and are declared as zero. Optional Module D – Benefits and Loads Beyond the System Boundary – is not included in this LCA study. In the interest of conciseness, the tables with results in this section do not include these modules.

Polyiso Roof Insulation Boards

Table 9: Description of the System Boundary Modules.

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE					END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	C1	C2	C3	C4	D
Raw Material Supply	Transport	Manufacturing	Transport from Gate to Site	Assembly / Install	Use	Maintenance	Repair	Replacement	Refurbishment	Deconstruction	Transport	Waste Processing	Disposal	Reuse, Recovery, Recycling Potential
					B6	Building Operational Energy Use During Product Use			X					
					B7	Building Operational Water Use During Product Use			X					
X	X	X	X	X	X	X	X	X	X	X	X	X	X	MND
MND = module not declared														

Polyiso Roof Insulation Boards

The following tables detail the results of the roof products by functional unit $RSI=1 \text{ m}^2 \cdot \text{K/W}$, including the impact assessment results using the TRACI 2.1 impact assessment method and the inventory metrics required by the PCR. These six impact categories are globally deemed mature enough to be included in Type III environmental declarations. Other categories are being developed and defined and LCA should continue making advances in their development, however the EPD users shall not use additional measures for comparative purposes. LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks.

Product: Glass Fiber Reinforced Cellulosic Facer (GRF) Polyiso Roof Insulation.

Table 10: TRACI 2.1 Impact Categories – Functional Unit for all Life Cycle Stages Totals.

IMPACT CATEGORY	UNIT	TOTAL VALUE
GWP: Global Warming Potential	kg CO ₂ eq	4.50E+00
ODP: Ozone Depletion Potential	kg CFC-11 eq	3.34E-07
AP: Acidification Potential	kg SO ₂ eq	2.16E-02
EP: Eutrophication Potential	kg N eq	3.24E-02
POCP: Photochemical Oxidant Creation Potential	kg O ₃ eq	2.48E-01
ADP _{fossil} : Abiotic Resource Depletion Potential of Non-renewable energy resources	MJ, LHV	1.23E+01

Table 11: TRACI 2.1 Impact Categories – Functional Unit by System Boundary Module.

IMPACT CATEGORY	UNIT	A1	A2	A3	A4	A5	B4	C2	C4
GWP	kg CO ₂ eq	1.85E+00	6.48E-02	2.61E-01	7.81E-02	2.35E-02	2.13E+00	3.73E-03	9.12E-02
ODP	kg CFC-11 eq	1.23E-07	1.38E-08	1.71E-08	1.94E-08	4.47E-11	1.58E-07	9.28E-10	1.64E-09
AP	kg SO ₂ eq	9.56E-03	5.63E-04	3.99E-04	4.01E-04	3.10E-04	1.02E-02	1.92E-05	1.09E-04
EP	kg N eq	2.82E-03	1.17E-04	8.70E-04	9.36E-05	2.41E-05	1.54E-02	4.47E-06	1.31E-02
POCP	kg O ₃ eq	8.62E-02	1.57E-02	5.48E-03	1.01E-02	1.00E-02	1.18E-01	4.82E-04	2.65E-03
ADP _{fossil}	MJ, LHV	5.91E+00	1.25E-01	1.86E-01	1.75E-01	4.76E-02	5.83E+00	8.35E-03	2.37E-02

Polyiso Roof Insulation Boards

Table 12: Resource Use Indicators – Functional Unit by System Boundary Module.

RESOURCE INDICATOR	UNIT	A1	A2	A3	A4	A5	B4	C2	C4
RPRE	MJ, LHV	9.52E-01	1.88E-02	1.12E-01	1.26E-02	7.27E-04	9.91E-01	6.01E-04	4.39E-03
RPRM	MJ, LHV	3.62E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.26E-01	0.00E+00	0.00E+00
NRPRE	MJ, LHV	2.34E+01	9.27E-01	2.29E+00	1.22E+00	3.22E-01	2.56E+01	5.85E-02	1.91E-01
NRPRM	MJ, LHV	2.06E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.85E+01	0.00E+00	0.00E+00
SM	kg	1.89E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.70E-01	0.00E+00	0.00E+00
FW	m ³	7.69E-03	2.02E-04	4.26E-04	2.06E-04	2.93E-05	7.92E-03	9.85E-06	2.31E-04
RSF	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
NRSF	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
RE	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Note	The data for the following resource indicators: RSF: Renewable secondary fuels; NRSF: Non-renewable secondary fuels; RE: Recovered energy, are not available and it is designated with a symbol N/A.								

Polyiso Roof Insulation Boards

Table 13: Waste and Other Outputs – Functional Unit by System Boundary Module.

OUTPUT FLOWS	UNIT	A1	A2	A3	A4	A5	B4	C2	C4
HWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	8.88E-08	0.00E+00	9.87E-08
NHWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.44E-03	0.00E+00	4.93E-03
MR	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.44E-06	0.00E+00	4.93E-06
HLRW	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ILLRW	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
CRU	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
MER	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
EE	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Note	No substances required to be reported as hazardous are associated with the production of this product, however a small percentage of the manufacturing waste is disposed of as hazardous waste. The data for the following output flows: HLRW: High level radioactive waste disposed; ILLRW: Intermediate-and low-level radioactive waste, conditioned, to final repository; CRU: Components for re-use; MER: Materials for energy recovery; EE: Exported energy, are not available and it is designated with symbol N/A.								

Product: Coated Glass Facer (CGF) Polyiso Roof Insulation.

Table 14: TRACI 2.1 Impact Categories – Functional Unit for all Life Cycle Stages Totals.

IMPACT CATEGORY	UNIT	TOTAL VALUE
GWP: Global Warming Potential	kg CO ₂ eq	6.14E+00
ODP: Ozone Depletion Potential	kg CFC-11 eq	4.53E-07
AP: Acidification Potential	kg SO ₂ eq	2.86E-02
EP: Eutrophication Potential	kg N eq	4.10E-02
POCP: Photochemical Oxidant Creation Potential	kg O ₃ eq	3.39E-01
ADP _{fossil} : Abiotic Resource Depletion Potential of Non-renewable energy resources	MJ, LHV	1.38E+01

Polyiso Roof Insulation Boards

Table 15: TRACI 2.1 Impact Categories – Functional Unit by System Boundary Module.

IMPACT CATEGORY	UNIT	A1	A2	A3	A4	A5	B4	C2	C4
GWP	kg CO ₂ eq	2.69E+00	6.48E-02	2.61E-01	8.66E-02	2.35E-02	2.91E+00	4.15E-03	1.02E-01
ODP	kg CFC-11 eq	1.83E-07	1.38E-08	1.71E-08	2.15E-08	4.47E-11	2.14E-07	1.03E-09	1.82E-09
AP	kg SO ₂ eq	1.32E-02	5.63E-04	3.99E-04	4.45E-04	3.10E-04	1.35E-02	2.13E-05	1.21E-04
EP	kg N eq	5.82E-03	1.17E-04	8.70E-04	1.04E-04	2.41E-05	1.94E-02	4.98E-06	1.46E-02
POCP	kg O ₃ eq	1.32E-01	1.57E-02	5.48E-03	1.12E-02	1.00E-02	1.60E-01	5.36E-04	2.95E-03
ADP _{fossil}	MJ, LHV	6.66E+00	1.25E-01	1.86E-01	1.94E-01	4.76E-02	6.53E+00	9.30E-03	2.64E-02

Table 16: Resource Use Indicators – Functional Unit by System Boundary Module.

RESOURCE INDICATOR	UNIT	A1	A2	A3	A4	A5	B4	C2	C4
RPRE	MJ, LHV	1.63E+00	1.88E-02	1.12E-01	1.15E-02	7.27E-04	1.60E+00	6.69E-04	4.89E-03
RPRM	MJ, LHV	3.62E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.26E-01	0.00E+00	0.00E+00
NRPRE	MJ, LHV	3.53E+01	9.27E-01	2.29E+00	1.12E+00	3.22E-01	3.62E+01	6.51E-02	2.13E-01
NRPRM	MJ, LHV	2.06E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.85E+01	0.00E+00	0.00E+00
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	1.31E-02	2.02E-04	4.26E-04	2.29E-04	2.93E-05	1.29E-02	1.10E-05	2.57E-04
RSF	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
NRSF	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
RE	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Note	The data for the following resource indicators; RSF: Renewable secondary fuels; NRSF: Non-renewable secondary fuels; RE: Recovered energy, are not available and it is designated with a symbol N/A.								

Polyiso Roof Insulation Boards

Table 17: Waste and Other Outputs – Functional Unit by System Boundary Module.

OUTPUT FLOWS	UNIT	A1	A2	A3	A4	A5	B4	C2	C4
HWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	8.88E-08	0.00E+00	9.87E-08
NHWD	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.44E-03	0.00E+00	4.93E-03
MR	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.44E-06	0.00E+00	4.93E-06
HLRW	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
ILLRW	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
CRU	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
MER	kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
EE	MJ	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Note	No substances required to be reported as hazardous are associated with the production of this product, however a small percentage of the manufacturing waste is disposed of as hazardous waste. The data for the following output flows: HLRW: High level radioactive waste disposed; ILLRW: Intermediate-and low-level radioactive waste, conditioned, to final repository; CRU: Components for re-use; MER: Materials for energy recovery; EE: Exported energy, are not available and it is designated with symbol N/A.								

LCA INTERPRETATION

Module Impact Analysis

The life cycle assessment results inform the users on the cradle-to-grave environmental profile for polyiso roof insulation boards. As described in the Use and Reference Service Life section of this declaration, all life cycle stage environmental impacts are connected with the original building construction with “Roof Recover” operation at 20-years as well as the building’s “Roof Replacement” operation at 40-years. This translates to 1.9 replacement cycles during the 75-year building ESL. The impact of the Roof Replacement operation is captured in module B4. The environmental profile for the initial 40-years for polyiso roof insulation boards is captured in modules A1 through A5, C2 and C4. This distinction allows a closer examination of the impacts that the individual modules have on the overall environmental profile of polyiso roof insulation boards.

Polyiso Roof Insulation Boards

When assessing environmental profiles of products, Global Warming Potential (GWP) is an important Impact Category.

The relative impact of modules on GWP for polyiso roof insulation boards with GRF facer is illustrated in Figure 5. Module A1 (raw materials) is the most dominant module accounting for 78% of the impacts, followed by Module A3 (manufacturing) accounting for 11%. The remaining modules A2, A4, A5, C2, and C4, each contribute 4% or less to the impacts.




Figure 5: Relative Impact of Modules on Global Warming Potential for GRF Faced Polyiso Roof Insulation Boards.

The analysis in Tables 10 through 13 indicates that Module A1 (raw materials) dominates the environmental profile of polyiso roof insulation boards. The aggregated primary and secondary data indicate that extraction and processing of raw materials have the largest impact. The polyiso industry is characterized as having many plants that produce polyiso roof insulation boards located throughout the United States and Canada. Many plants are located near large population centers with significant roof replacement and new roof construction activity, thus reducing the impacts from transportation.

The relative impact of modules on GWP for polyiso roof insulation boards with CGF facer is illustrated in Figure 5. Module A1 (raw materials) is the most dominant module accounting for 83% of the impacts, followed by Module A3 (manufacturing) accounting for 8%. The remaining modules A2, A4, A5, C2, and C4, each contribute 3% or less to the impacts.

Polyiso Roof Insulation Boards




Figure 6: Relative Impact of Modules on Global Warming Potential for CGF Faced Polyiso Roof Insulation Boards.

The analysis in Tables 14 through 17 indicates that Module A1 (raw materials) dominates the environmental profile of polyiso roof insulation boards. The aggregated primary and secondary data indicate that extraction and processing of raw materials have the largest impact. The polyiso industry is characterized as having many plants that produce polyiso roof insulation boards located throughout the United States and Canada. Many plants are located near large population centers with significant roof replacement and new roof construction activity, thus reducing the impacts from transportation.

Environmental Profiles for Common Polyiso Thicknesses Configurations

Polyiso Roof Insulation Boards with GRF and CGF facers are available in incremental R_{IP} -values from 5.7 ft²·°F·h/Btu to 27 ft²·°F·h/Btu. For this declaration, cradle-to-grave environmental profiles were calculated on three popular thicknesses for the two facer types: 1.8-inch (R_{IP} – 10.3 ft²·°F·h/Btu), 2.6-inch (R_{IP} – 15 ft²·°F·h/Btu) and 3.5-inch (R_{IP} – 20.5 ft²·°F·h/Btu). The International Energy Conservation Code (IECC) requires roof insulation to be installed in multiple layers with staggered joints to enhance the thermal performance of the roof system. These requirements do not exist in the Canada's National Energy Code for Buildings. To provide the users of this document the opportunity to assess common Polyiso roof insulation configurations, the Impact and Indicator metrics are listed for all life cycle stages for four two layer combinations corresponding to the minimum R-value requirements of the IECC and ASHRAE 90.1 Standard for insulation entirely above deck in all climate zones throughout the United States and Canada. The data for single board and two-layer combinations are provided in Tables 18 through 22. **Impact and Indicator values on any thickness of product between 1.8-inch and 3.5-inch can be calculated through linear extrapolation from the data in these Tables.**

Polyiso Roof Insulation Boards

Table 18: Impacts/Indicators for All Life Cycle Stages of Common GRF Product Thicknesses.

<i>Product: Glass Fiber Reinforced Cellulosic Facer (GRF) Polyiso Roof Insulation</i>								
Impact Category / Environmental Indicator		Unit	1.8-inch Thick R _{IP} : 10.3		2.6 -inch Thick R _{IP} : 15		3.5-inch Thick R _{IP} : 20.5	
			Per 1 ft ²	Per 1 m ²	Per 1 ft ²	Per 1 m ²	Per 1 ft ²	Per 1 m ²
TRACI 2.1 Impact Categories	GWP: Global Warming Potential	kg CO ₂ eq	7.95E-01	8.56E+00	1.11E+00	1.19E+01	1.49E+00	1.60E+01
	ODP: Ozone Depletion Potential	kg CFC-11 eq	5.92E-08	6.37E-07	8.20E-08	8.83E-07	1.09E-07	1.18E-06
	AP: Acidification Potential	kg SO ₂ eq	3.77E-03	4.06E-02	5.30E-03	5.70E-02	7.11E-03	7.65E-02
	EP: Eutrophication Potential	kg N eq	5.98E-03	6.43E-02	7.96E-03	8.56E-02	1.04E-02	1.12E-01
	POCP: Photochemical Oxidant Creation Potential	kg O ₃ eq	4.48E-02	4.82E-01	6.09E-02	6.55E-01	8.07E-02	8.68E-01
	ADP _{fossil} : Abiotic Resource Depletion Potential of Non-Renewable Energy Resources	MJ, LHV	2.14E+00	2.30E+01	3.02E+00	3.25E+01	4.10E+00	4.41E+01
Resource Use Indicators	RPR _E : Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	3.77E-01	4.05E+00	5.13E-01	5.52E+00	7.07E-01	7.62E+00
	RPR _M : Renewable Primary Resources with Energy Content Used as Material	MJ, LHV	1.22E-01	1.32E+00	1.69E-01	1.82E+00	2.41E-01	2.59E+00
	NRPR _E : Non-Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	1.02E+01	1.10E+02	1.32E+01	1.42E+02	1.87E+01	2.01E+02
	NRPR _M : Non-Renewable Primary Resources Used as Material	MJ, LHV	5.96E+00	6.42E+01	9.61E+00	1.03E+02	1.23E+01	1.33E+02
	PED: Total Primary Energy Demand	MJ, LHV	1.67E+01	1.80E+02	2.35E+01	2.53E+02	3.19E+01	3.44E+02
	SM: Secondary Materials	kg	8.83E-02	9.51E-01	8.83E-02	9.51E-01	8.83E-02	9.51E-01
	FW: Use of Net Fresh Water Resources	m ³	2.98E-03	3.21E-02	4.10E-03	4.41E-02	5.63E-03	6.05E-02
Waste Output	HWD: Hazardous Waste Disposed	kg	3.19E-08	3.44E-07	4.60E-08	4.95E-07	6.29E-08	6.77E-07
	NHWD: Non-Hazardous Waste Disposed	kg	1.59E-03	1.72E-02	2.30E-03	2.47E-02	3.14E-03	3.38E-02
	MR: Materials for Recycle	kg	1.60E-06	1.72E-05	2.30E-06	2.48E-05	3.15E-06	3.39E-05

Polyiso Roof Insulation Boards

Table 19: Impacts/Indicators for All Life Cycle Stages of Common GRF Two-Layer Configurations.

Product: Glass Fiber Reinforced Cellulosic Facer (GRF) Polyiso Roof Insulation										
Impact Category / Environmental Indicator		Unit	2 Layers of 1.8-inch Thick R _{IP} : 20.6		1 Layer of 1.8-inch & 1 Layer of 2.6-inch Thick R _{IP} : 25.3		2 Layers of 2.6-inch Thick R _{IP} : 30.0		1 Layers of 2.6 inch & 1 Layer of 3.5-inch Thick R _{IP} : 35.5	
			Per ft ²	Per m ²	Per ft ²	Per m ²	Per ft ²	Per m ²	Per ft ²	Per m ²
TRACI 2.1 Impact Categories	GWP: Global Warming Potential	kg CO ₂ eq	1.59E+00	1.71E+01	1.90E+00	2.05E+01	2.21E+00	2.38E+01	2.60E+00	2.79E+01
	ODP: Ozone Depletion Potential	kg CFC-11 eq	1.18E-07	1.27E-06	1.41E-07	1.52E-06	1.64E-07	1.77E-06	1.91E-07	2.06E-06
	AP: Acidification Potential	kg SO ₂ eq	7.55E-03	8.12E-02	9.07E-03	9.76E-02	1.06E-02	1.14E-01	1.24E-02	1.34E-01
	EP: Eutrophication Potential	kg N eq	1.20E-02	1.29E-01	1.39E-02	1.50E-01	1.59E-02	1.71E-01	1.84E-02	1.98E-01
	POCP: Photochemical Oxidant Creation Potential	kg O ₃ eq	8.96E-02	9.64E-01	1.06E-01	1.14E+00	1.22E-01	1.31E+00	1.42E-01	1.52E+00
	ADP _{fossil} : Abiotic Resource Depletion Potential of Non-Renewable Energy Resources	MJ, LHV	4.27E+00	4.60E+01	5.15E+00	5.55E+01	6.04E+00	6.50E+01	7.12E+00	7.66E+01
Resource Use Indicators	RPR _E : Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	7.53E-01	8.11E+00	8.90E-01	9.58E+00	1.03E+00	1.10E+01	1.22E+00	1.31E+01
	RPR _M : Renewable Primary Resources with Energy Content Used as Material	MJ, LHV	2.45E-01	2.64E+00	2.91E-01	3.14E+00	3.38E-01	3.64E+00	4.10E-01	4.41E+00
	NRPR _E : Non-Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	2.05E+01	2.21E+02	2.34E+01	2.52E+02	2.64E+01	2.84E+02	3.19E+01	3.43E+02
	NRPR _M : Non-Renewable Primary Resources Used as Material	MJ, LHV	1.19E+01	1.28E+02	1.56E+01	1.68E+02	1.92E+01	2.07E+02	2.19E+01	2.36E+02
	PED: Total Primary Energy Demand	MJ, LHV	3.34E+01	3.60E+02	4.02E+01	4.33E+02	4.70E+01	5.06E+02	5.54E+01	5.96E+02
	SM: Secondary Materials	kg	1.77E-01	1.90E+00	1.77E-01	1.90E+00	1.77E-01	1.90E+00	1.77E-01	1.90E+00
	FW: Use of Net Fresh Water Resources	m ³	5.97E-03	6.42E-02	7.09E-03	7.63E-02	8.20E-03	8.83E-02	9.73E-03	1.05E-01
Waste Output	HWD: Hazardous Waste Disposed	kg	6.39E-08	6.87E-07	7.79E-08	8.39E-07	9.20E-08	9.90E-07	1.09E-07	1.17E-06
	NHWD: Non-Hazardous Waste Disposed	kg	3.19E-03	3.43E-02	3.89E-03	4.19E-02	4.60E-03	4.95E-02	5.44E-03	5.86E-02
	MR: Materials for Recycle	kg	3.19E-06	3.44E-05	3.90E-06	4.19E-05	4.60E-06	4.95E-05	5.45E-06	5.86E-05

Polyiso Roof Insulation Boards

Table 20: Impacts/Indicators for All Life Cycle Stages of Common CGF Product Thicknesses.

Product: Coated Glass Facer (CGF) Polyiso Roof Insulation								
Impact Category / Environmental Indicator		Unit	1.8-inch Thick R _{IP} : 10.3		2.6-inch Thick R _{IP} : 15		3.5-inch Thick R _{IP} : 20.5	
			Per 1 ft ²	Per 1 m ²	Per 1 ft ²	Per 1 m ²	Per 1 ft ²	Per 1 m ²
TRACI 2.1 Impact Categories	GWP: Global Warming Potential	kg CO ₂ eq	1.20E+00	1.29E+01	1.51E+00	1.62E+01	1.89E+00	2.04E+01
	ODP: Ozone Depletion Potential	kg CFC-11 eq	8.83E-08	9.50E-07	1.11E-07	1.20E-06	1.38E-07	1.49E-06
	AP: Acidification Potential	kg SO ₂ eq	5.48E-03	5.90E-02	7.01E-03	7.54E-02	8.82E-03	9.49E-02
	EP: Eutrophication Potential	kg N eq	8.06E-03	8.68E-02	1.01E-02	1.08E-01	1.25E-02	1.35E-01
	POCP: Photochemical Oxidant Creation Potential	kg O ₃ eq	6.70E-02	7.22E-01	8.31E-02	8.95E-01	1.03E-01	1.11E+00
	ADP _{fossil} : Abiotic Resource Depletion Potential of Non-Renewable Energy Resources	MJ, LHV	2.50E+00	2.69E+01	3.38E+00	3.64E+01	4.46E+00	4.81E+01
Resource Use Indicators	RPR _E : Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	6.95E-01	7.49E+00	8.32E-01	8.95E+00	1.03E+00	1.10E+01
	RPR _M : Renewable Primary Resources with Energy Content Used as Material	MJ, LHV	1.22E-01	1.32E+00	1.69E-01	1.82E+00	2.41E-01	2.59E+00
	NRPR _E : Non-Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	1.58E+01	1.70E+02	1.87E+01	2.02E+02	2.42E+01	2.60E+02
	NRPR _M : Non-Renewable Primary Resources Used as Material	MJ, LHV	5.96E+00	6.42E+01	9.61E+00	1.03E+02	1.23E+01	1.33E+02
	PED: Total Primary Energy Demand	MJ, LHV	2.26E+01	2.43E+02	2.93E+01	3.16E+02	3.78E+01	4.07E+02
	SM: Secondary Materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	FW: Use of Net Fresh Water Resources	m ³	5.55E-03	5.97E-02	6.67E-03	7.18E-02	8.19E-03	8.82E-02
Waste Output	HWD: Hazardous Waste Disposed	kg	3.19E-08	3.44E-07	4.60E-08	4.95E-07	6.29E-08	6.77E-07
	NHWD: Non-Hazardous Waste Disposed	kg	1.59E-03	1.72E-02	2.30E-03	2.47E-02	3.14E-03	3.38E-02
	MR: Materials for Recycle	kg	1.60E-06	1.72E-05	2.30E-06	2.48E-05	3.15E-06	3.39E-05

Polyiso Roof Insulation Boards

Table 21: Impacts/Indicators for All Life Cycle Stages of Common CGF Two-Layer Configurations.

Product: Coated Glass Facer (CGF) Polyiso Roof Insulation										
Impact Category / Environmental Indicator		Unit	2 Layers of 1.8-inch Thick R _{IP} : 20.6		1 Layer of 1.8-inch & 1 Layer of 2.6-inch Thick R _{IP} : 25.3		2 Layers of 2.6-inch Thick R _{IP} : 30.0		1 Layer of 2.6-inch & 1 Layer of 3.5-inch Thick R _{IP} : 35.5	
			Per ft ²	Per m ²	Per ft ²	Per m ²	Per ft ²	Per m ²	Per ft ²	Per m ²
TRACI 2.1 Impact Categories	GWP: Global Warming Potential	kg CO ₂ eq	2.39E+00	2.58E+01	2.70E+00	2.91E+01	3.01E+00	3.24E+01	3.40E+00	3.66E+01
	ODP: Ozone Depletion Potential	kg CFC-11 eq	1.77E-07	1.90E-06	1.99E-07	2.15E-06	2.22E-07	2.39E-06	2.49E-07	2.68E-06
	AP: Acidification Potential	kg SO ₂ eq	1.10E-02	1.18E-01	1.25E-02	1.34E-01	1.40E-02	1.51E-01	1.58E-02	1.70E-01
	EP: Eutrophication Potential	kg N eq	1.61E-02	1.74E-01	1.81E-02	1.95E-01	2.01E-02	2.16E-01	2.26E-02	2.43E-01
	POCP: Photochemical Oxidant Creation Potential	kg O ₃ eq	1.34E-01	1.44E+00	1.50E-01	1.62E+00	1.66E-01	1.79E+00	1.86E-01	2.00E+00
	ADP _{fossil} : Abiotic Resource Depletion Potential of Non-Renewable Energy Resources	MJ, LHV	5.00E+00	5.38E+01	5.88E+00	6.33E+01	6.76E+00	7.28E+01	7.85E+00	8.45E+01
Resource Use Indicators	RPR _E : Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	1.39E+00	1.50E+01	1.53E+00	1.64E+01	1.66E+00	1.79E+01	1.86E+00	2.00E+01
	RPR _M : Renewable Primary Resources with Energy Content Used as Material	MJ, LHV	2.45E-01	2.64E+00	2.91E-01	3.14E+00	3.38E-01	3.64E+00	4.10E-01	4.41E+00
	NRPR _E : Non-Renewable Primary Resources Used as an Energy Carrier (Fuel)	MJ, LHV	3.16E+01	3.40E+02	3.45E+01	3.72E+02	3.75E+01	4.03E+02	4.29E+01	4.62E+02
	NRPR _M : Non-Renewable Primary Resources Used as Material	MJ, LHV	1.19E+01	1.28E+02	1.56E+01	1.68E+02	1.92E+01	2.07E+02	2.19E+01	2.36E+02
	PED: Total Primary Energy Demand	MJ, LHV	4.51E+01	4.86E+02	5.19E+01	5.59E+02	5.87E+01	6.32E+02	6.71E+01	7.22E+02
	SM: Secondary Materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	FW: Use of Net Fresh Water Resources	m ³	1.11E-02	1.19E-01	1.22E-02	1.31E-01	1.33E-02	1.44E-01	1.49E-02	1.60E-01
Waste Output	HWD: Hazardous Waste Disposed	kg	6.39E-08	6.87E-07	7.79E-08	8.39E-07	9.20E-08	9.90E-07	1.09E-07	1.17E-06
	NHWD: Non-Hazardous Waste Disposed	kg	3.19E-03	3.43E-02	3.89E-03	4.19E-02	4.60E-03	4.95E-02	5.44E-03	5.86E-02
	MR: Materials for Recycle	kg	3.19E-06	3.44E-05	3.90E-06	4.19E-05	4.60E-06	4.95E-05	5.45E-06	5.86E-05

ADDITIONAL ENVIRONMENTAL INFORMATION

Polyiso insulation provides a high net return on embedded energy and a low global warming potential.

- Zero ozone depletion potential (Zero-ODP)
- HCFC-Free
- Contains post-industrial recycled content
- LEED® benefits

The technical documents for Weatherbond's products can be found here:

1. https://www.weatherbondroofing.com/wp-content/uploads/WB-2136-XP-Polyiso-TDB_07-26-21.pdf
2. <https://www.weatherbondroofing.com/wp-content/uploads/WB-2138-XFP-Polyiso-TDB-07-27-21.pdf>

Fire Performance: The fire performance of low-slope roof assemblies is evaluated on assembly tests (from the deck to roof covering) with respect to both external and internal fire exposure. The fire exposures in tests simulates the type of fire exposure a roof may encounter during its service life, including interior building fires or exterior hazards. The resistance of a roof system to external fire exposure is evaluated using ASTM E108 "Standard Test Methods for Fire Tests of Roof Coverings," UL 790 "Standard Test Methods for Fire Tests of Roof Coverings" or the Canadian equivalent, CAN/ULC-S107 "Methods of Fire Tests of Roof Coverings." The test methods provide a basis for comparing roof assemblies under a simulated exterior fire. Roof assemblies restricted to noncombustible decks require only the spread-of-flame test, while roof assemblies used on combustible decks are evaluated for spread of flame, intermittent flame, and the burning brand tests. Roof assemblies can achieve a Class A, B, or C classification. Class A designates the resistance to relatively severe fire-test exposure. Class B designates resistance to relatively moderate fire-test exposure. Class C designates resistance to relatively light fire-test exposure.

Fires can also originate within the building interior and roof system response to fire exposure originating from interior of the building may be evaluated using NFPA 276 "Standard Method of Fire Test for Determining the Heat Release Rate of Roofing Assemblies with Combustible Above-Deck Roofing Components," FM Approval 4470 "Single-Ply, Polymer-Modified Bitumen Sheet, Built-Up Roof (BUR) and Liquid Applied Roof: Assemblies For Use in Class 1 and Noncombustible Roof Deck Construction," UL 1256 "Fire Test of Roof Deck Construction," or CAN/ULC-S126 "Standard Method of Test for Fire Spread Under Roof-Deck Assemblies." The passing criteria is established by a limit-of-fuel contribution within a designated time period. Polyiso remains the only foam plastic roof insulation to earn FM Class 1 approval for direct-to-steel deck applications when tested in accordance with FM Approval 4470. Polyiso is also classified by UL under UL 1256 for direct-to-steel deck applications with both single-ply and asphalt-based roof coverings.

Building Use-Stage Environmental Benefits

Demonstration Summary: Polyiso's low thermal conductivity limits a building's operational energy consumption and associated environmental impacts. Quantifying the reduction in energy for heating, cooling, and ventilating a specific building design using Polyiso versus a baseline design is important to demonstrating these benefits relative to environmental encumbrances of the declared product. For this purpose, extensive analyses involving building energy simulations were conducted on Roof Replacement (RR) scenarios for twenty-two (22) locations spread throughout the climate zones of the United States and ten (10) locations throughout the geographic regions of Canada. The protocol for this comprehensive study is in accordance with the guidelines set forth in the PCR (Part B, Section 7.2), including the utilization of the whole-building energy simulation tool, EnergyPlus, the PNNL Strip Mall commercial building prototype model (ASHRAE 90.1-2004 compliant), and representative baseline scenarios.

Roof Replacement Background: Reroofing is one of the most common alteration projects conducted on any given existing commercial building with roof recover(s) and/or roof replacement(s) performed 2-3 times during its life. It is recognized that roofs on buildings of twenty (20) years or more of age are likely to be under-insulated by today's standards and minimum energy code requirements. For the framework of the declared unit of the Polyiso Roof Insulation product, Roof Replacement (RR) is performed on the roof in which the product is installed forty (40) years after the building is constructed. Furthermore, the framework conservatively presumes that all of the Polyiso is replaced with new product which remains in place for the remainder of the building's life span, meaning an additional thirty-five (35) years. The cradle-to-grave environmental profile of the new product is accounted for in its entirety under Use-stage Module 4B, Replacement.

Modelling Protocol: In this demonstration, three (3) original single-layer mechanically attached roof insulation baselines of R_{IP-10} , $R_{IP-12.5}$ and R_{IP-15} are simulated for each location. A fourth model consists of a second layer of Polyiso adhered to the original layer, which for the United States, brings the roof assembly in R-value compliance with current versions of the IECC and ASHRAE 90.1 for Roof Replacements depending on Climate Zone. For Canada, the fourth model consists of a second layer bringing the R-value to R_{IP-30} ($R_{SI-5.3}$) as there is currently no minimum requirement for Roof Replacements. See Tables 22 and 23 for further detail of the modelled scenarios for the United States and Canada, respectively. As such, each simulation provides an assessment of the energy savings benefits of the additional insulation installed compared to its embodied aspects extrapolated from Tables 19 and 20 for GRF Polyiso Insulation product.

Result Metric Descriptions: The results of the analyses are presented for **Primary Energy Demand (PED)** and **Global Warming Potential (GWP)**. The values expressed represent specific RR-to-baseline comparisons or averages amongst a group of comparisons. Terms used are described as follows:

- **Add'l Polyiso PED** – Cradle-to-Grave PED embodied in the full life cycle (LC) of the additional installed Polyiso GRF roof insulation product (GJ/m^2 of roof area).
- **PED Savings** – The building operational PED savings over the 35-year life cycle of the additional installed Polyiso GRF roof insulation product (GJ/m^2 of roof area).
- **PED Savings Ratio** – This is the ratio of PED Savings to Add'l Polyiso PED. The higher the ratio, the greater the benefit of the additional Polyiso in regard to energy resource consumption.
- **PED Recoup Period** – The period of time estimated to recoup Add'l Polyiso PED following RR through PED Savings (Months).
- **Add'l Polyiso CO₂** – Cradle-to-Grave GWP emissions in the full life cycle (LC) of the additional installed Polyiso GRF roof insulation product ($kg\ CO_2/m^2$ of roof area).

Polyiso Roof Insulation Boards

- **CO₂ Avoidance** – The avoidance of GWP emissions associated with the building operational energy savings over the 35-year life cycle of the additional installed Polyiso GRF roof insulation product (kg CO₂/m² of roof area).
- **CO₂ Avoidance Ratio** – This is the ratio of CO₂ Avoidance to Add'l Polyiso CO₂. The higher the ratio, the greater the benefit of the additional Polyiso in regard to carbon emissions reduction.
- **CO₂ Recoup Period** – The period of time estimated to recoup Add'l Polyiso CO₂ following RR through CO₂ Avoidance (Months).

National Averages: Primary Energy Demand and Global Warming Potential national average results for the United States and Canada are presented in Figures 5 and 6, respectively. Averages were calculated for each United States Climate Zone and Canadian Region by averaging the three (3) baseline savings results for each location and by taking the average of all locations within each Zone/Region. National averages were calculated by weighting each Zone/Region on an estimated commercial floor area basis. Of special note for Canada, existing building floor area gives particularly heavy weighting to the Great Lakes Region (54%).

Primary Energy Demand Savings Ratios and Recoup Periods are shown in Figure 5. A ratio of 28 and a recoup of only 15 months of building operation provides context to the environmental benefits of Polyiso in Roof Replacement applications. The overall colder climate of Canada provides even greater evidence of these benefits with a Ratio of 37 and a recoup of a year. This compelling argument, the energy savings and the key opportunity posed by reroofing of existing buildings, is valuable insight for the sustainable-minded designer, building owner and public official.

Governments, corporations and individuals across the planet are committed to lowering carbon emissions. Polyiso for newly constructed roofs and walls, as well as new roofs on existing buildings, plays a key role in meeting these commitments. Figure 6 demonstrates how the relatively low Global Warming Potential of additional insulation installed during roof replacement contributes to the avoidance of emissions associated with the building operational energy saved by it. The national averages for both the United States and Canada exhibit even greater beneficial environmental results in terms of greenhouse gas emissions reductions. The CO₂ Avoidance Ratio is 34 and the CO₂ Recoup Period is 13 months. For Canada, the Ratio indicates that for every square meter of roof area replaced, the emissions prevented are 45 kg of CO₂ equivalents times that of the cradle-to-grave encumbered impact of each square meter of the additional Polyiso GRF Roof Insulation. Therefore, the life cycle insulation emissions are matched by those avoided as a result of energy savings in the first 9 months of the 35-years of remaining operation.

Polyiso Roof Insulation Boards




Figure 7: National average results for Primary Energy Demand




Figure 8: National average results for Global Warming Potential

United States Location Summary: See Figure 7 for United States GWP results noting the CO₂ Avoidance Ratios are represented by the scatter plot and the CO₂ Recoup Periods are represented by the columns. The Roof Replacement thermal performance for the twenty-two (22) United States locations established for these modelling analyses were based on the minimum roof insulation requirements of the model energy codes. They vary between R_{IP}-20 in Climate Zone 1 to R_{IP}-35 in Climate Zones 7 and 8. This creates a bit of a break in the continuity of the trends in the data. However, in general, the Ratio decreases slightly from very hot (CZ-1) to mild (CZ-4) climates. Yet still demonstrating being very emissions beneficial, the R-15 base cases for Philadelphia and New York registered the lowest Ratio (25) and highest Recoup Period (17 Months) of the sixty-six (66) United States scenarios modelled. Beginning with cold Climate Zone 5, the trend quite clearly and rapidly exhibits increasing Ratio and decreasing Recoup Period with increasing Heating Degree Days. For all locations, the R-10 baseline demonstrates providing the highest benefits with

Polyiso Roof Insulation Boards

regard to limiting carbon emissions for a Roof Replacement alteration. The R-10 baseline for International Falls, MN registered the highest Ratio and lowest Recoup Period with 55 and 8 Months, respectively.




Figure 9: U.S. location results for Global Warming Potential

Canada Location Summary: See Figure 8 for Canada GWP results noting the CO₂ Avoidance Ratios are represented by the scatter plot and the CO₂ Recoup Periods are represented by the columns. The Roof Replacement thermal performance for the ten (10) Canadian locations for all modelling scenario comparisons is R_{SI}-5.3 (R_{IP}-30). As noted above, Canadian energy codes currently do not include minimum roof insulation requirements other than maintaining the existing R-value levels for a Roof Replacement project. **The results of this examination provides compelling evidence that the implementation of regulations by Canada and its provinces on levels of insulation for alterations to roofs on existing buildings is critical to supporting an aggressive national policy on reducing greenhouse gas emissions.**

Here, the 10 locations are grouped geographically with overlap of climate. Canada consists predominately of cold to very cold climate with regard to commercial building floor space. The results closely follow the trend of increasing Ratios and decreasing Recoup Periods as Heating Degree Days increase. Just two (2) of the thirty (30) scenarios (the R-15 baseline for Windsor and Toronto) registered Ratios below the United States average of 34. The remaining twenty-eight (28) scenarios were greater than thirty-five (35), up to an extraordinary sixty seven (67) for the R_{SI}-1.8 (R_{IP}-10) baseline for Winnipeg. This scenario shows a CO₂ Recoup period of only six (6) months.

Polyiso Roof Insulation Boards




Figure 10: Canada location results for Global Warming Potential

Table 22: Minimum required roof insulation for Roof Replacement and 22 USA locations modelled by Climate Zone.

Climate Zone 1 - Roof Replacement R-value of R _{IP} -20
Location: Miami, FL
Climate Zone 2 - Roof Replacement R-value of R _{IP} -25
Locations: Tampa, FL; Dallas, TX.
Climate Zone 3 - Roof Replacement R-value of R _{IP} -25
Locations: Montgomery, AL; Atlanta, GA; Charlotte, NC.
Climate Zone 4 - Roof Replacement R-value of R _{IP} -30
Locations: Richmond, VA; Louisville, KY; Philadelphia, PA; New York, NY; Kansas City, KS; Indianapolis, IN.
Climate Zone 5 - Roof Replacement R-value of R _{IP} -30
Locations: Pittsburgh, PA; Hartford, CT; Chicago, IL; Buffalo, NY; Lansing, MI; Madison, WI.
Climate Zone 6 - Roof Replacement R-value of R _{IP} -30
Locations: St. Paul, MN; Rochester, MN.
Climate Zone 7/8 - Roof Replacement R-value of R _{IP} -35
Locations: Duluth, MN; International Falls, MN.
*Locations are listed in increasing value of Heating Degree Day 65°F Basis (HDD65)

Polyiso Roof Insulation Boards

Table 23: 10 Canadian locations modelled by Region.

Region: Atlantic - Roof Replacement R-value of R_{IP-30}
Location: St. Johns, NB
Region: Great Lakes - Roof Replacement R-value of R_{IP-30}
Locations: Windsor, ONT; Toronto, ONT; Montreal, QB; Ottawa; Quebec City, QB
Region: Central - Roof Replacement R-value of R_{IP-30}
Locations: Regina, SK; Winnipeg, MB
Region: Western - Roof Replacement R-value of R_{IP-30}
Locations: Calgary, AB; Edmonton, AB

REFERENCES & STANDARDS

1. ASHRAE. (2019). Standard 90.1-2019 – Energy Standard for Buildings Except Low-Rise Residential Buildings.
2. ASTM C203 – Test Methods for Breaching Load and Flexural Properties of Block-Type Thermal Insulation.
3. ASTM C209 – Standard Test Method for Cellulosic Fiber Insulating Board.
4. ASTM C518 – Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus.
5. ASTM C1289 – Standard Specification for Faced Rigid Cellular Polyisocyanurate Thermal Insulation Board.
6. ASTM C1303/C1303M – Test Method for Predicting Long-Term Thermal Resistance of Closed-Cell Foam Insulation.
7. ASTM C1763 – Test Method for Water Absorption by Immersion of Thermal Insulation Materials.
8. ASTM D1621 – Test Method for Compressive Properties of Rigid Cellular Plastics.
9. ASTM D1623 – Standard Test Method for Tensile and Tensile Adhesion Properties of Rigid Cellular Plastics.
10. ASTM D2126 – Test Method for Response of Rigid Cellular Plastics to Thermal and Humid Aging.
11. ASTM D2842 – Standard Test Method for Water Absorption of Rigid Cellular Plastics.
12. ASTM E96/E96M – Test Method for Water Vapor Transmission of Materials.
13. ASTM E108-17 / UL790-08 Standard Test Methods for Fire Tests of Roof Coverings.
14. CAN/ULC-S102 – Standard Method of Test for Surface Burning Characteristics of Building Materials and Assemblies.
15. CAN/ULC-S107 – Methods of Fire Tests of Roof Coverings.
16. CAN/ULC-S126 – Standard Method of Test for Fire Spread Under Roof-Deck Assemblies.
17. CAN/ULC-S704.1 – Standard for Thermal Insulation, Polyurethane and Polyisocyanurate, Boards, Faced.
18. CAN/ULC-S770 – Standard Testing Method for Determination of Long-Term Thermal Resistance of Closed-Cell Thermal Insulating Foams.
19. Ecoinvent centre. (2018). ecoinvent. Retrieved 2019, from ecoinvent 3.5: <https://ecoinvent.org/the-ecoinvent-database/data-releases/ecoinvent-3-5/>.
20. Ecoinvent center. (2019). Allocation cut-off by classification. Zurich, Switzerland: ecoinvent center. Retrieved 2019, from <https://ecoinvent.org/the-ecoinvent-database/system-models/#!/allocation-cut-off>.
21. EN15804. (2012). EN15804-2012 Sustainability of construction works, Environmental product declarations, Core rules for the product category of construction products.
22. FM 4450 – Approval Standard for Class 1 Insulated Steel Deck Roofs.
23. International Code Council. (2021). 2021 International Energy Conservation Code.
24. ISO 14025. (2006). ISO 14025-2006 Environmental labels and declarations — Type III environmental declarations — Principles and procedures. International Organization for Standardization.

Polyiso Roof Insulation Boards

25. ISO 14040. (2006). ISO14040-2006 Environmental management -- Life cycle assessment -- Principles and framework. International Organization for Standardization.
26. ISO 14044. (2006). ISO14044-2006 Environmental management -- Life cycle assessment -- Principles and framework. International Organization for Standardization.
27. ISO 21930. (2017). ISO 21930-2017 Sustainability in buildings and civil engineering works – Core rules for environmental product declarations of construction products and services. International Organization for Standardization.
28. Long Trail Sustainability. (2018). *DATASmart Life Cycle Inventory*. Retrieved from: <https://ltsexperts.com/services/software/datasmart-life-cycle-inventory>
29. Lei, X. et. al., PNNL-29787 (June 2020). *Development of National New Construction Weighting Factors for the Commercial Building Prototype Analyses (2003-2018)*.
30. Natural Resources Canada's Office of Energy Efficiency (December 2012). *Survey of Commercial and Institutional Energy Use -Buildings 2009*.
31. NFPA 276 – Standard Method of Fire Test for Determining the Heat Release Rate of Roofing Assemblies with Combustible Above-Deck Roofing Components.
32. NREL. (2015). United States Life Cycle Inventory Database. Retrieved from: <https://www.nrel.gov/lci/>
33. Pavlovich, et. al., (2011). *Life Cycle Assessment of Polyiso Insulation for Polyisocyanurate Insulation Manufacturers Association (PIMA)*. PIMA.
34. PE INTERNATIONAL, Inc. (2014). *Addendum to PIMA LCA for Updated EPDs*.
35. Phelan, J. (2019). *Improved Prediction and Optimization of Building Envelope Thermal Performance*. 2019 Buildings XIV International Conference, December 2019.
36. PNNL/U.S. Department of Energy, Energy Efficiency and Renewable Energy (April 17, 2020 updated). *Commercial Prototype Building Models*. https://www.energycodes.gov/development/commercial/prototype_models.
37. Stovall et al. (2012). Evaluation of Experimental Parameters in the Accelerated Aging of Closed-Cell. OakRidge National Laboratory.
38. UL. (2018).. Product Category Rules for Building-Related Products and Services Part A: Life Cycle Assessment Calculation Rules and Report Requirements (UL 10010, Version 3.2).
39. UL. (2018). Product Category Rule (PCR) Guidance for Building-Related Products and Services Part B: Building Thermal Insulation EPD Requirements (UL10010-1, Version 2.0).
40. UL-790 – Standard for Standard Test Method for Fire Tests of Roof Coverings.
41. UL-1256 – Standard for Fire Test of Roof Deck Constructions.
42. U.S. EPA. (2018). Tool for the Reduction and Assessment of Chemical and Other Environmental Impact (TRACI). For more information, visit: <https://www.epa.gov/chemical-research/tool-reduction-and-assessment-chemicals-and-other-environmental-impacts-traci>

Polyiso Roof Insulation Boards

43. U.S. EPA. (2018). Ozone depletion potential, or ODP, is a relative measure of substance's contribution to the degradation of the ozone layer. For more information, visit: <https://www.epa.gov/ozone-layer-protection/basic-ozone-layer-science>.
44. U.S. EPA. (2020). United States Environmental Protection Agency assigns pentane (isopentane) a GWP value of < 10. See EPA SNAP approved substitute list for polyisocyanurate (available at: <https://www.epa.gov/snap/substitutes-rigid-polyurethane-and-polyisocyanurate-laminated-boardstock#self>).

About WeatherBond Roofing Systems

WeatherBond is a leading supplier of single-ply roofing systems. These systems include EPDM, TPO, PVC and a full line of accessories for each membrane. WeatherBond empowers contractors and DIYers with the products, tools and resources they need to master single-ply roofing. With a commitment to and focus on training and innovation; and an ever-growing network of distributors; WeatherBond is dedicated to helping customers make the most out of these products. Additionally, WeatherBond offers unparalleled warranties for both commercial and residential applications. Offering both a material warranty and an extended warranty that includes labor costs, WeatherBond has a solution for all of your roofing system and warranty needs.



WEATHERBOND
ROOFING SYSTEMS

Single-Ply Simplified

P.O. Box 251 | Plainfield, PA 17081 | 866.471.5125 | FAX: 717.960.4034 | www.weatherbondroofing.com