

# EXSHAW CEMENT PLANT

ENVIRONMENTAL PRODUCT DECLARATION



[www.amrize.com](http://www.amrize.com)

**AMRIZE**

**BUILD YOUR AMBITION**



## ABOUT THIS EPD

This is a cradle-to-gate environmental product declaration for General Use (GU, Type I/II), High Sulphate (HS, Type V), General Use Limestone (GUL, Type IL), High Sulphate Limestone (HSL, Type IL – HS), High Early (HE, Type III), and Oil Well G (OWG) cements as produced at Amrize Canada's Exshaw, AB plant. The life cycle assessment was prepared according to ISO 14025:2006, ISO 21930:2017 (the core PCR) and the NSF product category rules for Portland, Blended, Masonry, Mortar and Plastic (stucco) Cements (subcategory PCR). This environmental product declaration (EPD) is intended for business-to-business audiences.

## GENERAL SUMMARY

EPD Commissioner and Owner



**Amrize Canada Inc.**  
#300 115 Quarry Park Road SE  
Calgary  
AB, T2C 5G9  
[www.amrize.com](http://www.amrize.com)

Amrize provided both LCI and meta-data for limestone quarrying, clinker production and cement manufacture for reference year 2020. The owner of the declaration is liable for the underlying information and evidence.

*For any explanatory material, regarding this EPD, please contact Matt Dalkie ([matt.dalkie@amrize.com](mailto:matt.dalkie@amrize.com)).*

Product Group and Name

Cement, UN CPC 3744.

Product Definition

**Portland Cement (GU, Type I/II, HE, Type III, HS, Type V):** a product obtained by pulverizing portland cement clinker consisting essentially of hydraulic calcium silicates, to which the various forms of calcium sulphate, up to 5% limestone, water, and processing additions may be added at the option of the manufacturer (CSA A3000, ASTM C150, ASTM C1157, AASHTO M85).

**Portland Limestone Cement (GUL, Type IL, HSL, Type IL – HS):** a product obtained by intergrinding portland cement clinker, to which the various forms of calcium sulphate, between 5 and 15% limestone, water, and processing additions may be added at the option of the manufacturer (CSA A3000, ASTM C595, ASTM C1157, AASHTO M240).

**Oil Well Cement (Class G):** a product obtained by pulverizing portland cement clinker consisting essentially of hydraulic calcium silicates, to which the various forms of calcium sulphate and water may be added at the option of the manufacturer (API Spec 10A).

Product Category Rules (PCR)

NSF International, Product Category Rules for Preparing an Environmental Product Declaration for Portland, Blended Hydraulic, Masonry, Mortar, and Plastic (Stucco) Cements, V3.2, September 2021.

Date of Issue & Validity Period

January 24, 2022 – 5 years

Declared Unit

1 metric tonne of cement





## EPD AND PROJECT REPORT INFORMATION

Program Operator	ASTM International
Declaration Number	EPD 290 – Amrize Exshaw Cement Plant
Declaration Type	Cradle-to-gate (modules A1 to A3). Facility and product-specific.
Applicable Countries	Canada and United States
Product Applicability	Cement is the basic ingredient of concrete. Concrete, one of the most widely used construction materials in the world, is formed when Portland cement creates a paste with water that binds with sand and rock to harden.
Content of the Declaration	This declaration follows Section 9; Content of an EPD, NSF International, Product Category Rules for Preparing an Environmental Product Declaration for Portland, Blended Hydraulic, Masonry, Mortar, and Plastic (Stucco) Cements, V3.2, September 2021.
This EPD was independently verified by ASTM in accordance with ISO 14025 and the reference PCR:	Tim Brooke ASTM International 100 Barr Harbor Drive PO Box C700 West Conshohocken PA 19428-2959, USA
Internal                      External X	<a href="mailto:cert@astm.org">cert@astm.org</a>
Notes	The LCA results are computed using the N.A. version 3.1 of GCCA Industry EPD tool for Cement and Concrete ( <a href="https://concrete-epd-tool.org">https://concrete-epd-tool.org</a> )
LCA report and EPD Prepared by:	Matt Dalkie Amrize Canada Inc. 7591 No 9 Rd Richmond BC, V6W 0A6

This EPD verified in accordance with ISO 14025, ISO 14040/44, and the reference PCR.

## PCR INFORMATION

Program Operator	NSF International
Reference PCR	Product Category Rules for Preparing an Environmental Product Declaration for Portland, Blended Hydraulic, Masonry, Mortar, and Plastic (Stucco) Cements, V3.2, September 2021.
PCR review was conducted by:	Thomas P. Gloria, PhD (Chair), Industrial Ecology Consultants, <a href="mailto:t.gloria@industrial-ecology.com">t.gloria@industrial-ecology.com</a> Mr. Jack Geibig, EcoForm Mr. Bill Stough, Sustainable Research Group



## AMRIZE AND PRODUCTION FACILITY

Facility Name: Amrize Exshaw Plant,  
Hwy 1A, Exshaw, AB, T0L 2C0

## PRODUCT DESCRIPTION

This EPD reports environmental transparency information for General Use (GU, Type I/II), High Sulphate (HS, Type V), General Use Limestone (GUL, Type IL), High Sulphate Limestone (HSL, Type IL – HS), High Early (HE, Type III), and Oil Well G (OWG) cements produced by Amrize at its Exshaw, AB plant. Cements are hydraulic binders and are manufactured by grinding cement clinker and other main or minor constituents into a finely ground, usually grey colored mineral powder. When mixed with water, cement acts as a glue to bind together the sand, gravel, or crushed stone to form concrete, one of the most durable, resilient, and widely used construction materials in the world. The table below sets out each cement type constituents and applicable standards. All Exshaw cements are sold in bulk.

## PRODUCTS AND STANDARDS

Inputs	General Use (GU) High Sulphate (HS)	General Use Limestone (GUL) High Sulphate Limestone (HSL)	High Early (HE)	Oil Well (OWG)
Standards	CSA A3001 ASTM C150 ASTM C1157 AASHTO M85	CSA A3001 ASTM C595 ASTM C1157 AASHTO M240	CSA A3001 ASTM C150 ASTM C1157 AASHTO M85	API Spec 10A
Clinker	92%	86%	91%	94%
Gypsum, Limestone	8%	14%	9%	6%
<b>Total</b>	<b>100%</b>	<b>100%</b>	<b>100%</b>	<b>100%</b>

### Applicable Standards:

CSA A3000-18 Cementitious Materials Compendium  
ASTM C150 / C150M – 21 Standard Specification for Portland Cement  
ASTM C595 / C595M – 21 Standard Specification for Blended Hydraulic Cements  
ASTM C1157 / C1157M – 20a Standard Performance Specification for Hydraulic Cement  
AASHTO M85-20 Standard Specification for Portland Cement  
AASHTO M240-20 Standard Specification for Blended Hydraulic Cement  
API Spec 10A – Cements and Materials for Well Cementing

## Environmental Product Declaration (EPD)

In accordance with ISO 14025 and 21930



### Note:

CSA cement type designations have been used throughout this document as the primary identifier. The equivalent types and classes under other standards are shown below. Cements are produced to meet all applicable standards shown.

Standard	GU	GUL	HE	HS	HSL	OWG
ASTM C150	Type I/II	N/A	Type III	Type V	N/A	N/A
ASTM C595	N/A	Type IL	N/A	N/A	Type IL – HS	N/A
ASTM C1157	Type GU	Type GU	Type HE	Type HS	Type HS	N/A
AASHTO M85	Type I/II	N/A	Type III	Type V	N/A	N/A
AASHTO M240	N/A	Type IL	N/A	N/A	Type IL – HS	N/A
API Spec 10A	N/A	N/A	N/A	N/A	N/A	Class G

## DECLARED UNIT

The declared unit is one metric tonne of cement.

## SYSTEM BOUNDARY

This cradle-to-gate EPD covering the production stage (LCA modules A1-A3) as depicted in the figure below. The production stage includes extraction of raw materials (cradle) through the manufacture of cements ready for shipment (gate). The Exshaw, AB cement plant sources its limestone supply from an adjacent quarry operated by Amrize.

Production			Construction		Use							End-of-Life				
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Extraction and upstream processing	Transport to factory	Manufacturing	Transport to site	Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction or demolition	Transport	Waste Processing	Disposal of waste	Optional information beyond system boundary

	Included in LCA scope
	Excluded from LCA scope

### Items excluded from the system boundary include:

- Production, manufacture, and construction of manufacturing capital goods and infrastructure
- Production and manufacture of production equipment, delivery vehicles, and laboratory equipment
- Personnel-related activities (travel, furniture, and office supplies)
- Energy and water use related to company management and sales activities that may be located either within the factory site or at another location

### Cut-off Criteria

The cut-off criteria as per NSF PCR, Section 7.1.8 and ISO 21930, 7.1.8 were followed. Per ISO 21930, 7.1.8, all input/output data required were collected and included in the LCI modelling. No substances with hazardous and toxic





properties that pose a concern for human health and/or the environment were identified in the framework of this EPD. Any plant specific data gaps for the reference year 2020 e.g. amount of lubricants and refractory were filled in with industry data (secondary data).

### Primary Data Collection

Gate-to-gate input/output flow data were collected for the following processes for the reference year 2020:

- Limestone quarry, clinker production and cement manufacture – Exshaw, AB.

Exshaw's direct greenhouse gas (GHG) emissions were calculated in accordance with Canada's Greenhouse Gas Reporting Program (GHGRP) as reported to the Province of Alberta and Government of Canada. Calcination emissions were calculated based on the Cement CO<sub>2</sub> and Energy Protocol detailed output method (B2) published by the World Business Council for Sustainable Development (WBCSD) Cement Sustainability Initiative (CSI).

## ALLOCATION RULES

Allocation follows the requirements and guidance of ISO 14044 Clause 4.3.4, NSF PCR, and ISO 21930 section 7.2. Recycling and recycled content are modeled using the cut-off rule. The sub-category PCR recognizes fly ash, furnace bottom ash, bypass dust, mill scale, polluted soils, spent catalyst, aluminum oxide waste, silica fume, granulated blast furnace slag, iron rich waste, cement kiln dust (CKD), flue gas desulfurization (FGD) gypsum, and calcium fluoride rich waste as recovered materials and thus the environmental impacts allocated to these materials are limited to the treatment and transportation required to use as a cement material input. Further, used tires, plastics, solvents, used oil and oily waste, coal/carbon waste, roofing asphalt, household refuse-derived waste and non-hazardous liquid waste are considered non-renewable and/or renewable secondary fuels. Only the materials, water, energy, emissions, and other elemental flows associated with reprocessing, handling, sorting and transportation from the point of the generating industrial process to their use in the production process are considered. All emissions from combustion at the point of use are considered.

## DATA QUALITY REQUIREMENTS AND ASSESSMENT

It should be noted that the data quality assessment here covers only the clinker and cement production inventories (i.e., activity data). An evaluation of the quality of data used to model background processes (e.g., electricity generation) has also been carried out, and the results are located in the *LCA core model and database report* of the *U.S. version of GCCA tool for EPDs of concrete and cement*.

Data Quality Requirements	Description
Technology Coverage	Data represents the prevailing technology in use at the Exshaw, AB facility. The Exshaw, AB plant utilizes <i>pre-calcliner kiln technology</i> . <i>Technological representativeness is characterized as "high"</i> .
Geographic Coverage	The geographic region considered is Canada. The electricity was modelled based on the AESO 2020 grid mix for AB, consisting of 45.8% gas, 35.1% coal, 10.6% wind, 4.9% oil, 3.5% hydro, and 0.2% solar generation. <i>Geographical representativeness is characterized as "high"</i> .





<b>Time Coverage</b>	<p>Activity (primary) data are representative of 2020 calendar year (12 months).</p> <ul style="list-style-type: none"> <li>- Exshaw, AB limestone extraction,</li> <li>- Exshaw, AB clinker production,</li> <li>- Exshaw, AB cement manufacturing,</li> <li>- In-bound/out-bound transportation data - primary data collected for Exshaw, AB quarry site and cement manufacturing plant.</li> <li>- Total carbon dioxide emissions from fuel use and calcination were reported for clinker production as part of the facility data collection.</li> </ul> <p><i>Temporal representativeness is characterized as “high”.</i></p>
<b>Completeness</b>	<p>All relevant, specific processes, including inputs (raw materials, energy, and ancillary materials) and outputs (emissions and production volume) were considered and modelled to complete production profile for Exshaw cement products.</p>
<b>Consistency</b>	<p>To ensure consistency, the modeling of the production input and output LCI data for the Exshaw cement products of interest used the same LCI modeling structure, which consisted of input material and intermediate products, ancillary and packaging materials (if applicable), energy flows, water resource inputs, product outputs, co-products, by-products, emissions to air, water and soil, and solid and liquid waste disposal. The calculated LCI was subsequently inputted into the N.A. version of GCCA Industry EPD tool for Cement and Concrete (<a href="https://concrete-epd-tool.org">https://concrete-epd-tool.org</a>)</p> <p>Crosschecks concerning the plausibility of mass and energy flows were continuously conducted. The LCA team conducted mass and energy balances at the facility level and selected process levels to maintain a high level of consistency.</p>
<b>Reproducibility</b>	<p>Internal reproducibility is possible since the data and the models are stored the N.A. version of GCCA Industry EPD tool for Cement and Concrete (<a href="https://concrete-epd-tool.org">https://concrete-epd-tool.org</a>). Key primary (manufacturer specific) and secondary (generic) LCI data sources are also summarized in the GCCA Tool documentation. External reproducibility is not possible as the background report is confidential.</p>
<b>Transparency</b>	<p>Activity and LCI datasets are disclosed in the project report, including all data sources.</p>

## LIFE CYCLE IMPACT ASSESSMENT RESULTS

This section summarizes the production stage life cycle impact assessment (LCIA) results including resource use and waste generated metrics based on the cradle-to-gate life cycle inventory inputs and outputs analysis. The results are calculated based on 1 metric tonne of each cement type as produced at the Exshaw, AB plant.

*It should be noted that LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks. Further, a number of LCA impact categories and inventory items are still emerging or under development and can have high levels of uncertainty that preclude international acceptance pending further development. Use caution when interpreting results for these categories – identified with an “\*”.*

Only EPDs prepared from cradle-to-grave life-cycle results and based on the same function, quantified by the same functional unit, and taking account of replacement based on the product reference service life (RSL) relative to an assumed building service life, can be used to assist purchasers and users in making informed comparisons between products. Environmental declarations from different programs may not be comparable. EPDs are comparable only if they comply with ISO 21930, use the same, sub-category PCR where applicable, include all relevant information modules and are based on equivalent scenarios with respect to the context of construction works.



**Production Stage EPD Results: Exshaw, AB— per metric tonne**

Impact category and inventory indicators	Unit	GU / HS	GUL / HSL	HE	OWG
Global warming potential, GWP 100, AR5	kg CO <sub>2</sub> eq	838	788	858	860
Ozone depletion potential, ODP	kg CFC-11 eq	2.81E-5	2.68E-5	3.12E-5	2.86E-5
Smog formation potential, SFP	kg O <sub>3</sub> eq	36.0	34.0	36.7	36.8
Acidification potential, AP	kg SO <sub>2</sub> eq	2.89	2.73	2.97	2.96
Eutrophication potential, EP	kg N eq	0.832	0.807	1.022	0.849
Abiotic depletion potential for non-fossil mineral resources, ADP elements*	kg Sb eq	1.49E-4	1.47E-4	1.76E-4	1.51E-4
Abiotic depletion potential for fossil resources, ADP fossil	MJ NCV	816	773	844	835
Renewable primary resources used as an energy carrier (fuel), RPRE*	MJ NCV	103	100	128	105
Renewable primary resources with energy content used as material, RPRM *	MJ NCV	0	0	0	0
Non-renewable primary resources used as an energy carrier (fuel), NRPRE*	MJ NCV	5700	5405	6066	5839
Non-renewable primary resources with energy content used as material, NRPRM *	MJ NCV	0	0	0	0
Secondary materials, SM *	kg	104.5	95.6	99.9	104.3
Renewable secondary fuels, RSF *	MJ NCV	0	0	0	0
Non-renewable secondary fuels, NRSF *	MJ NCV	0	0	0	0
Recovered energy, RE *	MJ NCV	0	0	0	0
Consumption of freshwater, FW	m <sup>3</sup>	0.985	1.00	1.10	1.00
Hazardous waste disposed, HWD *	kg	1.92E-3	1.86E-3	1.91E-3	1.95E-3
Non-hazardous waste disposed, NHWD*	kg	1.13E-2	1.07E-2	1.12E-2	1.15E-2
High-level radioactive waste, conditioned, to final repository, HLRW *	m <sup>3</sup>	x	x	x	x
Intermediate- and low-level radioactive waste, conditioned, to final repository, ILLRW *	m <sup>3</sup>	x	x	x	x
Components for re-use, CRU *	kg	0	0	0	0
Materials for recycling, MR *	kg	0.105	0.101	0.104	0.108
Materials for energy recovery, MER *	kg	0	0	0	0
Recovered energy exported from the product system, EE *	MJ NCV	0	0	0	0
<b>Additional Inventory Parameters for Transparency</b>					
Emissions from calcination	kg CO <sub>2</sub> eq	491	459	484	505
Biogenic CO <sub>2</sub> , reporting the removals and emissions of biogenic carbon within biobased	kg CO <sub>2</sub> eq	0	0	0	0

**Table Notes:**

- 1) (x) Not all LCA datasets for upstream materials include these impact categories and thus results may be incomplete.
- 2) (\*) Use caution when interpreting results for these categories.





## LCA INTERPRETATION

The Manufacturing module (A3) drives most of the potential environmental impacts. Manufacturing impacts are primarily driven by energy use (electricity and thermal fuels) used during the pyroprocessing of limestone in the production of clinker. Clinker content in cement similarly defines the relative environmental profile of the final cement product. Raw material extraction (A1) is the second largest contributor to the Production stage EPD results, followed by the transportation (A2).

## LIMITATIONS AND DISCLAIMER

Environmental declarations from different programs (ISO 14025) may not be comparable. Comparison of the environmental performance of products using EPD or ED information shall be based on the product's use and impacts at the building or construction works level, and therefore EPDs and EDs may not be used for comparability purposes when not considering the whole building life cycle. EPD and ED comparability is only possible when all stages of a life cycle have been considered. However, variations and deviations are possible. Example of variations: Different LCA software and background LCI datasets may lead to differences in results upstream or downstream of the life cycle stages declared.

The environmental impact results of products in this document are based on a declared unit and therefore do not provide sufficient information to establish comparisons. The results shall not be used for comparisons without knowledge of how the physical properties of the product impact the precise function at the construction level. The environmental impact results shall be converted to a functional unit basis before any comparison is attempted.

Amrize Canada Inc. believes the information contained in, and used in the creation of, this EPD is accurate, however Amrize Canada Inc. makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein, which is not intended to be and should not be construed as legal advice or ensuring compliance with any federal, provincial, state or local laws or regulations. Further and for certainty, Amrize Canada Inc. assumes no liability whatsoever in respect of the calculations presented herein or in connection with the tools, software or processes used to produce such calculations. Any party using this EPD or the product for which it is prepared should review all laws, rules or regulations applicable to such party and/or product, and each such party is solely responsible for its reliance on, decisions made based on, or actions taken as a result of the use of the information in this EPD.

NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE MADE, AND ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED.

## REFERENCES

1. CSA A3000-18 Cementitious materials compendium
2. ASTM C150/C150M-21, Standard Specification for Portland Cement
3. ASTM C595/C595M-21, Standard Specification for Blended Hydraulic Cements
4. AASTHO M85 - 20, Standard Specification for Portland Cement
5. AAHTO M240M/M240 -20, Standard Specification for Blended Hydraulic Cement
6. API Spec 10A, Cements and Materials for Well Cementing
7. NSF International, Product Category Rule Environmental Product Declarations, PCR for Portland, Blended, Masonry, Mortar, and Plastic (Stucco) Cements, V3.2, September 2021.
8. ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products and services.
9. ISO 14040:2006 Environmental management - Life cycle assessment - Principles and framework.

## Environmental Product Declaration (EPD)

In accordance with ISO 14025 and 21930



10. ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
11. ISO 14025:2006 Environmental labeling and declarations - Type III environmental declarations - Principles and procedures.
12. ISO 14021:2016 Environmental labels and declarations -- Self-declared environmental claims (Type II environmental labelling).
13. ASTM General Program Instructions, v8.0, April 29, 2020.
14. GCCA CO<sub>2</sub> and Energy Protocol Version 3.1 of 9 December 2013.  
(<https://www.cement-co2-protocol.org/en/>) accessed 08-2021.
15. GCCA Industry EPD tool for Cement and Concrete, N.A. version 3.1  
(<https://concrete-epd-tool.org>) accessed 11-2021
16. GCCA Industry EPD tool for Cement and Concrete (v3.1) LCA Model, North American Version, November 10, 2021