


Environmental Product Declaration

Imperial® Veneer Finish

Shoals, IN

For strong, abrasion-resistant interior finishes

- Durable and stable. Imperial® brand veneer finish offers the durability needed in high-traffic areas.
- Economical construction. Substantial savings in finishing materials and application time.
- Fast finishing. Imperial veneer finish is usually ready for next-day decoration with a latex-based breather-type paint.
- Provides noncombustibility. When used with Imperial® brand gypsum base, Imperial plaster systems provide fire-resistant construction.



Declared Unit – 1 tonne

(A1-A3) Cradle-to-Gate

 Global Warming Potential -Total¹ (kg CO₂ eq.)¹	1.35E+02
Ozone Depletion Potential (kg CFC-11 eq.)²	3.05E-08
Acidification Potential (kg SO₂ eq.)¹	1.74E-01
Eutrophication Potential – Freshwater (kg P eq.)¹	2.82E-04
Eutrophication Potential – Marine (kg N eq.)¹	9.70E-02
Photochemical Ozone Creation Potential (kg O₃ eq.)¹	3.22E+00
Abiotic Resource Depletion Potential Fossil Fuels (MJ, LHV)²	2.05E+03

1 TRACI 2.2

2 CML 2001; Aug. 2016

Imperial® Veneer Finish

Shoals, IN

This declaration is an Environmental Product Declaration (EPD) in accordance with ISO 14025 and ISO 21930: 2017. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds – e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. USG Corporation has sole ownership, liability, and responsibility for this EPD.

The owner of the declaration shall be liable for the underlying information and evidence; ASTM, or its affiliates, shall not be liable with respect to manufacturer information, life cycle assessment data, and evidence.

DECLARATION NUMBER	EPD 1024	
EPD TYPE	Product specific, facility specific EPD	
PROGRAM OPERATOR	ASTM International – 100 Barr Harbor Drive, West Conshohocken, PA USA www.astm.org	
DECLARATION HOLDER	USG Corporation - 550 W. Adams St., Chicago, IL USA	
EPD Type	Type III Declaration per ISO 14025:2006	
DECLARED PRODUCT	Imperial® Veneer Finish	
DATE OF ISSUE PERIOD OF VALIDITY	6/18/25 5 Years	
MARKETS OF APPLICABILITY	North America	
CORE PCR	ISO 21930: 2017	
SUB-CATEGORY PCR	NSF International, PCR for Portland, Blended, Masonry, Mortar and Plastic (Stucco) Cements, v3.2 September 2021, Validity extended to December 31, 2025.	
SUB-CATEGORY PCR REVIEW	Dr. Thomas P. Gloria, Industrial Ecology Consultants t.gloria@industrial-ecology.com	
ACLCA PCR OPEN STANDARD CONFORMANCE	Transparency	
ACLCA PCR OPEN STANDARD VERSION	Version 1.0 May 25, 2022	
This declaration was independently verified in accordance with ISO 14025 and ISO 21930:2017 ☐ INTERNAL ☒ EXTERNAL		Tim Brooke, ASTM International
This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:		Thomas P. Gloria, Industrial Ecology Consultants

Imperial® Veneer Finish

Shoals, IN

1. Product System Documentation

1.1 Product Description and Product Identification

USG Imperial® veneer finish is a high-strength veneer plaster designed for single-coat application over Imperial® gypsum base, or as a high-strength finish over veneer or conventional high-strength sanded basecoats. Applied in 1/16" to 3/32" thicknesses, it is formulated for hand application. It produces a hard, 3,000 lb./in.² compressive strength, abrasion-resistant finished surface. Imperial veneer finish may be used in one-coat work or as a finish over Imperial® veneer basecoat in two-coat work, or as a finish over Diamond® veneer basecoat applied to either Durock® brand cement board or Fiberock® brand abuse-resistant panels treated with USG™ plaster bonder. Smooth-trowel or texture finishes are recommended. Imperial veneer finish over Imperial or Diamond veneer basecoats should be selected when very high surface hardness and abrasion resistance is desired in a two-coat veneer system. Though easily textured, smooth-coat finishing is achieved by ensuring that the initial application is completed with minimal lap marks and voids, as this product's hardness makes it difficult to remove blemishes and cat faces during final troweling. It is also suitable as a finish applied to job-sanded Structo-Base® gypsum plaster to provide the ultimate in surface hardness with conventional plaster assemblies.

1.2 Designated Application

Imperial® veneer finish over Imperial or Diamond veneer basecoats should be selected when very high surface hardness and abrasion resistance is desired in a two-coat veneer system.

1.3 Product Technical Data

Table 1: Performance Data

Technical Data	Approximate Values Standard (Metric)
Coverage	Covers approximately 3,500 – 4,000 sq. ft. per ton.
Compliance with standards	Meets ASTM Designation C587
Storage	Store material in a cool, dry place. Avoid direct sunlight. Maintain temperature above 40 °F (4 °C).
Shelf Life	Up to 6 months under protected storage conditions. Rotate stock.
Packaging	Available in 50 lb. (22.7 kg) bags.

1.4 Placing on the Market/Application Rules

USG Imperial® Veneer Finish is sold to distributors and installed by hand application over USG Sheetrock® Brand Gypsum Base or as a high-strength finish over veneer or conventional high-strength sanded basecoats.

Imperial® Veneer Finish

Shoals, IN

1.5 Product Composition

Table 2: Product Composition

Material	Imperial® Veneer Finish
Calcium Sulfate Hemihydrate	> 65%
Sand	< 35%
Additives	< 5%

1.6 Product Manufacturing

The manufacture of USG Imperial® Veneer Finish consists of the blending of the dry ingredients followed by packaging into multi-walled paper bags. The finished product is then stacked on wooden pallets and wrapped with a plastic cover bag.

1.7 Environment and Health During Manufacturing

USG and CGC have led the building sector's efforts in developing and supplying sustainable construction materials. Today, sustainability is integrated into the design and manufacture of every wall, ceiling, and flooring product. As both a producer and a buyer of raw materials, we have a responsibility to extensively review and select each material we use. Each decision we make is based on careful consideration of environmental and safety effects over time. Raw materials used in our products are carefully selected and go through a screening procedure. Incoming raw materials are tested for contaminants by an internal lab and third-party labs for consideration of use and worker, environmental, and end-user exposure. This due diligence helps to ensure our products are safe to handle in our manufacturing plants and on job sites while having minimal impact on occupant health and indoor and outdoor environments.

1.8 Packaging

USG Imperial® Veneer Finish is packaged in 50 lb. multiwall paper bags. The finished product is then stacked on wooden pallets and wrapped with a plastic cover bag. All packaging components have been modeled in this study.

1.9 Conditions of Use

To ensure the longevity of the product, products should not be exposed to moisture, high humidity, or high temperature. Criteria can be found in USG warranty information specific to each product.

1.10 Reference Service Life

The Reference Service Life is considered not to be relevant for this cradle-to-gate study.

1.11 Documentation on Additional Environmental Information

There are no regulated waste substances of very high concern to be declared.

2 LCA Calculation Methodology

2.1 Declared Unit

The declared unit for this LCA study is one metric tonne of product.


Table 3: Declared Unit

	Value and Units
Declared Unit	1,000 kg
Declared Unit	2,205 lbs.

3 System Boundary

This EPD represents a “cradle-to-gate” LCA analysis for USG Imperial® Veneer Finish. It covers all the production steps from raw material extraction (i.e., the cradle) to finished product on wooden pallets (i.e., the gate).

Figure 1: Specific processes covered by this EPD by life cycle stage



3.1 Estimates and Assumptions

These plaster products are USG products with well-defined formulations, energy inputs and raw material transport distances. No significant assumptions were required. All material and energy inputs were accounted for as were the raw material transportation mode and distances. Additional data limitations included the use of proxy processes rather than actual supplier generated primary data. This would include such processes as sand, which is representative of US-produced sand but may not necessarily be representative of USG's particular sand supplier. In addition, the data is limited in that the primary data was collected during the year 2024 and changes in operations may increase/decrease impacts in the future. Other data limitations include the use of secondary data sets instead of primary data for upstream and downstream processes, local impacts vs. global impacts, possible impacts vs. actual impacts, inherent uncertainty in the data sets, accuracy, and precision of impacts assessment methodology, etc.

3.2 Cut-off Criteria

All inputs and outputs to a (unit) process were included in the calculation for which data is available. In case of insufficient input data or data gaps for a unit process, the cut-off criteria was 1% of renewable and non-renewable primary energy usage and 1% of the total mass of that unit process. The total neglected input flows did not exceed 1% of energy usage and mass.

3.3 Background Data

All background data was sourced from critically reviewed LCA for Experts databases.

Data Requirements and Data Sources

The LCA model was created using LCA for Experts software (version 10.9.1.10) from Sphera. Specific comments related to data quality requirements cited in ISO 14025 Section 4.2.3.6.2 include the following.

Temporal: In the case of production, the LCI data was collected from the manufacturing plants for the 2024 production year.

Geographical: Where possible, all processes were chosen as being representative of US manufacturing processes.

Technical: The data selected for this study is specific to the technology used in the preparation of the various raw materials.

Precision: The raw material usage amounts were derived from plant quality data on finished products, energy usage plant data and product formulas.

Completeness: Virtually all the significant raw material flows (> 99%) used in production have been modeled. The exception consists of retarders which are biopolymers derived from animal byproducts.

Representative: Where possible all the data sets were selected to be representative of US-based production, are less than 10 years in age and are representative of the technology being employed.

Consistency: All the manufacturing processes were modeled in a consistent manner throughout this study in accordance with the goal and scope definitions.

Reproducibility: The information contained in this study, including raw material, energy and transportation distance inputs, have been fully documented in the LCA report.

Sources of Data: The sources for the processes used in this study have been fully provided in the LCA report and are representative of the material and energy sources used in actual production.

Uncertainty: The relative uncertainty associated with this study has been minimized. No significant assumptions have been made.

Allocation

At each production facility, energy was allocated to each department based on usage. The LCI product formula data was collected for the 2024 production year. The LCI product mining data was collected for the 2021 production year.

4. LCA: Scenarios and Additional Technical Information

Product Stage			Construction Process stage		Use							End of Life Stage			
Raw Material Supply	Transport	Manufacturing	Transport	Construction-Installation Process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy Use	Operational water Use	De-construction Demolition	Transport	Waste Processing	Disposal
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND

Figure 2: System Boundary

5. Life Cycle Assessment Results

5.1 LCA Results

Note: Global Warming Potential – Total (GWP – Total) is the sum of the contributions from fossil fuels (GWP – Fossil), biogenic carbon (GWP – Biogenic) and land use change (GWP – Land Use Change)

Table 4: North American LCA Environmental Impacts – 1 Tonne of Imperial® Veneer Finish

Impact Category	Units	A1	A2	A3	A1-A3
Global Warming Potential – Total ¹	kg CO ₂ eq.	1.15E+02	3.55E-01	1.90E+01	1.35E+02
Ozone Depletion Potential (ODP) ¹	kg CFC-11 eq.	1.41E-10	1.01E-13	3.03E-08	3.05E-08
Acidification Potential (AP) ¹	kg SO ₂ eq.	1.17E-01	1.58E-03	5.51E-02	1.74E-01
Eutrophication Potential – Freshwater ¹	kg P eq.	2.10E-04	2.92E-07	7.13E-05	2.82E-04
Eutrophication Potential – Marine ¹	kg N eq.	6.73E-02	1.46E-03	2.82E-02	9.70E-02
Photochemical Ozone Creation Potential (POCP) ¹	kg O ₃ eq.	2.16E+00	5.28E-02	1.00E+00	3.22E+00
Abiotic Depletion Potential (ADP) fossil fuels ²	MJ	1.65E+03	4.57E+00	3.99E+02	2.05E+03

The LCIA characterization factors used in this study were taken from the following sources.

1 TRACI 2.2

2 CML 2001; Aug. 2016

Imperial® Veneer Finish

Shoals, IN

Table 5: Resource and Waste Flows for 1 Tonne of Imperial® Veneer Finish

Use of Primary Resources	Units	A1	A2	A3	A1-A3
Renewable primary resources used as an energy carrier (RPRE)	MJ, NCV	2.24E+02	1.92E-01	2.73E+02	4.97E+02
Renewable primary resources with energy content used as material (RPRM)	MJ, NCV	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Non-renewable primary resources used as an energy carrier (NRPRE)	MJ, NCV	1.93E+03	4.61E+00	5.51E+02	2.49E+03
Non-renewable primary resources with energy content used as material (NRPRM)	MJ, NCV	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Secondary material, fuel, and recovered energy	Units	A1	A2	A3	A1-A3
Secondary material (SM)	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renewable secondary fuel (RSF)	MJ, NCV	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Non-renewable secondary fuel (NRSF)	MJ, NCV	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renewable energy (RE)	MJ, NCV	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Consumption of fresh water	m ³	3.70E-01	2.07E-04	1.32E-01	5.02E-01
Emissions inventory parameters for transparency	Units	A1	A2	A3	A1-A3
Biogenic carbon content of product	kg CO ₂ eq.	-7.82E+00	0.00E+00	0.00E+00	-7.82E+00
Calcination uptake from carbonation	kg CO ₂ eq.	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon of bio-based packaging	kg CO ₂ eq.	0.00E+00	0.00E+00	-1.29E+01	-1.29E+01
Combustion of waste from renewable sources used in production	kg CO ₂ eq.	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Combustion of waste from non-renewable sources used in production	kg CO ₂ eq.	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Indicators describing waste	Units	A1	A2	A3	A1-A3
Hazardous waste disposed	kg	4.86E-07	7.64E-10	9.07E-05	9.12E-05
Non-hazardous waste disposed	kg	9.86E-01	4.72E-04	3.71E-01	1.36E+00
High-level radioactive waste	kg	1.01E-01	1.58E-05	5.40E-02	1.55E-01
Intermediate and low-level waste	kg	N/A	N/A	N/A	N/A
Assignments of output flows at the end-of-life	Units	A1	A2	A3	A1-A3
Components for re-use (CRU)	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling (MR)	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for energy recovery (MER)	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Recovered energy exported (EE)	MJ, NCV	0.00E+00	0.00E+00	0.00E+00	0.00E+00

5.2 LCA Results


Comparisons cannot be made between product-specific or industry average EPDs at the design stage of a project, before a building or construction works has been specified. Comparisons may be made between product-specific or industry average EPDs at the time of product purchase only when product or construction works performance and specifications have been established and serve as a functional unit for comparison.

Environmental impact results shall be converted to a functional unit basis before any comparison is attempted. Any comparison of EPDs shall be subject to the requirements of ISO 21930. EPDs are not comparative assertions and are either not comparable or have limited comparability when they have different system boundaries, are based on different product category rules or are missing relevant environmental impacts. Such comparisons can be inaccurate and could lead to an erroneous selection of materials or products that have higher impact, at least in some impact categories.

5.3 LCA Interpretation

The LCA results for the production of 1 tonne of Imperial® Veneer Finish (A1-A3) produced at the Shoals, IN plant were dominated by calcium sulfate hemihydrate usage. Future efforts to reduce the GWP for these products should focus on the formula; specifically the use of high-impact calcium sulfate hemihydrate.

Figure 3: Process Dominance Analysis for GWP for the Production of 1 Tonne of Imperial® Veneer Finish (A1-A3) – Shoals, IN Plant



6. References

LCA Report

A Cradle-to-Gate Life Cycle Assessment of USG Building Plaster Products, 4/29/25. USG (Confidential)

Product PCR

NSF International, PCR for Portland, Blended, Masonry, Mortar, and Plastic (Stucco) Cements, v3.2 September 2021. Validity extended to December 31, 2025.

ASTM Program Instructions, v8.0, 4/29/2020, ASTM International

Sustainability Reporting Standards

ISO 14025:2006 - Environmental labels and declarations — Type III environmental declarations — Principles and procedures

ISO 14040:2006/Amended 1:2020 - Environmental management – Life cycle assessment – Principles and framework

ISO 14044:2006/Amended 2:2020 - Environmental management – Life cycle assessment – Requirements and guidelines

ISO 14046:2014 - Environmental management- Water footprint- Principles, requirements and guidelines

ISO 15392:2008 - Sustainability in building construction- General principles

ISO 15686-1:2011 - Buildings and constructed assets- Service life planning- Part 1: General principles

ISO 15686-2:2012 - Buildings and constructed assets- Service life planning Part 2: Service life prediction procedures

ISO 15686-7:2017 - Buildings and constructed assets- Service life planning Part 7: Performance evaluation for feedback of service life data from practice

ISO 15686-8:2008 - Buildings and constructed assets- Service life planning Part 8: Reference service life and service life estimation

ISO 21930:2017 - Sustainability in buildings and civil engineering works — Core rules for environmental product declarations of construction products and services