

Environmental Product Declaration



Log and Timber
Homes Council

A Cradle-to-Gate EPD of Sawn timber framing products (STF)





According to
ISO 21930
ISO 14025
ISO 14040/44



| Summary Results –per m ³ Full Results in Table 1 | | Cradle-to-Gate Total |
|---|----------------------|----------------------|
| Global warming potential | kg CO ₂ e | 1.34E+02 |
| Acidification potential of soil and water sources | kg SO ₂ e | 2.19E-01 |
| Eutrophication potential | kg Ne | 2.30E-02 |
| Depletion potential of the stratospheric ozone layer | kg CFC11e | 1.12E-09 |
| Formation potential of tropospheric ozone | kg O ₃ e | 4.59E+00 |
| Abiotic depletion potential (ADP _{fossil}) for fossil resources | MJ, NCV | 3.26E+02 |

1.0 General Information

| | |
|--|---|
| EPD Program and Program Operator | ASTM International 100 Barr Harbor Drive PO Box C700 West Conshohocken, PA, 19428-2959 USA www.astm.org  ASTM INTERNATIONAL Helping our world work better |
| General Program Instructions and Version Number | ASTM Program Operator for Product Category Rules (PCR) and Environmental Product Declarations (EPDs) - General Program Instructions, version: 6.0 |
| Manufacturer | National Association of homebuilders National Housing Center 1201 15th Street, NW Washington, DC 20005 https://nwfa.org  Log and Timber Homes Council |
| Declaration Number | EPD 1000 |
| Declared Product | Sawn timber framing products (STF) |
| Declared Unit | 1 m ³ of STF produced. |
| Reference PCR and Version Number | ISO 21930:2017 Sustainability in Building Construction — Environmental Declaration of Building Products. [7] ISO 14040/44:2006 Underwriters Laboratory, Product Category Rule for Architectural and Structural Wood Products. Version 1.1. (2020) |
| Markets of Applicability | Construction Sector, Building homes |
| Date of Issue | 25.09.2025 |
| Period of Validity | 24.09.2030 |
| EPD Type | Industry Average EPD |

| | | | |
|---|--|---|---|
| EPD Scope | | Cradle-to-Gate | |
| Year of reported manufacturer primary data | | 2019 | |
| LCA Software | | SimaPro v9.2 | |
| LCI Databases | | USLCI [9], Ecoinvent 3.9 [15], Datasmart 2023[8] | |
| LCIA Methodology | | TRACI 2.1 [3] | |
| The sub-category PCR review was conducted by: | | Jack Geibig, Chair Ecoform | Dr. Thomas Gloria Industrial Ecology Consultants Thaddeus Owen |
| LCA and EPD Developer This life cycle assessment was conducted in accordance with ISO 14044 and the reference PCR by: | | <div><div><div>Athena Sustainable Materials Institute</div><div>100 Broadview Avenue, Suite 909</div><div>Ottawa, ON K1S 5P6</div><div>https://www.athenasmi.org/</div><div>Athena</div></div><div><div><div>Athena</div><div>Sustainable Materials</div><div>Institute</div></div></div></div> | |
| This declaration was independently verified in accordance with ISO 14025:2006[4] . Environmental declarations from different programs (ISO 14025) may not be comparable. The UL Environment “Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report,” v3.2 (September 2018), based on ISO 21930:2017 and CEN Norm EN 15804 (2012) , serves as the core PCR, with additional considerations from the USGBC/UL Environment Part A Enhancement (2017) . <div><input type="checkbox"/> INTERNAL<input checked="" type="checkbox"/> EXTERNAL</div> | | | |
| Independent Verifier This life cycle assessment was independently verified in accordance with ISO 14044 [6] and the reference PCR by: | | <div><div>Tim Brooke</div><div>100 Barr Harbor Drive</div><div>PO Box C700</div><div>West Conshohocken, PA,</div><div>19428-2959 USA</div><div>www.astm.org</div></div> | |
| LCA and EPD Manufacturer Participants | | | |
| <div><div></div><div>Log and Timber Homes Council</div></div> | | | |

About the National Wood Flooring Association

NAHB collaborates with industry partners to quantify and report the environmental impact of building materials and products. For example, in the LCA report you shared, NAHB commissioned the Athena Sustainable Materials Institute to conduct a cradle-to-gate LCA of log home and timber frame products. The study was aligned with the association’s goal of promoting sustainable building practices and creating transparency in environmental impacts across the construction sector. Through such initiatives, the NAHB supports efforts toward more sustainable construction practices by providing detailed data on environmental performance to industry stakeholders, including architects, policymakers, and manufacturers. This EPD initiative helps builders meet criteria for sustainable building certifications like LEED and Green Globes, advancing environmentally friendly construction practices in North America. Detailed information about NAHB can be found at <https://www.nahb.org/>

2. PRODUCT DESCRIPTION

Sawn Timber Framing Products (STF)

Sawn Timber Framing (STF) products are precision-cut wood components used in structural applications for residential, commercial, and industrial buildings. These timber products offer excellent load-bearing capacity and much more economically friendly than any laminated products in the market. Also, timber products are far better than laminated products in terms of carbon footprint which improves the environmental performance of the product. STF products are valued for their durability, versatility, ease of use, and ability to seamlessly integrate into various architectural designs.

STF Product Variations

Full conformance with the PCR for wood products allows EPD comparability only when all life cycle stages (A1 to C4 and beyond, if applicable) have been considered, when EPDs comply with all referenced standards, utilize the same sub-category Part B PCR, and apply equivalent scenarios related to the construction works. It is important to note that variations and deviations may still occur.

STF products are available in different variations to meet diverse construction needs. Key variations include:

- **Dimensions:** Available in a range of standardized and custom sizes to fit various structural applications.
- **Species:** Manufactured from both softwoods (e.g., pine, spruce) and hardwoods (e.g., oak, maple) to provide the desired strength and performance.
- **Surface Finish:** Offered in smooth, planed, or rough-sawn finishes to suit aesthetic or functional requirements.
- **Joinery Options:** Customizable for tight-fitting joints, including mortise-and-tenon or lap joints, to enhance structural stability.

Source of Timber and Sustainability

STF products are made from timber sourced from sustainably managed forests in North America. Production practices align with sustainable forestry management to ensure minimal environmental impact. Key aspects include:

- **Sustainable Growth:** Timber harvesting follows sustainable forestry practices, ensuring that forest growth outpaces harvesting rates.
- **Selective Harvesting:** Practices like selective logging help maintain forest health and biodiversity while preventing clear-cutting.
- **Common Species:** STF products commonly use species like pine, fir, spruce, and oak, valued for their strength, durability, and suitability for framing.

3. METHODOLOGY

The underlying LCA investigates the lifecycle stages of Sawn Round Timber Framing Products production in the United States and Canada from cradle-to-gate.

System Boundaries and Product Flow Diagram

The scope for Sawn Timber Framing (STF) products follows a cradle-to-gate system boundary, encompassing environmental impacts from raw material extraction to the finished product ready for shipment. It includes three modules: A1 – Raw Material Production, covering log harvesting, nursery operations, reforestation, thinning, fertilization, and preparation of secondary materials; A2 – Raw Material Transportation, which details the movement of logs and inputs to manufacturing facilities via trucks, rail, or ships; and A3 – Manufacturing, which involves sawing logs to precise dimensions, applying finishes such as planing or rough-sawing, and packaging the products for

delivery. The manufacturing process consumes energy in the form of electricity, propane, and wood fuels, along with consumables such as motor oil, hydraulic fluids, and fasteners. It also generates co-products like sawdust and wood chips, which are reused for bioenergy or sold to other industries. This cradle-to-gate system ensures a detailed and transparent assessment of the environmental impacts associated with STF products, promoting sustainable construction practices and environmentally conscious decision-making.

| Building Life Cycle Information Modules | | | | | | | | | | | | | | | | |
|---|----------------------|---------------|--------------------|--------------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|--------------------------------|--------------------|------------------|----------|-------------------------|
| Production stage | | | Construction Stage | | Use stage | | | | | | | End-of-life stage | | | | Substitution Effects |
| Extraction and upstream production | Transport to factory | Manufacturing | Transport to site | Installation | Use | Maintenance | Repair | Replacement | Refurbishment | Operational Energy Use | Operational Water Use | De-Construction/ Demolition | Transport to waste | Waste processing | Disposal | Benefits Outside System |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | . | . | . | . | . | . | . | . | . | . | . | . | . | . |

Figure 2: Life Cycle Stages and Information Modules per ISO 21930:2017

Construction and Service Life Assumptions

The construction and service life assumption aligns with typical building industry standards. While the report emphasizes the cradle-to-gate scope, meaning that the product's full lifecycle (including end-of-life) is not assessed here, the data suggests that SRT products have a long service life, contributing to their sustainability performance.

Declared Unit

The declared unit for the SRT product is defined as one cubic meter (1 m³) of sawn timber framing. This unit provides a consistent basis for measuring the product's environmental impact across different stages of production. The STF product system primarily consists of wood with a density of 439.8 dry kg/m³.

Data Sources

The data sources for this study include both primary data collected directly from eight manufacturing facilities across North America and secondary data from publicly available databases such as DATASMART 2023 and Ecoinvent 3.9. Primary data reflects facility-specific information on energy use, material inputs, and manufacturing processes for the 2021 production year. Secondary data covers aspects such as transportation and raw material extraction.

Treatment of Biogenic Carbon

The report follows the guidelines of UL PCR Part B and ISO 21930 to account for biogenic carbon. North American forests are assumed to have a neutral forest carbon stock, meaning that the biogenic CO₂ emitted during biomass combustion (e.g., for kiln-drying) does not contribute to the overall global warming potential. Although the cradle-to-gate scope of this study does not cover end-of-life emissions, the biogenic carbon stored in the product is quantified as 806.31 kg CO₂ equivalent per m³ (assuming 50% carbon content). This ensures that the carbon sequestration within the wood product is transparently reported and can be used in future cradle-to-grave

assessments Biogenic carbon emissions and removals are reported in accordance with ISO 21930 7.2.7. and 7.2.12. Detailed information is provided in Section 4 of the underlying LCA.

Allocation Procedures:

Allocation procedures are conducted in accordance with ISO 14044 and ISO 21930. When processes produce multiple co-products, inputs and outputs are allocated to the products based on physical relationships (such as mass or energy content) or economic value, depending on data availability and relevance. When neither physical nor economic allocation is possible, system expansion is applied to avoid allocation. Specific allocation details for coproducts are provided within the life cycle inventory documentation.

Cut-off Criteria:

The cut-off criteria applied in this study exclude flows that collectively contribute less than 1% of the total mass, energy, or environmental significance of the product system. All significant inputs and outputs are included. No known flows are deliberately excluded from this EPD.

Health, Safety and Environmental Aspects

This product does not contain hazardous, dangerous, or regulated substances that are known to adversely affect human health or the environment. The product is free from substances that are restricted or subject to specific regulations under applicable health, safety, and environmental legislation. This declaration is made in accordance with ISO 21930:2017 standards for sustainability in building construction.

4. LCA Results

The Life Cycle Assessment (LCA) results for STF products provide a detailed environmental profile from cradle-to-gate. The impact categories and characterization factors are based on the U.S. EPA's TRACI 2.1 methodology. The LCA modelling used SimaPro v9.1 to gather life cycle inventory (LCI) data and calculate the life cycle impact assessment (LCIA) results.

The contribution analysis shows that manufacturing (A3) is the most significant phase, contributing 58.4% to the Global Warming Potential (GWP), followed by transportation (A2) at 23.5%, and raw material production (A1) at 18.0%. The reliance on renewable energy sources and the efficient management of co-products, such as wood chips, align STF products with sustainable production practices. These results provide a transparent understanding of the environmental impact of STF products, promoting their use in sustainable construction and encouraging the adoption of carbon-storing materials in the building sector.

Table 1: LCIA Results Summary for Cradle-to-Gate production of 1 m³ of STF-absolute basis

| Core Mandatory Impact Indicator | Unit | Total | A1 | A2 | A3 |
|---|----------------------|----------|-----------|----------|----------|
| Global warming potential – w/biogenic CO ₂ | kg CO ₂ e | 1.34E+02 | -7.14E+02 | 3.15E+01 | 8.17E+02 |
| Global warming potential – TRACI 2.1 | kg CO ₂ e | 1.34E+02 | 2.41E+01 | 3.15E+01 | 7.89E+01 |
| Acidification potential of soil and water sources | kg SO ₂ e | 2.19E-01 | 2.13E-01 | 2.80E-01 | 2.19E-01 |
| Eutrophication potential | kg Ne | 2.30E-02 | 1.96E-02 | 2.17E-01 | 2.30E-02 |
| Depletion potential of the stratospheric ozone layer | kg CFC11e | 1.12E-09 | 1.32E-06 | 6.84E-07 | 1.12E-09 |
| Formation potential of tropospheric ozone | kg O ₃ e | 4.59E+00 | 6.26E+00 | 6.07E+00 | 4.59E+00 |
| Abiotic depletion potential (ADP _{fossil}) for fossil resources | MJ, NCV | 3.26E+02 | 3.97E+02 | 1.07E+03 | 3.26E+02 |
| Use of Primary Resources | | | | | |
| Renewable primary energy carrier used as energy | MJ, NCV | 7.50E+01 | 0.00E+00 | 1.88E+00 | 7.31E+01 |
| Renewable primary energy carrier used as material | MJ, NCV | 8.15E+03 | 8.15E+03 | 0.00E+00 | 0.00E+00 |

| | | | | | |
|---|--------------------|-----------|-----------|----------|----------|
| Non-renewable primary energy carrier used as energy | MJ, NCV | 2.18E+03 | 3.26E+02 | 4.06E+02 | 1.45E+03 |
| Non-renewable primary energy carrier used as material | MJ, NCV | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Secondary Material, Secondary Fuel, and Recovered Energy | | | | | |
| Secondary material | kg | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Renewable secondary fuel | MJ, NCV | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Non-renewable secondary fuel | MJ, NCV | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Recovered energy | MJ, NCV | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Mandatory Inventory Parameters | | | | | |
| Consumption of freshwater resources | m ³ | 1.29E+01 | 2.69E-02 | 1.24E+01 | 4.08E-01 |
| Indicators Describing Waste | | | | | |
| Hazardous waste disposed | kg | 7.03E-02 | 0.00E+00 | 3.64E-02 | 3.39E-02 |
| Non-hazardous waste disposed | kg | 1.46E+02 | 1.44E+00 | 1.13E+00 | 1.44E+02 |
| High-level radioactive waste | m ³ | 1.94E-07 | 0.00E+00 | 4.99E-09 | 1.89E-07 |
| Intermediate- and low-level radioactive waste | m ³ | 1.71E-06 | 0.00E+00 | 2.39E-08 | 1.68E-06 |
| Components for re-use | kg | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Materials for recycling | kg | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Materials for energy recovery | kg | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Recovered energy exported from the product system | MJ, NCV | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| Additional Inventory Parameters | | | | | |
| Biogenic Carbon Removal from Product | kg CO ₂ | -9.96E+02 | -9.96E+02 | 0.00E+00 | 0.00E+00 |
| Biogenic Carbon Emission from Product | kg CO ₂ | 8.27E+02 | 0.00E+00 | 0.00E+00 | 8.27E+02 |
| Biogenic Carbon Removal from Packaging | kg CO ₂ | -6.80E-01 | -6.80E-01 | 0.00E+00 | 0.00E+00 |

5. LIMITATIONS

Comparability

This study does not include comparative assertions, making it challenging to benchmark STF products against other building materials. To enable meaningful comparisons, system boundaries, allocation methods, and data sources would need to be harmonized, limiting the application of these results for competitive evaluations or market-based comparisons. Environmental declarations from different programs (ISO 14025) may not be comparable. Comparison of the environmental performance of wood products using EPD information shall be based on the product's use and impacts at the construction works level, and therefore EPDs may not be used for comparability purposes when not considering the construction works energy use phase as instructed under this PCR".

Forest Management

The study assumes that North American forests are carbon neutral, meaning there is no net carbon loss due to sustainable forestry practices. However, this assumption may not fully account for regional variations in forest management, changes in land use, or unforeseen environmental events. These factors could affect the actual carbon balance and introduce uncertainty regarding the long-term sustainability of biogenic carbon sequestration.

While this EPD does not address landscape level forest management impacts, potential impacts may be addressed through requirements put forth in regional regulatory frameworks, ASTM 7612-15 guidance, and ISO 21930 Section 7.2.11 including notes therein. These documents, combined with this EPD, may provide a more complete picture of the environmental and social performance of wood products.

EPD Scope

The cradle-to-gate scope limits the EPD by excluding the product's use phase, maintenance, and end-of-life stages. This restricts the report's ability to offer insights into the total environmental performance of STF products in real-world applications.

Accuracy of Results

The accuracy of the results may be affected by the limited sample size, as only eight manufacturing facilities were included. Additionally, the reliance on secondary data for aspects such as transportation and raw material extraction introduces variability. While primary data collection reflects actual production practices, averaging across facilities could mask specific differences, reducing the precision of the environmental impact assessments for individual production sites.

6. REFERENCES

1. Abergel, T.; Dean, B.; Dulac, J. 2017. Towards a zeroemission, efficient, and resilient buildings and construction sector: Global Status Report 2017. Paris, France: UN Environment, International Energy Agency.
2. ULE. 2018. Part A: life cycle assessment calculation rules and report requirements. Washington, DC: UL Environment. 47 p.
3. ULE. 2019. Guidance for building-related products and services: Part b: Structural and architectural wood products EPD requirements. Washington, DC: UL Environment. 31 p.
4. ISO. 2006c. ISO 14044. Environmental management: life cycle assessments: requirements and guidelines. Geneva, Switzerland: International Standardization Organization. 54 p.
5. ISO. 2006b. ISO 14040. Environmental management: life cycle assessment; principles and framework. Geneva, Switzerland: International Organization for Standardization. 28 p.
6. PRé Consultants. 2020. SimaPro 9.5 life-cycle assessment software package, version 9.0. Amersfoort, the Netherlands: PRé Consultants.
7. LTS. 2023. DATASMART LCI package (US-EI SimaPro®Library). Huntington, VT: Long Trail Sustainability. <https://ltsexperts.com/services/software/datasmart-lifecycle-inventory/>.
8. Bare, J. 2011. TRACI 2.1: the tool for the reduction and assessment of chemical and other environmental impacts 2.1. Clean Technologies and Environmental Policy. 13(5): 687-696.
9. ISO. 2017. ISO 21930. Sustainability in buildings and civil engineering works — Core rules for environmental product declarations of construction products and services. Geneva, Switzerland: International Standardization Organization. 90 p.
10. ASTM International. 2022. General Program Instructions for EPDs, Version 8.0. ASTM International, West Conshohocken, PA.